

Package ‘shrinkDSM’

November 15, 2022

Type Package

Title Efficient Bayesian Inference for Dynamic Survival Models with Shrinkage

Version 0.2.0

Description Efficient Markov chain Monte Carlo (MCMC) algorithms for fully Bayesian estimation of dynamic survival models with shrinkage priors. Details on the algorithms used are provided in Wagner (2011) <[doi:10.1007/s11222-009-9164-5](https://doi.org/10.1007/s11222-009-9164-5)>, Bitto and Frühwirth-Schnatter (2019) <[doi:10.1016/j.jeconom.2018.11.006](https://doi.org/10.1016/j.jeconom.2018.11.006)> and Cadonna et al. (2020) <[doi:10.3390/econometrics8020020](https://doi.org/10.3390/econometrics8020020)>.

License GPL (>= 2)

Encoding UTF-8

LazyData true

Depends R (>= 3.3.0),

Imports Rcpp, stochvol (>= 3.0.3), coda, utils, shrinkTVP (>= 2.0.2)

LinkingTo Rcpp, RcppArmadillo, RcppProgress, stochvol, shrinkTVP

RoxygenNote 7.2.1

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation yes

Author Daniel Winkler [aut, cre],
Peter Knaus [aut] (<<https://orcid.org/0000-0001-6498-7084>>)

Maintainer Daniel Winkler <daniel.winkler@wu.ac.at>

Repository CRAN

Date/Publication 2022-11-15 21:20:02 UTC

R topics documented:

divisionpoints	2
gastric	3
plot.mcmc.dsm.tvp	3

plot.shrinkDSM	6
plot.shrinkDSM_pred	8
predict.shrinkDSM	9
prep_tvinput	10
print.shrinkDSM	12
shrinkDSM	13

Index	19
--------------	-----------

divisionpoints	<i>Create division points for estimation of a dynamic survival model</i>
----------------	--

Description

Create a vector of division points for the model. These points mark the times at which the parameters are allowed to evolve, with the parameters being fixed between division points. The points are generated in a data driven fashion, with a new point being created when events number of interesting events have been observed since the last division point.

Usage

```
divisionpoints(times, delta, events = 1)
```

Arguments

times	A vector of real, positive numbers indicating the survival times. For right censored data, this is the follow up time.
delta	A vector of status indicators, with 0 = alive and 1 = dead. Other choices are TRUE/FALSE (TRUE = death) or 1/2 (2 = death).
events	A positive integer indicating the number of interesting events per interval until a new division is created.

Value

Returns an integer vector of time points to be used as division points S in `shrinkDSM`.

Author(s)

Daniel Winkler <daniel.winkler@wu.ac.at>

Examples

```
data("gastric")

# Create intervals for piecewise exponential model
intervals <- divisionpoints(gastric$time, gastric$status, 2)
```

gastric	<i>Survival times of gastric cancer patients</i>
---------	--

Description

A data set of survival times of patients with locally advanced, nonresectable gastric carcinoma. The patients were either treated with chemotherapy plus radiation or chemotherapy alone.

Usage

gastric

Format

A data frame with 90 rows and 4 variables:

id patient id

radiation dummy variable indicating which treatment was employed, 0 = chemotherapy, 1 = combined chemotherapy/radiation

time time survived by patient in days

status dummy variable indicating whether death of the patient was observed, 0 = death not observed (i.e. censored), 1 = death observed.

Source

Moreau, T., O'Quigley, J., and Mesbah M. (1985) A global goodness-of-fit statistic for the proportional hazards model Appl. Statist., 34, 212:218 (p 213)

<https://www.mayo.edu/research/documents/gastrichtml/DOC-10027680>

plot.mcmc.dsm.tvp	<i>Graphical summary of posterior distribution for a piecewise constant, time-varying parameter</i>
-------------------	---

Description

plot.mcmc.dsm.tvp plots empirical posterior quantiles for a piecewise constant, time-varying parameter.

Usage

```
## S3 method for class 'mcmc.dsm.tvp'
plot(
  x,
  probs = c(0.025, 0.25, 0.75, 0.975),
  shaded = TRUE,
  quantlines = FALSE,
  shadecol = "skyblue",
  shadealpha = 0.5,
  quantlty = 2,
  quantcol = "black",
  quantlwd = 0.5,
  drawzero = TRUE,
  zeroqty = 2,
  zerolwd = 1,
  zerocol = "grey",
  ...
)
```

Arguments

x	mcmc.dsm.tvp object
probs	vector of boundaries for credible intervals to plot for each point in time, with values in [0,1]. The largest and smallest value form the outermost credible interval, the second smallest and second largest the second outermost and so forth. The default value is <code>c(0.025, 0.25, 0.75, 0.975)</code> . Note that there have to be the same number of probs < 0.5 as there are > 0.5.
shaded	single logical value or a vector of logical values, indicating whether or not to shade the area between the pointwise credible intervals. If a vector is given, the first value given is used to determine if the area between the outermost credible interval is shaded, the second for the second outermost and so forth. Recycled in the usual fashion if the vector is shorter than the number of quantile pairs. The default value is TRUE.
quantlines	single logical value or a vector of logical values, indicating whether or not to draw borders along the pointwise credible intervals. If a vector is given, the first value given is used to determine whether the outermost credible interval is marked by lines, the second for the second outermost and so forth. Recycled in the usual fashion if the vector is shorter than the number of credible intervals. The default value is FALSE.
shadecol	single character string or a vector of character strings. Determines the color of the shaded areas that represent the credible intervals. If a vector is given, the first color given is used for the outermost area, the second for the second outermost and so forth. Recycled in the usual fashion if the vector is shorter than the number of shaded areas. Has no effect if shaded = FALSE. The default value is "skyblue".
shadealpha	real number between 0 and 1 or a vector of real numbers between 0 and 1. Determines the level of transparency of the shaded areas that represent the credible

	intervals. If a vector is given, the first value given is used for the outermost area, the second for the second outermost and so forth. Recycled in the usual fashion if the vector is shorter than the number of shaded areas. Has no effect if shaded = FALSE. The default value is 0.5.
quantlty	either a single integer in [0,6] or one of the character strings "blank", "solid", "dashed", "dotted", "dotdash", "longdash", "twodash" or a vector containing these. Determines the line type of the borders drawn around the shaded areas that represent the credible intervals. Note that if a vector is supplied the elements have to either be all integers or all character strings. If a vector is given, the first value given is used for the outermost area, the second for the second outermost and so forth. Recycled in the usual fashion if the vector is shorter than the number of shaded areas. Has no effect if quantlines = FALSE. The default value is 2.
quantcol	single character string or a vector of character strings. Determines the color of the borders drawn around the shaded areas that represent the credible intervals. If a vector is given, the first color given is used for borders of the outermost area, the second for the second outermost and so forth. Recycled in the usual fashion if the vector is shorter than the number of shaded areas. Has no effect if quantlines = FALSE. The default value is "black".
quantlwd	single real, positive number or a vector of real, positive numbers. Determines the line width of the borders drawn around the shaded areas that represent the credible intervals. If a vector is given, the first number given is used for the borders of the outermost area, the second for the second outermost and so forth. Recycled in the usual fashion if the vector is shorter than the number of shaded areas. Has no effect if quantlines = FALSE. The default value is 0.5.
drawzero	single logical value determining whether to draw a horizontal line at zero or not. The default value is TRUE.
zerolty	single integer in [0,6] or one of the character strings "blank", "solid", "dashed", "dotted", "dotdash", "longdash", "twodash". Determines the line type of the horizontal line at zero. Has no effect if drawzero = FALSE. The default value is 2.
zerolwd	single real, positive number. Determines the line width of the horizontal line at zero. Has no effect if drawzero = FALSE. The default value is 1.
zerocol	single character string. Determines the color of the horizontal line at zero. Has no effect if drawzero = FALSE. The default value is "grey".
...	further arguments to be passed to plot.

Value

Called for its side effects and returns invisibly.

Author(s)

Peter Knaus <peter.knaus@wu.ac.at>

See Also

Other plotting functions: [plot.shrinkDSM_pred\(\)](#), [plot.shrinkDSM\(\)](#)

Examples

```

set.seed(123)
data("gastric")

# Create intervals for piecewise exponential model
intervals <- divisionpoints(gastric$time, gastric$status, 2)

# Estimate model
mod <- shrinkDSM(time ~ radiation, gastric,
                 delta = gastric$status, S = intervals)

# Plot piecewise constant, time-varying parameter
plot(mod$beta$beta_radiation)

```

plot.shrinkDSM	<i>Graphical summary of posterior distribution of fitted dynamic survival model</i>
----------------	---

Description

plot.shrinkDSM generates plots visualizing the posterior distribution estimated as a result from a call to shrinkDSM.

Usage

```

## S3 method for class 'shrinkDSM'
plot(
  x,
  pars = c("beta"),
  nplot = 3,
  h_borders = c(0.05, 0.05),
  w_borders = c(0.02, 0.02),
  ...
)

```

Arguments

x	a shrinkDSM object.
pars	a character vector containing the names of the parameters to be visualized. The names have to coincide with the names of the list elements of the shrinkDSM object. Throws an error if any element of pars does not fulfill this criterium. The default is c("beta").
nplot	positive integer that indicates the number of tvp plots to display on a single page before a new page is generated. The default value is 3.

h_borders	single real, positive number smaller than 0.5 or a vector containing two such numbers. Determines the relative amount of space (the total amount summing up to 1) left blank on the left and right of the plot, in that order. The default is <code>c(0.05, 0.05)</code> .
w_borders	single real, positive number smaller than 0.5 or a vector containing two such numbers. Determines the relative amount of space (the total amount summing up to 1) left blank at the top and bottom of the plot, in that order. The default is <code>c(0.02, 0.02)</code> .
...	further arguments to be passed to the respective plotting functions.

Value

Called for its side effects and returns invisibly.

Author(s)

Peter Knaus <peter.knaus@wu.ac.at>

See Also

Other plotting functions: [plot.mcmc.dsm.tvp\(\)](#), [plot.shrinkDSM_pred\(\)](#)

Examples

```
set.seed(123)
data("gastric")

# Create intervals for piecewise exponential model
intervals <- divisionpoints(gastric$time, gastric$status, 2)

# Estimate model
mod <- shrinkDSM(time ~ radiation, gastric,
                 delta = gastric$status, S = intervals)
plot(mod)

# Will produce an error because 'hello' is not a parameter in the model
## Not run:
plot(mod, pars = c("beta", "hello"))

## End(Not run)
```

plot.shrinkDSM_pred *Graphical summary of posterior predictive density*

Description

plot.shrinkDSM_pred generates plots visualizing the posterior predictive density generated by predict.shrinkDSM.

Usage

```
## S3 method for class 'shrinkDSM_pred'  
plot(x, dens_args, legend = TRUE, ...)
```

Arguments

x	a shrinkDSM_pred object.
dens_args	<i>optional</i> named list containing arguments passed to density.
legend	logical value indicating whether a legend should be added. Defaults to TRUE.
...	further arguments to be passed to plots.

Value

Called for its side effects and returns invisibly.

See Also

Other plotting functions: [plot.mcmc.dsm.tvp\(\)](#), [plot.shrinkDSM\(\)](#)

Examples

```
set.seed(123)  
data("gastric")  
  
# Create intervals for piecewise exponential model  
intervals <- divisionpoints(gastric$time, gastric$status, 2)  
  
# Estimate model  
mod <- shrinkDSM(time ~ radiation, gastric,  
                 delta = gastric$status, S = intervals)  
  
# Draw from posterior predictive distribution  
newdata <- data.frame(radiation = c(0, 1))  
pred <- predict(mod, newdata = newdata)  
  
# Plot predictions  
plot(pred)
```



```
# Draw from posterior predictive distribution
newdata <- data.frame(radiation = c(0, 1))
pred <- predict(mod, newdata = newdata)
```

prep_tvinput	<i>Prepare time-varying inputs for estimation of a dynamic survival model</i>
--------------	---

Description

This function pre-processes time-varying inputs in such a way that shrinkDSM can work with time-varying inputs. Its main inputs are two data frames, namely `surv_data` and `covariate_data`. `surv_data` contains meta data about each observation (i.e. survival time and censoring indicator), while `covariate_data` contains the time-varying covariates (one per observation and time interval) and an index for which time interval each covariate is observed in. The two are merged together via an ID that needs to be unique for each observation and present in both `surv_data` and `covariate_data`.

Usage

```
prep_tvinput(
  surv_data,
  covariate_data,
  id_var,
  surv_var,
  delta_var,
  interval_var,
  covariate_id_var = id_var
)
```

Arguments

<code>surv_data</code>	data frame containing meta-data for each observation (survival time and censoring indicator) as well as an ID for each observation.
<code>covariate_data</code>	data frame containing the time-varying covariates (one per observation and time interval), an index for which time interval each covariate is observed in as well as an ID for each observation.
<code>id_var</code>	character string specifying the column name of the ID variable. If the name is different in <code>surv_data</code> and <code>covariate_data</code> , <code>id_var</code> will be used in <code>surv_data</code> , whereas <code>covariate_id_var</code> will be used in <code>covariate_data</code> .
<code>surv_var</code>	character string specifying the column name of the survival times in <code>surv_data</code> .
<code>delta_var</code>	character string specifying the column name of the status indicators in <code>surv_data</code> , 0 = censored or 1 = event observed..
<code>interval_var</code>	character string specifying the column name of the time interval ID in <code>covariate_data</code> .
<code>covariate_id_var</code>	character string specifying the column name of the ID variable in <code>covariate_data</code> . Defaults to <code>id_var</code> .

Value

Returns an object of class `data.frame` and `tvsvrv` to be used as an input in `shrinkDSM`.

Author(s)

Daniel Winkler <daniel.winkler@wu.ac.at>

Peter Knaus <peter.knaus@wu.ac.at>

Examples

```
# A toy example with 5 observations and 2 covariates, observed over 3 time periods
set.seed(123)
n_obs <- 5
surv_var <- round(rgamma(n_obs, 1, .1)) + 1
delta_var <- sample(size = n_obs, c(0, 1), prob = c(0.2, 0.8), replace = TRUE)

surv_data <- data.frame(id_var = 1:n_obs, surv_var, delta_var)

# Determine intervals
S <- c(3, 11)

# Create synthetic observations for each individual
covariate_list <- list()

for (i in 1:n_obs) {
  nr_periods_survived <- sum(surv_var[i] > S) + 1
  covariate_list[[i]] <- data.frame(id_var = i,
                                   interval_var = 1:nr_periods_survived,
                                   x1 = rnorm(nr_periods_survived),
                                   x2 = rnorm(nr_periods_survived))
}

# Bind all individual covariate data frames together
# Each observation now has a covariate in each period they
# were observed in.
covariate_data <- do.call(rbind, covariate_list)

# Call prep_tvinput to pre-process for shrinkDSM
merged_data <- prep_tvinput(surv_data,
                           covariate_data,
                           id_var = "id_var",
                           surv_var = "surv_var",
                           delta_var = "delta_var",
                           interval_var = "interval_var")

# Can now be used in shrinkDSM
# Note that delta is now automatically extracted from merged_data,
# providing it will throw a warning
mod <- shrinkDSM(surv_var ~ x1 + x2, merged_data, S = S)
```

`print.shrinkDSM` *Nicer printing of shrinkDSM objects*

Description

Nicer printing of shrinkDSM objects

Usage

```
## S3 method for class 'shrinkDSM'  
print(x, ...)
```

Arguments

<code>x</code>	a shrinkDSM object.
<code>...</code>	Currently ignored.

Value

Called for its side effects and returns invisibly.

Author(s)

Peter Knaus <peter.knaus@wu.ac.at>

Examples

```
set.seed(123)  
data("gastric")  
  
# Create intervals for piecewise exponential model  
intervals <- divisionpoints(gastric$time, gastric$status, 2)  
  
# Estimate model  
mod <- shrinkDSM(time ~ radiation, gastric,  
                 delta = gastric$status, S = intervals)  
  
# Print  
print(mod)  
  
# Alternatively  
mod
```

shrinkDSM	<i>Markov Chain Monte Carlo (MCMC) for time-varying parameter survival models with shrinkage</i>
-----------	--

Description

shrinkDSM samples from the joint posterior distribution of the parameters of a time-varying parameter survival model with shrinkage and returns the MCMC draws. See also [shrinkTVP](#) to see more examples of how to modify the prior setup of the time-varying component of the model.

Usage

```
shrinkDSM(
  formula,
  data,
  mod_type = "double",
  delta,
  S,
  group,
  subset,
  niter = 10000,
  nburn = round(niter/2),
  nthin = 1,
  learn_a_xi = TRUE,
  learn_a_tau = TRUE,
  a_xi = 0.1,
  a_tau = 0.1,
  learn_c_xi = TRUE,
  learn_c_tau = TRUE,
  c_xi = 0.1,
  c_tau = 0.1,
  a_eq_c_xi = FALSE,
  a_eq_c_tau = FALSE,
  learn_kappa2_B = TRUE,
  learn_lambda2_B = TRUE,
  kappa2_B = 20,
  lambda2_B = 20,
  hyperprior_param,
  sv_param,
  MH_tuning,
  phi_param,
  display_progress = TRUE
)
```

Arguments

formula	an object of class "formula": a symbolic representation of the model, as in the function <code>lm</code> . For details, see formula .
---------	---

data	<i>optional</i> data frame containing the response variable and the covariates. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>shrinkDSM</code> is called. No NAs are allowed in the response variable and the covariates.
mod_type	character string that reads either "triple", "double" or "ridge". Determines whether the triple gamma, double gamma or ridge prior are used for <code>theta_sr</code> and <code>beta_mean</code> . The default is "double".
delta	The status indicator of the last period, 0 = censored or 1 = event observed.
S	integer vector of time points that start a new interval. Parameters are fixed within an interval and vary across intervals.
group	<i>optional</i> grouping indicator for latent factor.
subset	<i>optional</i> vector specifying a subset of observations to be used in the fitting process.
niter	positive integer, indicating the number of MCMC iterations to perform, including the burn-in. Has to be larger than or equal to <code>nburn + 2</code> . The default value is 10000.
nburn	non-negative integer, indicating the number of iterations discarded as burn-in. Has to be smaller than or equal to <code>niter - 2</code> . The default value is <code>round(niter / 2)</code> .
nthin	positive integer, indicating the degree of thinning to be performed. Every <code>nthin</code> draw is kept and returned. The default value is 1, implying that every draw is kept.
learn_a_xi	logical value indicating whether to learn <code>a_xi</code> , the spike parameter of the state variances. The default value is TRUE.
learn_a_tau	logical value indicating whether to learn <code>a_tau</code> , the spike parameter of the mean of the initial values of the states. The default value is TRUE.
a_xi	positive, real number, indicating the (fixed) value for <code>a_xi</code> . Ignored if <code>learn_a_xi</code> is TRUE or <code>mod_type</code> is set to "ridge". The default value is 0.1.
a_tau	positive, real number, indicating the (fixed) value for <code>a_tau</code> . Ignored if <code>learn_a_tau</code> is TRUE or <code>mod_type</code> is set to "ridge". The default value is 0.1.
learn_c_xi	logical value indicating whether to learn <code>c_xi</code> , the tail parameter of the state variances. Ignored if <code>mod_type</code> is not set to "triple" or <code>a_eq_c_xi</code> is set to TRUE. The default value is TRUE.
learn_c_tau	logical value indicating whether to learn <code>c_tau</code> , the tail parameter of the mean of the initial values of the states. Ignored if <code>mod_type</code> is not set to "triple" or <code>a_eq_c_tau</code> is set to TRUE. The default value is TRUE.
c_xi	positive, real number, indicating the (fixed) value for <code>c_xi</code> . Ignored if <code>learn_c_xi</code> is TRUE, <code>mod_type</code> is not set to "triple" or <code>a_eq_c_xi</code> is set to TRUE. The default value is 0.1.
c_tau	positive, real number, indicating the (fixed) value for <code>c_tau</code> . Ignored if <code>learn_c_xi</code> is TRUE, <code>mod_type</code> is not set to "triple" or <code>a_eq_c_tau</code> is set to TRUE. The default value is 0.1.

<code>a_eq_c_xi</code>	logical value indicating whether to force <code>a_xi</code> and <code>c_xi</code> to be equal. If set to TRUE, <code>beta_a_xi</code> and <code>alpha_a_xi</code> are used as the hyperparameters and <code>beta_c_xi</code> and <code>alpha_c_xi</code> are ignored. Ignored if <code>mod_type</code> is not set to "triple". The default value is FALSE.
<code>a_eq_c_tau</code>	logical value indicating whether to force <code>a_tau</code> and <code>c_tau</code> to be equal. If set to TRUE, <code>beta_a_tau</code> and <code>alpha_a_tau</code> are used as the hyperparameters and <code>beta_c_tau</code> and <code>alpha_c_tau</code> are ignored. Ignored if <code>mod_type</code> is not set to "triple". The default value is FALSE.
<code>learn_kappa2_B</code>	logical value indicating whether to learn <code>kappa2_B</code> , the global level of shrinkage for the state variances. The default value is TRUE.
<code>learn_lambda2_B</code>	logical value indicating whether to learn the <code>lambda2_B</code> parameter, the global level of shrinkage for the mean of the initial values of the states. The default value is TRUE.
<code>kappa2_B</code>	positive, real number. Initial value of <code>kappa2_B</code> . The default value is 20.
<code>lambda2_B</code>	positive, real number. Initial value of <code>lambda2_B</code> . The default value is
<code>hyperprior_param</code>	<p><i>optional</i> named list containing hyperparameter values. Not all have to be supplied, with those missing being replaced by the default values. Any list elements that are misnamed will be ignored and a warning will be thrown. All hyperparameter values have to be positive, real numbers. The following hyperparameters can be supplied:</p> <ul style="list-style-type: none"> • <code>e1</code>: The default value is 0.001. • <code>e2</code>: The default value is 0.001. • <code>d1</code>: The default value is 0.001. • <code>d2</code>: The default value is 0.001. • <code>beta_a_xi</code>: The default value is 10. • <code>beta_a_tau</code>: The default value is 10. • <code>alpha_a_xi</code>: The default value is 5. • <code>alpha_a_tau</code>: The default value is 5.
<code>sv_param</code>	<p><i>optional</i> named list containing hyperparameter values for the stochastic volatility parameters. Not all have to be supplied, with those missing being replaced by the default values. Any list elements that are misnamed will be ignored and a warning will be thrown. Ignored if <code>group</code> is missing. The following elements can be supplied:</p> <ul style="list-style-type: none"> • <code>Bsigma_sv</code>: positive, real number. The default value is 1. • <code>a0_sv</code>: positive, real number. The default value is 5. • <code>b0_sv</code>: positive, real number. The default value is 1.5.
<code>MH_tuning</code>	<p><i>optional</i> named list containing values used to tune the MH steps for <code>a_xi</code> and <code>a_tau</code>. Not all have to be supplied, with those missing being replaced by the default values. Any list elements that are misnamed will be ignored and a warning will be thrown. The arguments for <code>a_xi(a_tau)</code> are only used if <code>learn_a_xi(learn_a_tau)</code> is set to TRUE. Arguments ending in "adaptive" are logical values indicating whether or not to make the MH step for the respective parameter adaptive. Arguments ending in "tuning_par" serve two different</p>

purposes. If the respective MH step is not set to be adaptive, it acts as the standard deviation of the proposal distribution. If the respective MH step is set to be adaptive, it acts as the initial standard deviation. Arguments ending in "target_rate" define the acceptance rate the algorithm aims to achieve. Arguments ending in "max_adapt" set the maximum value by which the logarithm of the standard deviation of the proposal distribution is adjusted. Finally, arguments ending in "batch_size" set the batch size after which the standard deviation of the proposal distribution is adjusted. The following elements can be supplied:

- a_xi_adaptive: logical value. The default is TRUE.
- a_xi_tuning_par: positive, real number. The default value is 1.
- a_xi_target_rate: positive, real number, between 0 and 1. The default value is 0.44.
- a_xi_max_adapt: positive, real number. The default value is 0.01.
- a_xi_batch_size: positive integer. The default value is 50.
- a_tau_adaptive: logical value. The default is TRUE.
- a_tau_tuning_par: positive, real number. The default value is 1.
- a_tau_target_rate: positive, real number, between 0 and 1. The default value is 0.44.
- a_tau_max_adapt: positive, real number. The default value is 0.01.
- a_tau_batch_size: positive integer. The default value is 50.

phi_param

optional named list containing hyperparameter values for the grouped factor and values to tune the MH steps for a_phi and c_phi. Not all have to be supplied, with those missing being replaced by the default values. Any list elements that are misnamed will be ignored and a warning will be thrown. Ignored if group is missing. The following elements can be supplied:

- mod_type_phi character string that reads either "triple", "double" or "ridge". Determines whether the triple gamma, double gamma or ridge prior are used for phi. The default is "double".
- learn_a_phi: logical value. The default is TRUE.
- a_phi: positive, real number. The default value is 0.1.
- learn_c_phi: logical value. The default is TRUE.
- c_phi: positive, real number. The default value is 0.1,
- a_phi_eq_c_phi: logical value. The default is FALSE.
- learn_lambda2_B_phi: logical value. The default is TRUE.
- lambda2_B_phi: positive, real number. The default value is 20.
- e1_phi: positive, real number. The default value is 0.001.
- e2_phi: positive, real number. The default value is 0.001.
- beta_a_phi: positive, real number. The default value is 10.
- alpha_a_phi: positive, real number. The default value is 5.
- beta_c_phi: positive, real number. The default value is 10.
- alpha_c_phi: positive, real number. The default value is 5.
- a_phi_adaptive: logical value. The default is TRUE.
- a_phi_tuning_par: positive, real number. The default value is 1.

- `a_phi_target_rate`: positive, real number, between 0 and 1. The default value is 0.44.
- `a_phi_max_adapt`: positive, real number. The default value is 0.01.
- `a_phi_batch_size`: positive integer. The default value is 50.
- `c_phi_adaptive`: logical value. The default is TRUE.
- `c_phi_tuning_par`: positive, real number. The default value is 1.
- `c_phi_target_rate`: positive, real number, between 0 and 1. The default value is 0.44.
- `c_phi_max_adapt`: positive, real number. The default value is 0.01.
- `c_phi_batch_size`: positive integer. The default value is 50.

`display_progress`

logical value indicating whether the progress bar and other informative output should be displayed. The default value is TRUE.

Value

The value returned is a list object of class `shrinkDSM` containing

<code>beta</code>	list object containing an <code>mcmc.dsm.tvp</code> object for the parameter draws from the posterior distribution of the centered states, one for each covariate. In the case that there is only one covariate, this becomes just a single <code>mcmc.dsm.tvp</code> object.
<code>beta_mean</code>	<code>mcmc</code> object containing the parameter draws from the posterior distribution of <code>beta_mean</code> .
<code>theta_sr</code>	<code>mcmc</code> object containing the parameter draws from the posterior distribution of the square root of <code>theta</code> .
<code>tau2</code>	<code>mcmc</code> object containing the parameter draws from the posterior distribution of <code>tau2</code> .
<code>xi2</code>	<code>mcmc</code> object containing the parameter draws from the posterior distribution of <code>xi2</code> .
<code>lambda2</code>	<i>(optional)</i> <code>mcmc</code> object containing the parameter draws from the posterior distribution of <code>lambda2</code> . Not returned if <code>mod_type</code> is not "triple".
<code>kappa2</code>	<i>(optional)</i> <code>mcmc</code> object containing the parameter draws from the posterior distribution of <code>kappa2</code> . Not returned if <code>mod_type</code> is not "triple".
<code>a_xi</code>	<i>(optional)</i> <code>mcmc</code> object containing the parameter draws from the posterior distribution of <code>a_xi</code> . Not returned if <code>learn_a_xi</code> is FALSE or <code>mod_type</code> is "ridge".
<code>a_tau</code>	<i>(optional)</i> <code>mcmc</code> object containing the parameter draws from the posterior distribution of <code>a_tau</code> . Not returned if <code>learn_a_tau</code> is FALSE or <code>mod_type</code> is "ridge".
<code>c_xi</code>	<i>(optional)</i> <code>mcmc</code> object containing the parameter draws from the posterior distribution of <code>c_xi</code> . Not returned if <code>learn_c_xi</code> is FALSE or <code>mod_type</code> is not "triple".
<code>c_tau</code>	<i>(optional)</i> <code>mcmc</code> object containing the parameter draws from the posterior distribution of <code>c_tau</code> . Not returned if <code>learn_c_tau</code> is FALSE or <code>mod_type</code> is not "triple".

Index

* **datasets**

gastric, [3](#)

* **plotting functions**

plot.mcmc.dsm.tvp, [3](#)

plot.shrinkDSM, [6](#)

plot.shrinkDSM_pred, [8](#)

* **prediction functions**

predict.shrinkDSM, [9](#)

divisionpoints, [2](#)

formula, [13](#)

gastric, [3](#)

plot.mcmc.dsm.tvp, [3](#), [7](#), [8](#)

plot.shrinkDSM, [5](#), [6](#), [8](#)

plot.shrinkDSM_pred, [5](#), [7](#), [8](#)

predict.shrinkDSM, [9](#)

prep_tvinput, [10](#)

print.shrinkDSM, [12](#)

shrinkDSM, [13](#)

shrinkTVP, [13](#)