

# Package ‘tidytext’

April 10, 2024

**Type** Package

**Title** Text Mining using 'dplyr', 'ggplot2', and Other Tidy Tools

**Version** 0.4.2

**Description** Using tidy data principles can make many text mining tasks easier, more effective, and consistent with tools already in wide use. Much of the infrastructure needed for text mining with tidy data frames already exists in packages like 'dplyr', 'broom', 'tidyr', and 'ggplot2'. In this package, we provide functions and supporting data sets to allow conversion of text to and from tidy formats, and to switch seamlessly between tidy tools and existing text mining packages.

**License** MIT + file LICENSE

**URL** <https://juliasilge.github.io/tidytext/>,  
<https://github.com/juliasilge/tidytext>

**BugReports** <https://github.com/juliasilge/tidytext/issues>

**Depends** R (>= 2.10)

**Imports** cli, dplyr (>= 1.1.1), generics, janeaustenr, lifecycle, Matrix, methods, purrr (>= 0.1.1), rlang (>= 0.4.10), stringr, tibble, tokenizers, vctrs

**Suggests** broom, covr, data.table, ggplot2, hunspell, knitr, mallet, NLP, quanteda, readr, reshape2, rmarkdown, scales, stm, stopwords, testthat (>= 2.1.0), textdata, tidyr, tm, topicmodels, vdiff, wordcloud

**VignetteBuilder** knitr

**Config/Needs/website** ropensci/gutenbergr

**Config/testthat/edition** 3

**Encoding** UTF-8

**LazyData** TRUE

**RoxygenNote** 7.3.1

**NeedsCompilation** no

**Author** Gabriela De Queiroz [ctb],  
 Colin Fay [ctb] (<<https://orcid.org/0000-0001-7343-1846>>),  
 Emil Hvitfeldt [ctb],  
 Os Keyes [ctb] (<<https://orcid.org/0000-0001-5196-609X>>),  
 Kanishka Misra [ctb],  
 Tim Mastny [ctb],  
 Jeff Erickson [ctb],  
 David Robinson [aut],  
 Julia Silge [aut, cre] (<<https://orcid.org/0000-0002-3671-836X>>)

**Maintainer** Julia Silge <julia.silge@gmail.com>

**Repository** CRAN

**Date/Publication** 2024-04-10 12:50:06 UTC

## R topics documented:

bind_tf_idf . . . . .	3
cast_sparse . . . . .	4
cast_tdm . . . . .	5
corpus_tidiers . . . . .	5
dictionary_tidiers . . . . .	6
get_sentiments . . . . .	7
get_stopwords . . . . .	8
lda_tidiers . . . . .	8
mallet_tidiers . . . . .	11
nma_words . . . . .	13
parts_of_speech . . . . .	13
reorder_within . . . . .	14
sentiments . . . . .	16
stm_tidiers . . . . .	16
stop_words . . . . .	19
tdm_tidiers . . . . .	19
tidy.Corpus . . . . .	20
tidy_triplet . . . . .	21
unnest_characters . . . . .	22
unnest_ngrams . . . . .	23
unnest_ptb . . . . .	25
unnest_regex . . . . .	27
unnest_sentences . . . . .	28
unnest_tokens . . . . .	30

**Index** 33

---

bind_tf_idf	<i>Bind the term frequency and inverse document frequency of a tidy text dataset to the dataset</i>
-------------	---

---

### Description

Calculate and bind the term frequency and inverse document frequency of a tidy text dataset, along with the product, tf-idf, to the dataset. Each of these values are added as columns. This function supports non-standard evaluation through the tidyeval framework.

### Usage

```
bind_tf_idf(tbl, term, document, n)
```

### Arguments

tbl	A tidy text dataset with one-row-per-term-per-document
term	Column containing terms as string or symbol
document	Column containing document IDs as string or symbol
n	Column containing document-term counts as string or symbol

### Details

The arguments `term`, `document`, and `n` are passed by expression and support [quasiquotation](#); you can unquote strings and symbols.

If the dataset is grouped, the groups are ignored but are retained.

The dataset must have exactly one row per document-term combination for this to work.

### Examples

```
library(dplyr)
library(janeaustenr)

book_words <- austen_books() %>%
  unnest_tokens(word, text) %>%
  count(book, word, sort = TRUE)

book_words

# find the words most distinctive to each document
book_words %>%
  bind_tf_idf(word, book, n) %>%
  arrange(desc(tf_idf))
```

---

cast_sparse	<i>Create a sparse matrix from row names, column names, and values in a table.</i>
-------------	--

---

## Description

This function supports non-standard evaluation through the tidyeval framework.

## Usage

```
cast_sparse(data, row, column, value, ...)
```

## Arguments

data	A tbl
row	Column name to use as row names in sparse matrix, as string or symbol
column	Column name to use as column names in sparse matrix, as string or symbol
value	Column name to use as sparse matrix values (default 1) as string or symbol
...	Extra arguments to pass on to <code>sparseMatrix()</code>

## Details

Note that `cast_sparse` ignores groups in a grouped `tbl_df`. The arguments `row`, `column`, and `value` are passed by expression and support [quasiquote](#); you can unquote strings and symbols.

## Value

A sparse Matrix object, with one row for each unique value in the `row` column, one column for each unique value in the `column` column, and with as many non-zero values as there are rows in `data`.

## Examples

```
dat <- data.frame(a = c("row1", "row1", "row2", "row2", "row2"),
                 b = c("col1", "col2", "col1", "col3", "col4"),
                 val = 1:5)

cast_sparse(dat, a, b)

cast_sparse(dat, a, b, val)
```

---

cast_tdm	<i> Casting a data frame to a DocumentTermMatrix, TermDocumentMatrix, or dfm </i>
----------	---

---

### Description

This turns a "tidy" one-term-per-document-per-row data frame into a DocumentTermMatrix or TermDocumentMatrix from the tm package, or a dfm from the quanteda package. These functions support non-standard evaluation through the tidyeval framework. Groups are ignored.

### Usage

```
cast_tdm(data, term, document, value, weighting = tm::weightTf, ...)
```

```
cast_dtm(data, document, term, value, weighting = tm::weightTf, ...)
```

```
cast_dfm(data, document, term, value, ...)
```

### Arguments

data	Table with one-term-per-document-per-row
term	Column containing terms as string or symbol
document	Column containing document IDs as string or symbol
value	Column containing values as string or symbol
weighting	The weighting function for the DTM/TDM (default is term-frequency, effectively unweighted)
...	Extra arguments passed on to <a href="#">sparseMatrix()</a>

### Details

The arguments term, document, and value are passed by expression and support [quasiquote](#); you can unquote strings and symbols.

---

corpus_tidiers	<i> Tidiers for a corpus object from the quanteda package </i>
----------------	--

---

### Description

Tidy a corpus object from the quanteda package. tidy returns a tbl\_df with one-row-per-document, with a text column containing the document's text, and one column for each document-level metadata. glance returns a one-row tbl\_df with corpus-level metadata, such as source and created. For Corpus objects from the tm package, see [tidy.Corporus\(\)](#).

**Usage**

```
## S3 method for class 'corpus'  
tidy(x, ...)  
  
## S3 method for class 'corpus'  
glance(x, ...)
```

**Arguments**

x	A Corpus object, such as a VCorpus or PCorpus
...	Extra arguments, not used

**Details**

For the most part, the `tidy` output is equivalent to the "documents" data frame in the corpus object, except that it is converted to a `tbl_df`, and `texts` column is renamed to `text` to be consistent with other uses in `tidytext`.

Similarly, the `glance` output is simply the "metadata" object, with `NULL` fields removed and turned into a one-row `tbl_df`.

**Examples**

```
if (requireNamespace("quanteda", quietly = TRUE)) {  
  data("data_corpus_inaugural", package = "quanteda")  
  
  data_corpus_inaugural  
  
  tidy(data_corpus_inaugural)  
}
```

---

dictionary\_tidiers      *Tidy dictionary objects from the quanteda package*

---

**Description**

Tidy dictionary objects from the `quanteda` package

**Usage**

```
## S3 method for class 'dictionary2'  
tidy(x, regex = FALSE, ...)
```

**Arguments**

x	A dictionary object
regex	Whether to turn dictionary items from a glob to a regex
...	Extra arguments, not used

**Value**

A data frame with two columns: category and word.

---

get_sentiments	<i>Get a tidy data frame of a single sentiment lexicon</i>
----------------	--

---

**Description**

Get specific sentiment lexicons in a tidy format, with one row per word, in a form that can be joined with a one-word-per-row dataset. The "bing" option comes from the included [sentiments\(\)](#) data frame, and others call the relevant function in the **textdata** package.

**Usage**

```
get_sentiments(lexicon = c("bing", "afinn", "loughran", "nrc"))
```

**Arguments**

lexicon	The sentiment lexicon to retrieve; either "afinn", "bing", "nrc", or "loughran"
---------	---

**Value**

A `tbl_df` with a word column, and either a sentiment column (if lexicon is not "afinn") or a numeric value column (if lexicon is "afinn").

**Examples**

```
library(dplyr)

get_sentiments("bing")

## Not run:
get_sentiments("afinn")
get_sentiments("nrc")

## End(Not run)
```

---

get_stopwords	<i>Get a tidy data frame of a single stopword lexicon</i>
---------------	---

---

### Description

Get a specific stop word lexicon via the **stopwords** package's [stopwords](#) function, in a tidy format with one word per row.

### Usage

```
get_stopwords(language = "en", source = "snowball")
```

### Arguments

language	The language of the stopword lexicon specified as a two-letter ISO code, such as "es", "de", or "fr". Default is "en" for English. Use <a href="#">stopwords_getlanguages</a> from <b>stopwords</b> to see available languages.
source	The source of the stopword lexicon specified. Default is "snowball". Use <a href="#">stopwords_getsources</a> from <b>stopwords</b> to see available sources.

### Value

A tibble with two columns, word and lexicon. The parameter lexicon is "quanteda" in this case.

### Examples

```
library(dplyr)
get_stopwords()
get_stopwords(source = "smart")
get_stopwords("es", "snowball")
get_stopwords("ru", "snowball")
```

---

lda_tidiers	<i>Tidiers for LDA and CTM objects from the topicmodels package</i>
-------------	---

---

### Description

Tidy the results of a Latent Dirichlet Allocation or Correlated Topic Model.



**Usage**

```
## S3 method for class 'LDA'
tidy(x, matrix = c("beta", "gamma"), log = FALSE, ...)

## S3 method for class 'CTM'
tidy(x, matrix = c("beta", "gamma"), log = FALSE, ...)

## S3 method for class 'LDA'
augment(x, data, ...)

## S3 method for class 'CTM'
augment(x, data, ...)

## S3 method for class 'LDA'
glance(x, ...)

## S3 method for class 'CTM'
glance(x, ...)
```

**Arguments**

x	An LDA or CTM (or LDA_VEM/CTA_VEM) object from the topicmodels package
matrix	Whether to tidy the beta (per-term-per-topic, default) or gamma (per-document-per-topic) matrix
log	Whether beta/gamma should be on a log scale, default FALSE
...	Extra arguments, not used
data	For augment, the data given to the LDA or CTM function, either as a DocumentTermMatrix or as a tidied table with "document" and "term" columns

**Value**

tidy returns a tidied version of either the beta or gamma matrix.

If `matrix == "beta"` (default), returns a table with one row per topic and term, with columns

**topic** Topic, as an integer

**term** Term

**beta** Probability of a term generated from a topic according to the multinomial model

If `matrix == "gamma"`, returns a table with one row per topic and document, with columns

**topic** Topic, as an integer

**document** Document name or ID

**gamma** Probability of topic given document

augment returns a table with one row per original document-term pair, such as is returned by [tdm\\_tidiers](#):

**document** Name of document (if present), or index

**term** Term

**.topic** Topic assignment

If the data argument is provided, any columns in the original data are included, combined based on the document and term columns.

glance always returns a one-row table, with columns

**iter** Number of iterations used

**terms** Number of terms in the model

**alpha** If an LDA\_VEM, the parameter of the Dirichlet distribution for topics over documents

## Examples

```
if (requireNamespace("topicmodels", quietly = TRUE)) {
  set.seed(2016)
  library(dplyr)
  library(topicmodels)

  data("AssociatedPress", package = "topicmodels")
  ap <- AssociatedPress[1:100, ]
  lda <- LDA(ap, control = list(alpha = 0.1), k = 4)

  # get term distribution within each topic
  td_lda <- tidy(lda)
  td_lda

  library(ggplot2)

  # visualize the top terms within each topic
  td_lda_filtered <- td_lda %>%
    filter(beta > .004) %>%
    mutate(term = reorder(term, beta))

  ggplot(td_lda_filtered, aes(term, beta)) +
    geom_bar(stat = "identity") +
    facet_wrap(~ topic, scales = "free") +
    theme(axis.text.x = element_text(angle = 90, size = 15))

  # get classification of each document
  td_lda_docs <- tidy(lda, matrix = "gamma")
  td_lda_docs

  doc_classes <- td_lda_docs %>%
    group_by(document) %>%
    top_n(1) %>%
    ungroup()

  doc_classes
```

```

# which were we most uncertain about?
doc_classes %>%
  arrange(gamma)
}

```

---

mallet\_tidiers

*Tidiers for Latent Dirichlet Allocation models from the mallet package*


---

## Description

Tidy LDA models fit by the mallet package, which wraps the Mallet topic modeling package in Java. The arguments and return values are similar to `lda_tidiers()`.

## Usage

```

## S3 method for class 'jobjRef'
tidy(
  x,
  matrix = c("beta", "gamma"),
  log = FALSE,
  normalized = TRUE,
  smoothed = TRUE,
  ...
)

## S3 method for class 'jobjRef'
augment(x, data, ...)

```

## Arguments

<code>x</code>	A <code>jobjRef</code> object, of type <code>RTopicModel</code> , such as created by <code>mallet::MalletLDA()</code> .
<code>matrix</code>	Whether to tidy the beta (per-term-per-topic, default) or gamma (per-document-per-topic) matrix.
<code>log</code>	Whether beta/gamma should be on a log scale, default <code>FALSE</code>
<code>normalized</code>	If true (default), normalize so that each document or word sums to one across the topics. If false, values will be integers representing the actual number of word-topic or document-topic assignments.
<code>smoothed</code>	If true (default), add the smoothing parameter to each to avoid any values being zero. This smoothing parameter is initialized as <code>alpha.sum</code> in <code>mallet::MalletLDA()</code> .
<code>...</code>	Extra arguments, not used
<code>data</code>	For <code>augment</code> , the data given to the LDA function, either as a <code>DocumentTermMatrix</code> or as a tidied table with "document" and "term" columns.

## Details

Note that the LDA models from `mallet::MalletLDA()` are technically a special case of S4 objects with class `jobjRef`. These are thus implemented as `jobjRef` tidiers, with a check for whether the `toString` output is as expected.

## Value

argument must be provided a data argument containing one row per original document-term pair, such as is returned by `t dm_tidiers`, containing columns `document` and `term`. It returns that same data with an additional column `.topic` with the topic assignment for that document-term combination.

## See Also

`lda_tidiers()`, `mallet::mallet.doc.topics()`, `mallet::mallet.topic.words()`

## Examples

```
## Not run:
library(mallet)
library(dplyr)

data("AssociatedPress", package = "topicmodels")
td <- tidy(AssociatedPress)

# mallet needs a file with stop words
tmp <- tempfile()
writeLines(stop_words$word, tmp)

# two vectors: one with document IDs, one with text
docs <- td %>%
  group_by(document = as.character(document)) %>%
  summarize(text = paste(rep(term, count), collapse = " "))

docs <- mallet.import(docs$document, docs$text, tmp)

# create and run a topic model
topic_model <- MalletLDA(num.topics = 4)
topic_model$loadDocuments(docs)
topic_model$train(20)

# tidy the word-topic combinations
td_beta <- tidy(topic_model)
td_beta

# Examine the four topics
td_beta %>%
  group_by(topic) %>%
  top_n(8, beta) %>%
  ungroup() %>%
  mutate(term = reorder(term, beta)) %>%
```

```

ggplot(aes(term, beta)) +
  geom_col() +
  facet_wrap(~ topic, scales = "free") +
  coord_flip()

# find the assignments of each word in each document
assignments <- augment(topic_model, td)
assignments

## End(Not run)

```

---

nma\_words

*English negators, modals, and adverbs*


---

### Description

English negators, modals, and adverbs, as a data frame. A few of these entries are two-word phrases instead of single words.

### Usage

```
nma_words
```

### Format

A data frame with 44 rows and 2 variables:

**word** An English word or bigram

**modifier** The modifier type for word, either "negator", "modal", or "adverb"

### Source

<http://saifmohammad.com/WebPages/SCL.html#NMA>

---

parts\_of\_speech

*Parts of speech for English words from the Moby Project*


---

### Description

Parts of speech for English words from the Moby Project by Grady Ward. Words with non-ASCII characters and items with a space have been removed.

### Usage

```
parts_of_speech
```

**Format**

A data frame with 205,985 rows and 2 variables:

**word** An English word

**pos** The part of speech of the word. One of 13 options, such as "Noun", "Adverb", "Adjective"

**Details**

Another dataset of English parts of speech, available only for non-commercial use, is available as part of SUBTLEXus at <https://www.ugent.be/pp/experimentele-psychologie/en/research/documents/subtlexus/>.

**Source**

<https://archive.org/details/mobypartofspeech03203gut>

**Examples**

```
library(dplyr)

parts_of_speech

parts_of_speech %>%
  count(pos, sort = TRUE)
```

---

reorder\_within

*Reorder an x or y axis within facets*

---

**Description**

Reorder a column before plotting with faceting, such that the values are ordered within each facet. This requires two functions: `reorder_within` applied to the column, then either `scale_x_reordered` or `scale_y_reordered` added to the plot. This is implemented as a bit of a hack: it appends `___` and then the facet at the end of each string.

**Usage**

```
reorder_within(x, by, within, fun = mean, sep = "___", ...)

scale_x_reordered(..., labels = reorder_func, sep = deprecated())

scale_y_reordered(..., labels = reorder_func, sep = deprecated())

reorder_func(x, sep = "___")
```

**Arguments**

x	Vector to reorder.
by	Vector of the same length, to use for reordering.
within	Vector or list of vectors of the same length that will later be used for faceting. A list of vectors will be used to facet within multiple variables.
fun	Function to perform within each subset to determine the resulting ordering. By default, mean.
sep	Separator to distinguish by and within. You may want to set this manually if ___ can exist within one of your labels.
...	In reorder_within arguments passed on to reorder(). In the scale functions, extra arguments passed on to ggplot2::scale_x_discrete() or ggplot2::scale_y_discrete().
labels	Function to transform the labels of ggplot2::scale_x_discrete(), by default reorder_func.

**Source**

"Ordering categories within ggplot2 Facets" by Tyler Rinker: <https://trinkerrstuff.wordpress.com/2016/12/23/ordering-categories-within-ggplot2-facets/>

**Examples**

```
library(tidyr)
library(ggplot2)

iris_gathered <- gather(iris, metric, value, -Species)

# reordering doesn't work within each facet (see Sepal.Width):
ggplot(iris_gathered, aes(reorder(Species, value), value)) +
  geom_boxplot() +
  facet_wrap(~ metric)

# reorder_within and scale_x_reordered work.
# (Note that you need to set scales = "free_x" in the facet)
ggplot(iris_gathered, aes(reorder_within(Species, value, metric), value)) +
  geom_boxplot() +
  scale_x_reordered() +
  facet_wrap(~ metric, scales = "free_x")

# to reorder within multiple variables, set within to the list of
# facet variables.
ggplot(mtcars, aes(reorder_within(carb, mpg, list(vs, am)), mpg)) +
  geom_boxplot() +
  scale_x_reordered() +
  facet_wrap(vs ~ am, scales = "free_x")
```

---

sentiments

*Sentiment lexicon from Bing Liu and collaborators*

---

### Description

Lexicon for opinion and sentiment analysis in a tidy data frame. This dataset is included in this package with permission of the creators, and may be used in research, commercial, etc. contexts with attribution, using either the paper or URL below.

### Usage

sentiments

### Format

A data frame with 6,786 rows and 2 variables:

**word** An English word

**sentiment** A sentiment for that word, either positive or negative.

### Details

This lexicon was first published in:

Minqing Hu and Bing Liu, "Mining and summarizing customer reviews.", Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (KDD-2004), Seattle, Washington, USA, Aug 22-25, 2004.

Words with non-ASCII characters were removed.

### Source

<https://www.cs.uic.edu/~liub/FBS/sentiment-analysis.html>

---

stm\_tidiers

*Tidiers for Structural Topic Models from the stm package*

---

### Description

Tidy topic models fit by the stm package. The arguments and return values are similar to [lda\\_tidiers\(\)](#).



**Usage**

```
## S3 method for class 'STM'
tidy(
  x,
  matrix = c("beta", "gamma", "theta", "frex", "lift"),
  log = FALSE,
  document_names = NULL,
  ...
)

## S3 method for class 'estimateEffect'
tidy(x, ...)

## S3 method for class 'estimateEffect'
glance(x, ...)

## S3 method for class 'STM'
augment(x, data, ...)

## S3 method for class 'STM'
glance(x, ...)
```

**Arguments**

x	An STM fitted model object from either <code>stm::stm()</code> or <code>stm::estimateEffect()</code>
matrix	Which matrix to tidy: <ul style="list-style-type: none"> <li>• the beta matrix (per-term-per-topic, default)</li> <li>• the gamma/theta matrix (per-document-per-topic); the stm package calls this the theta matrix, but other topic modeling packages call this gamma</li> <li>• the FREX matrix, for words with high frequency and exclusivity</li> <li>• the lift matrix, for words with high lift</li> </ul>
log	Whether beta/gamma/theta should be on a log scale, default FALSE
document_names	Optional vector of document names for use with per-document-per-topic tidying
...	Extra arguments for tidying, such as w as used in <code>stm::calcfrex()</code>
data	For augment, the data given to the stm function, either as a dfm from <code>quanteda</code> or as a tidied table with "document" and "term" columns

**Value**

`tidy` returns a tidied version of either the beta, gamma, FREX, or lift matrix if called on an object from `stm::stm()`, or a tidied version of the estimated regressions if called on an object from `stm::estimateEffect()`.

`glance` returns a tibble with exactly one row of model summaries.

`augment` must be provided a data argument, either a dfm from `quanteda` or a table containing one row per original document-term pair, such as is returned by `tdm_tidiers`, containing columns `document` and `term`. It returns that same data with an additional column `.topic` with the topic assignment for that document-term combination.

**See Also**

`lda_tidiers()`, `stm::calcfrex()`, `stm::calclift()`

**Examples**

```
library(dplyr)
library(ggplot2)
library(stm)
library(janeaustrer)

austen_sparse <- austen_books() %>%
  unnest_tokens(word, text) %>%
  anti_join(stop_words) %>%
  count(book, word) %>%
  cast_sparse(book, word, n)
topic_model <- stm(austen_sparse, K = 12, verbose = FALSE)

# tidy the word-topic combinations
td_beta <- tidy(topic_model)
td_beta

# Examine the topics
td_beta %>%
  group_by(topic) %>%
  slice_max(beta, n = 10) %>%
  ungroup() %>%
  ggplot(aes(beta, term)) +
  geom_col() +
  facet_wrap(~ topic, scales = "free")

# high FREX words per topic
tidy(topic_model, matrix = "frex")

# high lift words per topic
tidy(topic_model, matrix = "lift")

# tidy the document-topic combinations, with optional document names
td_gamma <- tidy(topic_model, matrix = "gamma",
  document_names = rownames(austen_sparse))
td_gamma

# using stm's gardarianFit, we can tidy the result of a model
# estimated with covariates
effects <- estimateEffect(1:3 ~ treatment, gardarianFit, gardarian)
glance(effects)
td_estimate <- tidy(effects)
td_estimate
```

---

stop_words	<i>Various lexicons for English stop words</i>
------------	--

---

**Description**

English stop words from three lexicons, as a data frame. The snowball and SMART sets are pulled from the tm package. Note that words with non-ASCII characters have been removed.

**Usage**

```
stop_words
```

**Format**

A data frame with 1149 rows and 2 variables:

**word** An English word

**lexicon** The source of the stop word. Either "onix", "SMART", or "snowball"

**Source**

- <http://www.lextek.com/manuals/onix/stopwords1.html>
- <https://www.jmlr.org/papers/volume5/lewis04a/lewis04a.pdf>
- <http://snowball.tartarus.org/algorithms/english/stop.txt>

---

tdm_tidiers	<i>Tidy DocumentTermMatrix, TermDocumentMatrix, and related objects from the tm package</i>
-------------	---

---

**Description**

Tidy a DocumentTermMatrix or TermDocumentMatrix into a three-column data frame: term{}, and value (with zeros missing), with one-row-per-term-per-document.

**Usage**

```
## S3 method for class 'DocumentTermMatrix'
tidy(x, ...)
```

```
## S3 method for class 'TermDocumentMatrix'
tidy(x, ...)
```

```
## S3 method for class 'dfm'
tidy(x, ...)
```

```
## S3 method for class 'dfmSparse'
tidy(x, ...)

## S3 method for class 'simple_triplet_matrix'
tidy(x, row_names = NULL, col_names = NULL, ...)
```

### Arguments

x	A DocumentTermMatrix or TermDocumentMatrix object
...	Extra arguments, not used
row_names	Specify row names
col_names	Specify column names

### Examples

```
if (requireNamespace("topicmodels", quietly = TRUE)) {
  data("AssociatedPress", package = "topicmodels")
  AssociatedPress

  tidy(AssociatedPress)
}
```

---

tidy.Corpus

*Tidy a Corpus object from the tm package*

---

### Description

Tidy a Corpus object from the tm package. Returns a data frame with one-row-per-document, with a text column containing the document's text, and one column for each local (per-document) metadata tag. For corpus objects from the quanteda package, see [tidy.corpus\(\)](#).

### Usage

```
## S3 method for class 'Corpus'
tidy(x, collapse = "\n", ...)
```

### Arguments

x	A Corpus object, such as a VCorpus or PCorpus
collapse	A string that should be used to collapse text within each corpus (if a document has multiple lines). Give NULL to not collapse strings, in which case a corpus will end up as a list column if there are multi-line documents.
...	Extra arguments, not used

**Examples**

```

library(dplyr) # displaying tbl_dfs

if (requireNamespace("tm", quietly = TRUE)) {
  library(tm)
  #' # tm package examples
  txt <- system.file("texts", "txt", package = "tm")
  ovid <- VCorpus(DirSource(txt, encoding = "UTF-8"),
                 readerControl = list(language = "lat"))

  ovid
  tidy(ovid)

  # choose different options for collapsing text within each
  # document
  tidy(ovid, collapse = "")$text
  tidy(ovid, collapse = NULL)$text

  # another example from Reuters articles
  reut21578 <- system.file("texts", "crude", package = "tm")
  reuters <- VCorpus(DirSource(reut21578),
                    readerControl = list(reader = readReut21578XMLasPlain))

  reuters

  tidy(reuters)
}

```

---

tidy\_triplet

*Utility function to tidy a simple triplet matrix*


---

**Description**

Utility function to tidy a simple triplet matrix

**Usage**

```
tidy_triplet(x, triplets, row_names = NULL, col_names = NULL)
```

**Arguments**

x	Object with rownames and colnames
triplets	A data frame or list of i, j, x
row_names	rownames, if not gotten from rownames(x)
col_names	colnames, if not gotten from colnames(x)

---

unnest\_characters      *Wrapper around unnest\_tokens for characters and character shingles*

---

### Description

These functions are a wrapper around `unnest_tokens( token = "characters" )` and `unnest_tokens( token = "character_shingles" )`.

### Usage

```
unnest_characters(
  tbl,
  output,
  input,
  strip_non_alphanum = TRUE,
  format = c("text", "man", "latex", "html", "xml"),
  to_lower = TRUE,
  drop = TRUE,
  collapse = NULL,
  ...
)
```

```
unnest_character_shingles(
  tbl,
  output,
  input,
  n = 3L,
  n_min = n,
  strip_non_alphanum = TRUE,
  format = c("text", "man", "latex", "html", "xml"),
  to_lower = TRUE,
  drop = TRUE,
  collapse = NULL,
  ...
)
```

### Arguments

<code>tbl</code>	A data frame
<code>output</code>	Output column to be created as string or symbol.
<code>input</code>	Input column that gets split as string or symbol. The output/input arguments are passed by expression and support <a href="#">quasiquote</a> - <a href="#">tion</a> ; you can unquote strings and symbols.
<code>strip_non_alphanum</code>	Should punctuation and white space be stripped?

format	Either "text", "man", "latex", "html", or "xml". When the format is "text", this function uses the tokenizers package. If not "text", this uses the hunspell tokenizer, and can tokenize only by "word".
to_lower	Whether to convert tokens to lowercase.
drop	Whether original input column should get dropped. Ignored if the original input and new output column have the same name.
collapse	A character vector of variables to collapse text across, or NULL. For tokens like n-grams or sentences, text can be collapsed across rows within variables specified by collapse before tokenization. At tidytext 0.2.7, the default behavior for collapse = NULL changed to be more consistent. The new behavior is that text is <i>not</i> collapsed for NULL. Grouping data specifies variables to collapse across in the same way as collapse but you <b>cannot</b> use both the collapse argument and grouped data. Collapsing applies mostly to token options of "ngrams", "skip_ngrams", "sentences", "lines", "paragraphs", or "regex".
...	Extra arguments passed on to <a href="#">tokenizers</a>
n	The number of characters in each shingle. This must be an integer greater than or equal to 1.
n_min	This must be an integer greater than or equal to 1, and less than or equal to n.

**See Also**

- [unnest\\_tokens\(\)](#)

**Examples**

```
library(dplyr)
library(janeaustenr)

d <- tibble(txt = prideprejudice)

d %>%
  unnest_characters(word, txt)

d %>%
  unnest_character_shingles(word, txt, n = 3)
```

---

unnest\_ngrams

*Wrapper around unnest\_tokens for n-grams*


---

**Description**

These functions are wrappers around `unnest_tokens( token = "ngrams" )` and `unnest_tokens( token = "skip_ngrams" )`.

**Usage**

```
unnest_ngrams(
  tbl,
  output,
  input,
  n = 3L,
  n_min = n,
  ngram_delim = " ",
  format = c("text", "man", "latex", "html", "xml"),
  to_lower = TRUE,
  drop = TRUE,
  collapse = NULL,
  ...
)

unnest_skip_ngrams(
  tbl,
  output,
  input,
  n_min = 1,
  n = 3,
  k = 1,
  format = c("text", "man", "latex", "html", "xml"),
  to_lower = TRUE,
  drop = TRUE,
  collapse = NULL,
  ...
)
```

**Arguments**

<code>tbl</code>	A data frame
<code>output</code>	Output column to be created as string or symbol.
<code>input</code>	Input column that gets split as string or symbol. The output/input arguments are passed by expression and support <a href="#">quasiquote</a> - <a href="#">tion</a> ; you can unquote strings and symbols.
<code>n</code>	The number of words in the n-gram. This must be an integer greater than or equal to 1.
<code>n_min</code>	The minimum number of words in the n-gram. This must be an integer greater than or equal to 1, and less than or equal to <code>n</code> .
<code>ngram_delim</code>	The separator between words in an n-gram.
<code>format</code>	Either "text", "man", "latex", "html", or "xml". When the format is "text", this function uses the <code>tokenizers</code> package. If not "text", this uses the <code>hunspell</code> tokenizer, and can tokenize only by "word".
<code>to_lower</code>	Whether to convert tokens to lowercase.



drop	Whether original input column should get dropped. Ignored if the original input and new output column have the same name.
collapse	A character vector of variables to collapse text across, or NULL. For tokens like n-grams or sentences, text can be collapsed across rows within variables specified by collapse before tokenization. At tidytext 0.2.7, the default behavior for collapse = NULL changed to be more consistent. The new behavior is that text is <i>not</i> collapsed for NULL. Grouping data specifies variables to collapse across in the same way as collapse but you <b>cannot</b> use both the collapse argument and grouped data. Collapsing applies mostly to token options of "ngrams", "skip_ngrams", "sentences", "lines", "paragraphs", or "regex".
...	Extra arguments passed on to <a href="#">tokenizers</a>
k	For the skip n-gram tokenizer, the maximum skip distance between words. The function will compute all skip n-grams between 0 and k.

**See Also**

- [unnest\\_tokens\(\)](#)

**Examples**

```
library(dplyr)
library(janeaustenr)

d <- tibble(txt = prideprejudice)

d %>%
  unnest_ngrams(word, txt, n = 2)

d %>%
  unnest_skip_ngrams(word, txt, n = 3, k = 1)
```

---

unnest\_ptb

*Wrapper around unnest\_tokens for Penn Treebank Tokenizer*


---

**Description**

This function is a wrapper around `unnest_tokens( token = "ptb" )`.

**Usage**

```
unnest_ptb(
  tbl,
  output,
  input,
  format = c("text", "man", "latex", "html", "xml"),
```

```

  to_lower = TRUE,
  drop = TRUE,
  collapse = NULL,
  ...
)

```

## Arguments

tbl	A data frame
output	Output column to be created as string or symbol.
input	Input column that gets split as string or symbol. The output/input arguments are passed by expression and support <a href="#">quasiquote</a> - <a href="#">tion</a> ; you can unquote strings and symbols.
format	Either "text", "man", "latex", "html", or "xml". When the format is "text", this function uses the <code>tokenizers</code> package. If not "text", this uses the <code>hunspell</code> tokenizer, and can tokenize only by "word".
to_lower	Whether to convert tokens to lowercase.
drop	Whether original input column should get dropped. Ignored if the original input and new output column have the same name.
collapse	A character vector of variables to collapse text across, or NULL. For tokens like n-grams or sentences, text can be collapsed across rows within variables specified by <code>collapse</code> before tokenization. At <code>tidytext</code> 0.2.7, the default behavior for <code>collapse = NULL</code> changed to be more consistent. The new behavior is that text is <i>not</i> collapsed for NULL. Grouping data specifies variables to collapse across in the same way as <code>collapse</code> but you <b>cannot</b> use both the <code>collapse</code> argument and grouped data. Collapsing applies mostly to token options of "ngrams", "skip_ngrams", "sentences", "lines", "paragraphs", or "regex".
...	Extra arguments passed on to <a href="#">tokenizers</a>

## See Also

- [unnest\\_tokens\(\)](#)

## Examples

```

library(dplyr)
library(janeaustenr)

d <- tibble(txt = prideprejudice)

d %>%
  unnest_ptb(word, txt)

```

---

unnest_regex	<i>Wrapper around unnest_tokens for regular expressions</i>
--------------	---

---

### Description

This function is a wrapper around `unnest_tokens( token = "regex" )`.

### Usage

```
unnest_regex(
  tbl,
  output,
  input,
  pattern = "\\s+",
  format = c("text", "man", "latex", "html", "xml"),
  to_lower = TRUE,
  drop = TRUE,
  collapse = NULL,
  ...
)
```

### Arguments

tbl	A data frame
output	Output column to be created as string or symbol.
input	Input column that gets split as string or symbol. The output/input arguments are passed by expression and support <a href="#">quasiquote</a> ; you can unquote strings and symbols.
pattern	A regular expression that defines the split.
format	Either "text", "man", "latex", "html", or "xml". When the format is "text", this function uses the <code>tokenizers</code> package. If not "text", this uses the <code>hunspell</code> tokenizer, and can tokenize only by "word".
to_lower	Whether to convert tokens to lowercase.
drop	Whether original input column should get dropped. Ignored if the original input and new output column have the same name.
collapse	A character vector of variables to collapse text across, or NULL. For tokens like n-grams or sentences, text can be collapsed across rows within variables specified by <code>collapse</code> before tokenization. At <code>tidytext</code> 0.2.7, the default behavior for <code>collapse = NULL</code> changed to be more consistent. The new behavior is that text is <i>not</i> collapsed for NULL. Grouping data specifies variables to collapse across in the same way as <code>collapse</code> but you <b>cannot</b> use both the <code>collapse</code> argument and grouped data. Collapsing applies mostly to token options of "ngrams", "skip_ngrams", "sentences", "lines", "paragraphs", or "regex".
...	Extra arguments passed on to <a href="#">tokenizers</a>

**See Also**

- [unnest\\_tokens\(\)](#)

**Examples**

```
library(dplyr)
library(janeaustenr)

d <- tibble(txt = prideprejudice)

d %>%
  unnest_regex(word, txt, pattern = "Chapter [\\d]")
```

---

unnest\_sentences

*Wrapper around unnest\_tokens for sentences, lines, and paragraphs*

---

**Description**

These functions are wrappers around `unnest_tokens( token = "sentences" )`, `unnest_tokens( token = "lines" )` and `unnest_tokens( token = "paragraphs" )`.

**Usage**

```
unnest_sentences(
  tbl,
  output,
  input,
  strip_punct = FALSE,
  format = c("text", "man", "latex", "html", "xml"),
  to_lower = TRUE,
  drop = TRUE,
  collapse = NULL,
  ...
)

unnest_lines(
  tbl,
  output,
  input,
  format = c("text", "man", "latex", "html", "xml"),
  to_lower = TRUE,
  drop = TRUE,
  collapse = NULL,
  ...
)
```

```
unnest_paragraphs(
  tbl,
  output,
  input,
  paragraph_break = "\n\n",
  format = c("text", "man", "latex", "html", "xml"),
  to_lower = TRUE,
  drop = TRUE,
  collapse = NULL,
  ...
)
```

### Arguments

tbl	A data frame
output	Output column to be created as string or symbol.
input	Input column that gets split as string or symbol. The output/input arguments are passed by expression and support <a href="#">quasiquote</a> ; you can unquote strings and symbols.
strip_punct	Should punctuation be stripped?
format	Either "text", "man", "latex", "html", or "xml". When the format is "text", this function uses the <code>tokenizers</code> package. If not "text", this uses the <code>hunspell</code> tokenizer, and can tokenize only by "word".
to_lower	Whether to convert tokens to lowercase.
drop	Whether original input column should get dropped. Ignored if the original input and new output column have the same name.
collapse	A character vector of variables to collapse text across, or NULL. For tokens like n-grams or sentences, text can be collapsed across rows within variables specified by <code>collapse</code> before tokenization. At <code>tidytext</code> 0.2.7, the default behavior for <code>collapse = NULL</code> changed to be more consistent. The new behavior is that text is <i>not</i> collapsed for NULL. Grouping data specifies variables to collapse across in the same way as <code>collapse</code> but you <b>cannot</b> use both the <code>collapse</code> argument and grouped data. Collapsing applies mostly to token options of "ngrams", "skip_ngrams", "sentences", "lines", "paragraphs", or "regex".
...	Extra arguments passed on to <a href="#">tokenizers</a>
paragraph_break	A string identifying the boundary between two paragraphs.

### See Also

- [unnest\\_tokens\(\)](#)

**Examples**

```
library(dplyr)
library(janeaustenr)

d <- tibble(txt = prideprejudice)

d %>%
  unnest_sentences(word, txt)
```

unnest\_tokens

*Split a column into tokens***Description**

Split a column into tokens, flattening the table into one-token-per-row. This function supports non-standard evaluation through the tidyeval framework.

**Usage**

```
unnest_tokens(
  tbl,
  output,
  input,
  token = "words",
  format = c("text", "man", "latex", "html", "xml"),
  to_lower = TRUE,
  drop = TRUE,
  collapse = NULL,
  ...
)
```

**Arguments**

tbl	A data frame
output	Output column to be created as string or symbol.
input	Input column that gets split as string or symbol. The output/input arguments are passed by expression and support <a href="#">quasiquote-tion</a> ; you can unquote strings and symbols.
token	Unit for tokenizing, or a custom tokenizing function. Built-in options are "words" (default), "characters", "character_shingles", "ngrams", "skip_ngrams", "sentences", "lines", "paragraphs", "regex", and "ptb" (Penn Treebank). If a function, should take a character vector and return a list of character vectors of the same length.
format	Either "text", "man", "latex", "html", or "xml". When the format is "text", this function uses the tokenizers package. If not "text", this uses the hunspell tokenizer, and can tokenize only by "word".

to_lower	Whether to convert tokens to lowercase.
drop	Whether original input column should get dropped. Ignored if the original input and new output column have the same name.
collapse	A character vector of variables to collapse text across, or NULL. For tokens like n-grams or sentences, text can be collapsed across rows within variables specified by collapse before tokenization. At tidytext 0.2.7, the default behavior for collapse = NULL changed to be more consistent. The new behavior is that text is <i>not</i> collapsed for NULL. Grouping data specifies variables to collapse across in the same way as collapse but you <b>cannot</b> use both the collapse argument and grouped data. Collapsing applies mostly to token options of "ngrams", "skip_ngrams", "sentences", "lines", "paragraphs", or "regex".
...	Extra arguments passed on to <a href="#">tokenizers</a> , such as strip_punct for "words", n and k for "ngrams" and "skip_ngrams", and pattern for "regex".

### Details

If format is anything other than "text", this uses the `hunspell::hunspell_parse()` tokenizer instead of the `tokenizers` package. This does not yet have support for tokenizing by any unit other than words.

Support for `token = "tweets"` was removed in tidytext 0.4.0 because of changes in upstream dependencies.

### Examples

```
library(dplyr)
library(janeaustenr)

d <- tibble(txt = prideprejudice)
d

d %>%
  unnest_tokens(output = word, input = txt)

d %>%
  unnest_tokens(output = sentence, input = txt, token = "sentences")

d %>%
  unnest_tokens(output = ngram, input = txt, token = "ngrams", n = 2)

d %>%
  unnest_tokens(chapter, txt, token = "regex", pattern = "Chapter [\\d]")

d %>%
  unnest_tokens(shingle, txt, token = "character_shingles", n = 4)

# custom function
```

```
d %>%
  unnest_tokens(word, txt, token = stringr::str_split, pattern = " ")

# tokenize HTML
h <- tibble(row = 1:2,
            text = c("<h1>Text <b>is</b>", "<a href='example.com'>here</a>"))

h %>%
  unnest_tokens(word, text, format = "html")
```



# Index

## \* datasets

- nma\_words, 13
  - parts\_of\_speech, 13
  - sentiments, 16
  - stop\_words, 19
- augment.CTM(lda\_tidiers), 8  
augment.jobRef(mallet\_tidiers), 11  
augment.LDA(lda\_tidiers), 8  
augment.STM(stm\_tidiers), 16
- bind\_tf\_idf, 3
- cast\_dfm(cast\_tdm), 5  
cast\_dtm(cast\_tdm), 5  
cast\_sparse, 4  
cast\_tdm, 5  
corpus\_tidiers, 5
- dictionary\_tidiers, 6
- get\_sentiments, 7  
get\_stopwords, 8  
ggplot2::scale\_x\_discrete(), 15  
ggplot2::scale\_y\_discrete(), 15  
glance.corpus(corpus\_tidiers), 5  
glance.CTM(lda\_tidiers), 8  
glance.estimateEffect(stm\_tidiers), 16  
glance.LDA(lda\_tidiers), 8  
glance.STM(stm\_tidiers), 16
- hunspell::hunspell\_parse(), 31
- lda\_tidiers, 8  
lda\_tidiers(), 11, 12, 16, 18
- mallet::mallet.doc.topics(), 12  
mallet::mallet.topic.words(), 12  
mallet::MalletLDA(), 11, 12  
mallet\_tidiers, 11
- nma\_words, 13
- parts\_of\_speech, 13
- quasiquotation, 3–5, 22, 24, 26, 27, 29, 30
- reorder(), 15  
reorder\_func(reorder\_within), 14  
reorder\_within, 14
- scale\_x\_reordered(reorder\_within), 14  
scale\_y\_reordered(reorder\_within), 14  
sentiments, 16  
sentiments(), 7  
sparseMatrix(), 4, 5  
stm::calcfrex(), 17, 18  
stm::calclift(), 18  
stm::estimateEffect(), 17  
stm::stm(), 17  
stm\_tidiers, 16  
stop\_words, 19  
stopwords, 8  
stopwords\_getlanguages, 8  
stopwords\_getsources, 8
- tdm\_tidiers, 9, 12, 17, 19  
tidy.Corpora, 20  
tidy.corpus(corpus\_tidiers), 5  
tidy.Corpora(), 5  
tidy.corpus(), 20  
tidy.CTM(lda\_tidiers), 8  
tidy.dfm(tdm\_tidiers), 19  
tidy.dfmSparse(tdm\_tidiers), 19  
tidy.dictionary2(dictionary\_tidiers), 6  
tidy.DocumentTermMatrix(tdm\_tidiers), 19  
tidy.estimateEffect(stm\_tidiers), 16  
tidy.jobRef(mallet\_tidiers), 11  
tidy.LDA(lda\_tidiers), 8  
tidy.simple\_triplet\_matrix(tdm\_tidiers), 19  
tidy.STM(stm\_tidiers), 16

`tidy.TermDocumentMatrix (tdm_tidiers)`,  
19

`tidy_triplet`, 21

`tokenizers`, 23, 25–27, 29, 31

`unnest_character_shingles`  
(`unnest_characters`), 22

`unnest_characters`, 22

`unnest_lines (unnest_sentences)`, 28

`unnest_ngrams`, 23

`unnest_paragraphs (unnest_sentences)`, 28

`unnest_ptb`, 25

`unnest_regex`, 27

`unnest_sentences`, 28

`unnest_skip_ngrams (unnest_ngrams)`, 23

`unnest_tokens`, 30

`unnest_tokens()`, 23, 25, 26, 28, 29