

Examples of `paresse` package usage.
 le T_EXnicien de surface
 2008-08-12

This file loads the `amsmath` package and, if it locally exists, the `lmodern` package.

Caution: the `paresse` package is loaded with the option `tame` to show the usage of macro `\ActiveLaParsesse` and environment `ParsesseActive`.

With the macro `\ActiveLaParsesse` to make the § character active.

```
{\ActiveLaParsesse
\($a^{§b}_{§g}\) and also \($D^{§a}_{§d}\)
}
```

to obtain: α^β and also Δ_δ^α

With the environment `ParsesseActive`.

```
\begin{ParsesseActive}\large
\begin{tabular}{*4{||>\ttfamily \S}c|c|}} \hline
a & §a & b & §b & g & §g & d & §d\\ \hline
e & §e & z & §z & h & §h & v & §v\\ \hline
...
X & §X & P & §P & S & §S & U & §U\\ \hline
F & §F & Q & §Q & W & §W & \multicolumn{1}{c|}{& } & \\ \hline
\end{tabular}
\end{ParsesseActive}
```

§a	α	§b	β	§g	γ	§d	δ
§e	ε	§z	ζ	§h	η	§v	θ
§i	ι	§k	κ	§l	λ	§m	μ
§n	ν	§x	ξ	§p	π	§r	ρ
§s	σ	§y	τ	§u	υ	§f	φ
§c	χ	§q	ψ	§w	ω		
§G	Γ	§D	Δ	§V	Θ	§L	Λ
§X	Ξ	§P	Π	§S	Σ	§U	Υ
§F	Φ	§Q	Ψ	§W	Ω		