

**Solaris™ 2.5/2.5.1**  
**x86 Hardware Compatibility List**  
*November 1997*

**SunSoft, Inc.**

A Sun Microsystems, Inc. Business  
2550 Garcia Avenue  
Mountain View, CA 94043  
U.S.A.

Part No: 802-1974-23  
Revision A, November 1997

Copyright 1997 Sun Microsystems, Inc., 901 San Antonio Road, Palo Alto, California 94303 U.S.A. All rights reserved.

This product or document is protected by copyright and distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, SunSoft, SunDocs, SunExpress, Solaris, and OpenWindows are trademarks, registered trademarks, or service marks of Sun Microsystems, Inc. in the United States and other countries.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

**RESTRICTED RIGHTS:** Use, duplication, or disclosure by the U.S. Government is subject to restrictions of FAR 52.227-14(g)(2)(6/87) and FAR 52.227-19(6/87), or DFAR 252.227-7015(b)(6/95) and DFAR 227.7202-3(a).

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 1997 Sun Microsystems, Inc., 901 San Antonio Road, Palo Alto, Californie 94303 Etats-Unis. Tous droits réservés.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, SunSoft, SunDocs, SunExpress, Solaris, et OpenWindows sont des marques déposées ou enregistrées, ou marques de service de Sun Microsystems, Inc. aux Etats-Unis et d'autres pays.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

CETTE PUBLICATION EST FOURNIE "EN L'ETAT" ET AUCUNE GARANTIE, EXPRESSE OU IMPLICITE, N'EST ACCORDEE, Y COMPRIS DES GARANTIES CONCERNANT LA VALEUR MARCHANDE, L'APTITUDE DE LA PUBLICATION A REpondre A UNE UTILISATION PARTICULIERE, OU LE FAIT QU'ELLE NE SOIT PAS CONTREFAISANTE DE PRODUIT DE TIERS. CE DENI DE GARANTIE NE S'APPLIQUERAIT PAS, DANS LA MESURE OU IL SERAIT TENU JURIDIQUEMENT NUL ET NON AVENU.



# *Solaris 2.5/2.5.1 x86 Hardware Compatibility List*

---



This document provides information about general x86 hardware requirements and the peripherals and system platforms that are supported in the Solaris™ 2.5/2.5.1 x86 computing environment.

Throughout the Solaris 2.5/2.5.1 x86 release cycle, support for additional systems and devices is added to the product on an ongoing basis. This document will continue to be updated to describe the new support. You can access the locations listed in “How to Obtain Updated Hardware Compatibility Lists and Device Driver Information” to see if a more current version exists.

Many of the systems and peripherals listed in this document require the current Driver Update for proper operation in the Solaris environment.

System platforms listed in this document are tested “as-shipped” by the hardware manufacturers. Since it is the nature of this industry to have unexpected and unannounced changes, SunSoft is committed to working with customers who experience difficulties installing the Solaris software on supported systems. If any problems are encountered with this release, contact your Sun Software Support Provider (SSSP). In North America, you can also call SunSoft Technical Support at 1-800-SUNSOFT, option 4.

---

**Note** – It is common practice for hardware vendors to release variants of a particular hardware design under a single marketing name. In some cases, not all variants will work with the current Solaris device driver. Check the appropriate Device Reference Page in *Solaris 2.5/2.5.1 x86 Driver Update Guide* for additional information about specific hardware versions supported by the current Solaris device driver.

---

## *How This Book Is Organized*

This document is divided into these major sections:

- “**General Requirements**” lists the x86 hardware requirements for installing the Solaris 2.5/2.5.1 operating environment.



- “**System Platforms**” lists the platforms supported in Solaris 2.5/2.5.1 x86; not all of the peripherals listed in the “Supported Devices” section have been tested in all combinations on all of these platforms. This is *not* intended to be an exhaustive list of x86 machines that can run Solaris 2.5/2.5.1 software.
- “**Supported Devices**” lists the supported peripherals.

Specific machines and classes of devices are shown in these tables in this document.

<b><i>System Platforms</i></b>	
<i>Single Processor Systems</i>	<i>page 7</i>
<i>Multiprocessor Systems (SMP)</i>	<i>page 18</i>
<i>Notebook Computers (Prior to March 1996)</i>	<i>page 23</i>
<i>Notebook Certification Matrix (After March 1996)</i>	<i>page 24</i>
<b><i>Supported Devices</i></b>	
<i>SCSI Host Bus Adapters</i>	<i>page 26</i>
<i>SCSI RAID Controllers</i>	<i>page 29</i>
<i>Solid State SCSI Disk Devices</i>	<i>page 29</i>
<i>CD-ROM Drives</i>	<i>page 30</i>
<i>Printing Devices</i>	<i>page 32</i>
<i>Audio Devices</i>	<i>page 32</i>
<i>Telephony Products</i>	<i>page 33</i>
<i>Multiport Serial Adapters</i>	<i>page 34</i>
<i>Network Adapters—Ethernet</i>	<i>page 35</i>
<i>Network Adapters—Fast Ethernet</i>	<i>page 37</i>
<i>Network Adapters—FDDI</i>	<i>page 39</i>



<i>Network Adapters—Token Ring</i>	<i>page 39</i>
<i>Network Adapters—WAN</i>	<i>page 39</i>
<i>AT-ISDN Adapters</i>	<i>page 39</i>
<i>High-Speed Networking</i>	<i>page 39</i>
<i>PC Card (PCMCIA)—Add-On Boards</i>	<i>page 39</i>
<i>PC Card (PCMCIA)—GPS and Navigation Devices</i>	<i>page 39</i>
<i>PC Card (PCMCIA)—Modems</i>	<i>page 40</i>
<i>PC Card (PCMCIA)—Serial Cards</i>	<i>page 41</i>
<i>PC Card (PCMCIA)—SRAM Memory Cards</i>	<i>page 41</i>
<i>Pointing Devices</i>	<i>page 41</i>
<i>Tape Drives—SCSI</i>	<i>page 42</i>
<i>SCSI RAID Tape</i>	<i>page 43</i>
<i>Uninterruptable Power Supplies (UPS)</i>	<i>page 44</i>
<i>Motherboards</i>	<i>page 45</i>
<i>Video Display Adapters</i>	<i>page 48</i>
<i>Notebook Display Video Support</i>	<i>page 60</i>

## *Conventions Used*

Pentium system platforms and motherboards listed in this document show the CPU type and speed in parentheses after the model name.

The term (P-xxx) indicates a Pentium processor; the xxx is replaced by the speed of the system in megahertz. For example, P-100 indicates a 100-MHz Pentium processor.



The term (PP-xxx) indicates a Pentium Pro processor; the xxx is replaced by the speed of the system in megahertz. For example, PP-150 indicates a 150-MHz Pentium Pro processor.

The term (PII-xxx) indicates a Pentium II processor; the xxx is replaced by the speed of the system in megahertz. For example, PII-233 indicates a 233-MHz Pentium II processor.

## *How to Obtain Updated Hardware Compatibility Lists and Device Driver Information*

Hardware Compatibility Lists and Driver Update releases (including related documentation) are produced periodically as support for new hardware becomes available. They are available from these sources:

**The Web**—For Driver Updates, open URL

<http://access1.sun.com/drivers/>. For Hardware Compatibility Lists, open URL <http://access1.sun.com/certify/hcl.html>.

**FTP**—Use anonymous FTP to access <ftp.uu.net> (or from your web browser, type <ftp://ftp.uu.net>), then go to [/vendor/sun/solaris/x86/2.5.1/](ftp://ftp.uu.net/vendor/sun/solaris/x86/2.5.1/).

Note that the Web and ASK-IT (below) also point to Support-provided installation and configuration information as well as answers to frequently asked questions.

### *Related Documentation Only*

- Email Autoresponder—To obtain a Hardware Compatibility List or a Driver Update Announcement via email, write to [hcl-index@sun.com](mailto:hcl-index@sun.com) for a list of autoresponse aliases that return hardware support information.
- ASK-IT<sup>1</sup>—SunSoft's Automated Support Fax-on-Demand Service
  - In North America, call one of these numbers:  
1-800-SUNSOFT and choose options 4, 1, 1, 1  
(310) 348-6219 and choose option 1
  - Outside North America, call one of these numbers and choose option 1:  
Australia                      61-2-844-5374

1. Includes the current Hardware Compatibility List and document No. 51225, which summarizes the current Driver Update.



---

Japan	03-5717-2560
Singapore	65-383-1971
United Kingdom	44-1276-677131

## *Related Books*

For specific hardware configuration information necessary to install and run Solaris on your particular hardware, see *x86 Device Configuration Guide* and any documentation supplied with a Solaris 2.5/2.5.1 x86 Driver Update.

## *Ordering Sun Documents*

The SunDocs<sup>SM</sup> program provides over 250 manuals from Sun Microsystems, Inc. If you live in the U.S., Canada, Europe, or Japan, you can purchase documentation sets or individual manuals using this program.

For a list of documents and ordering information, see the catalog section of SunExpress<sup>TM</sup> On The Internet at <http://www.sun.com/sunexpress>.

## *Corrections and Additions*

Vendors, OEMs, and manufacturers: To supply corrections or add products to this list, or to obtain information on the hardware certification program, send email to [x86-certify@cypress.west.sun.com](mailto:x86-certify@cypress.west.sun.com) or leave voice mail at (310) 348-6170.

## *How to Obtain Technical Support*

To obtain technical support:

- Contact your Sun Software Support Provider.
- In North America, you can also call 1-800-SUNSOFT and choose option 4.



---

## General Requirements

CPU	Minimum Memory	Bus	Disk Interface	Distribution Media	Devices for Installing Solaris
Intel or compatible 386@33MHz (minimum <sup>1</sup> )	16 Mbytes	ISA,	IDE,	CD-ROM with a	Diskette drive
Intel or compatible 486DX, 486DX2, 486DX4, 486SL, 486SX		EISA,	E-IDE,	single boot diskette	<i>and</i> one of the following devices:
Intel Pentium		MCA,	SCSI		• Local SCSI or ATAPI/IDE
Intel Pentium Pro		PCI,			CD-ROM drive
Intel Pentium II		VLB			• Remote SCSI or ATAPI/IDE
Intel Pentium with MMX					CD-ROM drive available over the network
AMD 486DX2-66					• Remote hard disk available over the network
AMD 486DX2-80					
AMD 486DX4-100					
AMD 486DX4-100 Enhanced					
AMD-K5					
AMD-K6					
Cyrix 486DLC-40					
Cyrix 5x86-100GP					
Cyrix 6x86-P120+GP					
Cyrix 6x86-P150+					
Cyrix 6x86MX-PR150					
Cyrix 6x86-P166+					

1. A 486DX, 486DX2, or Pentium CPU is recommended for better performance.



---

## System Platforms

The Solaris 2.5/2.5.1 x86 system has been successfully installed and tested on the computers listed in this section configured as they are shipped by the system manufacturer.

---

### Single Processor Systems

---

Acer AcerAltos 300 (P-166)  
Acer AcerAltos 700  
Acer AcerAltos 800<sup>1</sup>  
Acer AcerAltos 800/P (P-90)  
Acer AcerAltos 900/Pro-200 with EIDE (PP-200)  
Acer AcerAltos 900/Pro-200 with SCSI (PP-200)  
Acer AcerAltos 7000 (P-60)  
Acer AcerAltos 7000 (P-90)  
Acer AcerAltos 7000/P (1 CPU, P-90)  
Acer AcerAltos 9000/Pro-200 (PP-200)  
Acer AcerAltos 19000 (PP-200)  
Acer AcerPower 5000 (P-60)<sup>2,3</sup>  
Acer AcerPower 5020 (P-90)<sup>2,3</sup>  
Acer AcerPower 7500 (P-75)  
Acer AcerPower 9000T  
Acer AcerPower Pentium-75 Desktop  
Acer AcerAltos 17000 Server (tested with 1 CPU only)<sup>4</sup>

---

---

### Single Processor Systems (Continued)

---

ALR BusinessVEISA DX2/66  
ALR Evolution 150 (PP-150)  
ALR Evolution 5DT (P-120)  
ALR Evolution 5DT (P-166)  
ALR Evolution Dual6 (1 CPU config, PP-200)  
ALR Evolution IV 4DX2/66  
ALR Evolution Q/MP2 100 (1 CPU config)  
ALR Evolution V STe/75 (P-75)  
ALR Evolution V ST/75 (P-75)  
ALR Evolution V ST/120 (P-120)  
ALR Evolution V ST/PCI (P-90)  
ALR Evolution VQ EISA (P-60)  
ALR Evolution VQ EISA (P-66)  
ALR Evolution VQ EISA (P-90)  
ALR Evolution X/75 (P-75)  
ALR Evolution X/120 (P-120)  
ALR FLYERv1 486 DX2/66  
ALR Optima DT/133 (P-133)  
ALR Optima MT (PP-200)  
ALR PROVEISA DX2/66  
ALR Revolution Dual6 (1 CPU config, PP-200, 512K)  
ALR Revolution MP-100 (1 CPU config)  
ALR Revolution MP-120 (1 CPU config)  
ALR Revolution MP-133 (1 CPU config)  
ALR Revolution MP-166 (1 CPU, P-166)  
ALR Revolution MP II (1 CPU, P-166)  
ALR Revolution MP II (1 CPU, P-200)  
ALR Revolution Q-SMP (1 CPU, P-166)  
ALR Revolution Quad6-200 (1 CPU, PP-200)  
  
AMD Desktop 5K86-90 (P-90)  
AMD Enhanced (486DX4-100)  
  
American Micro Group P90PE-SS Server  
American Micro Group P90PE-WS Workstation

---



---

**Single Processor Systems (Continued)**

---

AST Advantage Model 7302 (P-120)  
AST Advantage Model 7303 (P-133)  
AST Advantage Model 7304 (P-166)  
AST Advantage Model 9302 (P-120)  
AST Advantage Model 9304 (P-133)  
AST Advantage Model 9308 (P-166)  
AST Advantage Model 95xx (PII-233)  
AST Bravo LC 4/100T  
AST Bravo LCP-100 (P-100)  
AST Bravo MS P/75  
AST Bravo MS P/75 (Eagle) (P-75)  
AST Bravo MS P/75 (Monaco) (P-75)  
AST Bravo MS P/90)  
AST Bravo MS P/100 (P-100)  
AST Bravo MS P/100 (Eagle) (P-100)  
AST Bravo MS P/100 (Monaco) (P-100)  
AST Bravo MS P/120 (Eagle) (P-120)  
AST Bravo MS P/133 (Eagle) (P-133)  
AST Bravo MS P/133 (Monaco) (P-133)  
AST Bravo MS P/166 (Monaco) (P-166)  
AST Bravo MS 4/50d  
AST Bravo MS 4/50s  
AST Bravo MS 4/66d  
AST Bravo MST P100 (P-100)  
AST Bravo MST P120 (Eagle) (P-120)  
AST Bravo MST P133 (P-133)  
AST Bravo MST 6150 (PP-150)  
AST Bravo MST 6180 Model 1600C (PP-180)  
AST Bravo MST 6200 Model 2500C  
AST Manhattan G  
AST Manhattan P5090 (P-90)  
AST Manhattan P Series 5100 (P-100)  
AST Manhattan P5133 12003AE (1 CPU)  
AST Manhattan S6200 Model 2003 (PP-200)  
AST Manhattan S6200 Model 2003LC (PP-200)  
AST Manhattan V5090 (P-90)<sup>5</sup>

---

---

**Single Processor Systems (Continued)**

---

**AST, cont.**  
AST PowerExec 4/33SL  
AST Premium SE 4/50  
AST Premmia GX (P-90) E-IDE  
AST Premmia GX (P-90) Integrated SCSI<sup>5</sup>  
AST Premmia GX (P-100)  
AST Premmia GX (P-133)  
AST Premmia MTE 4/66  
AST Premmia MX 4/100t 486 DX4-100  
AST Premmia MX P/75 (P-75)  
  
AT&T GIS 3404 Server (P-90)  
  
Austin Direct Affinity SE  
Austin Direct Power System 66 (P-66)  
  
C&S Vertriebs GmbH AMICUS Advanced (P-133)  
C&S Vertriebs GmbH AMICUS Performance (P-100)  
C&S Vertriebs GmbH (P-100 ISA/PCI)  
  
Centerprise LEO-486 (486DX33)

---



---

**Single Processor Systems (Continued)**

---

Compaq Deskpro 4/33i  
Compaq Deskpro 2000 (P-166)  
Compaq Deskpro 2000 M6200 (PP-200)  
Compaq Deskpro 5100 (P-150)  
Compaq Deskpro 5133 (P-133)  
Compaq Deskpro 5166 (P-166)  
Compaq Deskpro 6000 Model 5166PDS (P-166)  
Compaq Deskpro XE 450  
Compaq Deskpro XE 560 (P-60)  
Compaq Deskpro XL 466 (486DX2/66)  
Compaq Deskpro XL 486 (486-66)  
Compaq Deskpro XL 590 (P-90)  
Compaq Deskpro XL 5120 (P-120)  
Compaq Deskpro XL 6150 (PP-150)  
Compaq Deskpro XL 6200 (PP-200)  
Compaq Professional Workstation 5000 (PP-200)  
Compaq Professional Workstation 5100 (PII-266)  
Compaq ProLiant 800 (PP-200)  
Compaq ProLiant 850R (PP-200)  
Compaq ProLiant 1000 Model 3121 (486DX2-66)  
Compaq ProLiant 1500 (P-75)  
Compaq ProLiant 1500 (1 CPU, P-100)  
Compaq ProLiant 1500 (P-133)  
Compaq ProLiant 1500 (P-166)  
Compaq ProLiant 2000 (1 CPU, P-90)  
Compaq ProLiant 2500 (PP-200)  
Compaq ProLiant 4000 (1 CPU, P-90)  
Compaq ProLiant 4500 (P-100)  
Compaq ProLiant 6000 (PP-200)  
Compaq ProLinea 4/33  
Compaq ProLinea 5/133  
Compaq ProLinea 575 (P-75)  
Compaq ProLinea 6150E  
Compaq ProSignia 200 (P-166)  
Compaq ProSignia 300 (P-90)  
Compaq ProSignia 300 (P-120)  
Compaq ProSignia 300 5/150 (P-150)  
Compaq ProSignia 300 Model 2100 (P-150)  
Compaq ProSignia 500 (P-90)

---

---

**Single Processor Systems (Continued)**

---

CompuAdd C4100D Low Profile (486DX4-100)  
CompuAdd 450  
CompuAdd C450D  
CompuAdd C450D Low Profile  
CompuAdd C4100D Low Profile (486DX4-100)  
CompuAdd C466d  
CompuAdd C466D Low Profile (486DX2-66)  
CompuAdd CP90p  
CompuAdd CP90p-LX Low Profile  
CompuTrend PREMIO Model 5107-AL1 (P-66)  
CompuTrend PREMIO Model 5107-AL3 (P-90)  
Cube Corp. ATX 466D2  
Cube Corp. PowerStation P66  
DEC Celebris 590 Low Profile (P-90)  
DEC Celebris FX 5133 (P-133)  
DEC Celebris GL 5120/ST (P-120)  
DEC Celebris XL 5100  
DEC Celebris XL 6150 (PP-150)  
DEC DECpc 466d2 MTE  
DEC DECpc LVp+ (433sx/466d2/4100d4)  
DEC Prioris HX 590 (P-90)<sup>6</sup>  
DEC Prioris MX 6200 (PP-200)<sup>7</sup>  
DEC Prioris MX 6200 (PP-200, 512K)<sup>7</sup>  
DEC Prioris MX 6200 (PP-200+RAID)<sup>7</sup>  
DEC Prioris MX 6200 (PP-200+RAID, 512K)<sup>7</sup>  
DEC Venturis 5133 (P-133)

---



---

**Single Processor Systems (Continued)**

---

Dell 433/DE  
Dell 450/DE  
Dell 466/ME  
Dell 466/MX  
Dell 466/T  
Dell Dimension XPS P90  
Dell Dimension XPS P100c  
Dell Dimension XPS P120c  
Dell Dimension XPS 6150 (PP-150)  
Dell Dimension XPS Pro200n (PP-200)  
Dell OmniPlex 466  
Dell OmniPlex 560  
Dell OmniPlex 566  
Dell OmniPlex 590  
Dell OptiPlex 486/LE MTE  
Dell OptiPlex 560/L Low Profile (P-60)  
Dell OptiPlex DGX 590  
Dell OptiPlex DGX 5100  
Dell OptiPlex DGX 5120  
Dell OptiPlex DGX 5133 (P-133)  
Dell OptiPlex DGX 5166 (P-166)  
Dell OptiPlex GL 575 (P-75)  
Dell OptiPlex GL 590 (P-90)  
Dell OptiPlex GL 5100 (P-100)  
Dell OptiPlex GL 5120 (P-120)  
Dell OptiPlex GL 5133 (P-133)  
Dell OptiPlex GL 5150 (P-150)  
Dell OptiPlex GL+ 575 (P-75)  
Dell OptiPlex GL+ 590 (P-90)  
Dell OptiPlex GL+ 5100 (P-100)  
Dell OptiPlex GL+ 5120 (P-120)  
Dell OptiPlex GL+ 5133 (P-133)  
Dell OptiPlex GL+ 5150 (P-150)  
Dell OptiPlex GM 5133 (P-133)  
Dell OptiPlex GM 5150 (P-150)  
Dell OptiPlex GM+ 575 (P-75)  
Dell OptiPlex GM+ 590 (P-90)  
Dell OptiPlex GM+ 5100 (P-100)  
Dell OptiPlex GM+ 5120 (P-120)  
Dell OptiPlex GM+ 5133 (P-133)  
Dell OptiPlex GM+ 5150 (P-150)

---

---

**Single Processor Systems (Continued)**

---

**Dell, cont.**  
Dell OptiPlex GMT 575 (P-75)  
Dell OptiPlex GMT 590 (P-90)  
Dell OptiPlex GMT 5100 (P-100)  
Dell OptiPlex GMT 5120 (P-120)  
Dell OptiPlex GMT 5133 (P-133)  
Dell OptiPlex GMT 5150 (P-150)  
Dell OptiPlex GMT+ 575 (P-75)  
Dell OptiPlex GMT+ 590 (P-90)  
Dell OptiPlex GMT+ 5133 (P-133)  
Dell OptiPlex GMT+ 5150 (P-150)  
Dell OptiPlex GS 5120 L+M Chassis (P-120)  
Dell OptiPlex GS 5133 L+M Chassis (P-133)  
Dell OptiPlex GS 5150 L+M Chassis (P-150)  
Dell OptiPlex GS 5166 MMX L+M Chassis (P-166)  
Dell OptiPlex GS 5200 MMX L+M Chassis (P-200)  
Dell OptiPlex GS+ 5166  
Dell OptiPlex GS+ 5200 (P-200)  
Dell OptiPlex GX 575 (P-75)  
Dell OptiPlex GX 590 (P-90)  
Dell OptiPlex GX 5100 (P-100)  
Dell OptiPlex GX 5120 (P-120)  
Dell OptiPlex GX 5133 (P-133)  
Dell OptiPlex GX 5150 (P-150)  
Dell OptiPlex GX Pro 200  
Dell OptiPlex GXi 5166 (P-166)  
Dell OptiPlex GXi 5200 (P-200)  
Dell OptiPlex GXi 5133 L+M Chassis (P-133)  
Dell OptiPlex GXi 5133 MMX L+M Chassis (P-133)  
Dell OptiPlex GXi 5166 MMX L+M Chassis (P-166)  
Dell OptiPlex GXi 5200 MMX L+M Chassis (P-200)  
Dell OptiPlex GXi 5233 MT (P-233 MMX)  
Dell OptiPlex GXL 575 (P-75)  
Dell OptiPlex GXL 590 (P-90)  
Dell OptiPlex GXL 5100 (P-100)  
Dell OptiPlex GXL 5120 (P-120)  
Dell OptiPlex GXL 5133 (P-133)  
Dell OptiPlex GXL 5150 (P-150)  
Dell OptiPlex GXL 5166 (P-166)

---



---

**Single Processor Systems (Continued)**

---

**Dell, cont.**

Dell OptiPlex GXM 575 (P-75)  
Dell OptiPlex GXM 590 (P-90)  
Dell OptiPlex GXM 5100 (P-100)  
Dell OptiPlex GXM 5120 (P-120)  
Dell OptiPlex GXM 5133 (P-133)  
Dell OptiPlex GXM 5150 (P-150)  
Dell OptiPlex GXM 5166 (P-166)  
Dell OptiPlex GXMT 575 (P-75)  
Dell OptiPlex GXMT 590 (P-90)  
Dell OptiPlex GXMT 5100 (P-100)  
Dell OptiPlex GXMT 5120 (P-120)  
Dell OptiPlex GXMT 5133 (P-133)  
Dell OptiPlex GXMT 5150 (P-150)  
Dell OptiPlex GXMT 5166 (P-166)  
Dell OptiPlex XL 575 (P-75)  
Dell OptiPlex XL 590 (P-90)  
Dell OptiPlex XL 5100 (P-100)  
Dell OptiPlex XL 5120 (P-120)  
Dell OptiPlex XM 575 (P-75)  
Dell OptiPlex XM 590 (P-90)  
Dell OptiPlex XM 5100 (P-100)  
Dell OptiPlex XM 5120 (P-120)  
Dell OptiPlex XMT 575 (P-75)  
Dell OptiPlex XMT 590 (P-90)  
Dell OptiPlex XMT 5100 (P-100)  
Dell OptiPlex XMT 5120 (P-120)  
Dell OptiPlex XMT 5133 (P-133)  
Dell PowerEdge 466/XE  
Dell PowerEdge SP 590  
Dell PowerEdge 2100 (PP-180)  
Dell PowerEdge 2100 (PP-200)  
Dell SP5100-2 (P-100)

Diversified Technologies (DTI) LBE4520 (P-90)  
Diversified Technologies (DTI) LBE4520 (P-100)

DTK FEAT-39 (DX4-100)  
DTK QUIN-35D PCI (P-90)  
DTK QUIN-35M PCI (P-90)  
DTK QUIN-54/I (P-133)

---

---

**Single Processor Systems (Continued)**

---

EIS Computers "The Client" (486/66 VLB)  
EIS Computers "The Client P60" (P-60)  
EIS Computers "The Developer" (486/66 EISA/VLB)  
EIS Computers "The Developer P90" (P-90 PCI)  
EIS Computers "The Developer P90i" (P-90 PCI)  
EIS Computers "The Developer P100" (P-100 PCI)  
EIS Computers "The Developer P100i" (P-100 PCI)  
EIS Computers "The Developer P120" (P-120 PCI)  
EIS Computers "The Developer P120i" (P-120)  
EIS Computers "The Developer P120s" (P-120)  
EIS Computers "The Developer P133" (P-133)  
EIS Computers "The Developer P133i" (P-133)  
EIS Computers "The Developer P133s" (P-133)  
EIS Computers "The Developer-Pro 150i" (PP-150)  
EIS Computers "The Developer-Pro 150s" (PP-150)  
EIS Computers "The Developer-Pro 200s"

Elonex MT-5166/I (P-166)  
Elonex PC-590-I  
Elonex PT 62233AX AMD K6 233  
Elonex PT 62266 II (PII-266)

Everex Step DP (tested with 1 CPU, P-90)  
Everex Step DPi (P-133)

---



---

**Single Processor Systems (Continued)**

---

Fujitsu FM-5000SV Model 250 (P-166)  
Fujitsu FM-5200SV Model 250 (P-166)  
Fujitsu FMV-466D (486DX2-66)  
Fujitsu FMV-575D4L (P-75)  
Fujitsu FMV-575D5 (P-75)<sup>2</sup>  
Fujitsu FMV-590D3 (P-90)  
Fujitsu FMV-590DE (P-90)  
Fujitsu FMV-5100D4L (P-100)  
Fujitsu FMV-5100D6 (P-100)  
Fujitsu FMV-5100DE3 (P-100)<sup>2</sup>  
Fujitsu FMV-5133D5 (P-133)<sup>2</sup>  
Fujitsu FMV-5133D6 (P-133)  
Fujitsu FMV-5133D7 (P-133)  
Fujitsu FMV-5133DE3 (P-133)<sup>2</sup>  
Fujitsu FMV-5133DE4 (P-133)  
Fujitsu FMV-5133T3 (P-133)<sup>2</sup>  
Fujitsu FMV-5150T4 (P-150)  
Fujitsu FMV-5166D5 (P-166)  
Fujitsu FMV-5166D6 (P-166)  
Fujitsu FMV-5166D8M (P-166 MMX)  
Fujitsu FMV-5166DE4 (P-166)  
Fujitsu FMV-5166DE5 (P-166)  
Fujitsu FMV-5166T5 (P-166)  
Fujitsu FMV-5200SV Model 250 (P-166)  
Fujitsu FMV-5200DE6 (P-200)  
Fujitsu FMV-5200T4 (P-200)  
Fujitsu FMV-5200T6M (P-200 MMX)  
Fujitsu FMV-6150T3 (PP-150)  
Fujitsu FMV-6200T4 (PP-200)  
Fujitsu FMV-6200T5 (PP-200)  
Fujitsu FMV-6233D8 (PII-233)  
Fujitsu FMV-6266T6 (PII-266)  
Fujitsu GranPower5000 Model 560S (PP-200)  
Fujitsu ICL ErgoPro Desktop X450-90 (P-90)  
  
FutureTech 4100V (486 DX4-100)  
FutureTech 462iV (i486 DX2-66)  
FutureTech 5601P (P-60)  
FutureTech FTS4414 (AMD486 DX-40)

---

---

**Single Processor Systems (Continued)**

---

Gateway 2000 486/33E  
Gateway 2000 4DX2-66 (low profile)<sup>3</sup>  
Gateway 2000 4DX2-66E  
Gateway 2000 4DX2-66V  
Gateway 2000 4SX-33 (low profile)<sup>3</sup>  
Gateway 2000 G6-150 (PP-150)  
Gateway 2000 G6-200 (PP-200)  
Gateway 2000 P4D-66<sup>3</sup>  
Gateway 2000 P4D-100 (486DX4-100)  
Gateway 2000 P5-60  
Gateway 2000 P5-66<sup>3</sup>  
Gateway 2000 P5-75 (P-75)  
Gateway 2000 P5-90 Tower  
Gateway 2000 P5-120 Tower  
Gateway 2000 P5-100 (P-100)<sup>8</sup>  
Gateway 2000 P5-100 new revised motherboard (P-100)  
Gateway 2000 P5-100XL (P-100)<sup>8</sup>  
Gateway 2000 P5-120 (P-120)<sup>9</sup>  
Gateway 2000 P5-133XL (P-133)  
  
GCH Systems EasyData 590 (P4C-90)  
GCH Systems Aegis 466 (i486DX2-66)  
GCH Systems Aegis 466ES (i486DX2-66)  
  
GoldStar GT51P PCI (P-60)  
  
Hitachi FLORA 1010DK (P-60)  
Hitachi FLORA 1010DL  
Hitachi FLORA 1010DM (P-100)  
Hitachi FLORA 1010DN  
Hitachi FLORA DM3 (P-200)  
Hitachi FLORA DS1 (P-75)  
Hitachi FLORA DS1 (P-100)  
Hitachi FLORA DS1 (P-133)  
Hitachi FLORA SA1 (P-166)  
Hitachi FLORA SA1 (P-200)  
Hitachi FLORA SM1 (PP-200)

---



---

**Single Processor Systems (Continued)**

---

HP NetServer 4d/66LE (486DX2-66)<sup>10</sup>  
HP NetServer 4d/66LM<sup>11</sup>  
HP NetServer 5/66 LC (P-66)  
HP NetServer 5/66 LF (P-66)  
HP NetServer 5/133 LS (P-133)  
HP NetServer LC 5/66 (P-66)  
HP NetServer LM 5/100 (P-100)  
HP Vectra VL 5/90 Series 3 PC (P-90)  
HP Vectra VL2 4/100 PC (486DX4-100)  
HP Vectra VL2 5/60 PC (P-60)  
HP Vectra VL2 5/90 PC (P-90)  
HP Vectra VT 6/150 PC (PP-150)  
HP Vectra XA 6/200 PC (PP-200)  
HP Vectra XM 5/90 Series 3 (P-90)  
HP Vectra XM 5/100 Series 4 PC (P-100)  
HP Vectra XM2 4/66i PC (486DX2-66)  
HP Vectra XU 5/90 PC (P-90)  
HP Vectra XU 5/90C PC (P-90)<sup>12</sup>  
HP Vectra XU 5/133C PC (P-133)  
HP Vectra XU 6/150 PC (PP-150)  
HP Vectra XU 6/200 PC (PP-200)  
  
Hyundai Phantom P-90 Desktop  
  
I BUS ORCA (486DX4/100)  
I BUS SHARK (P-133)  
  
IBM Aptiva H5F (P-150)  
IBM PC Server 310 Model 8639-ODO (P-133)  
IBM PC Server 310 Model 8639-OEO (P-166)  
IBM PC Server 310 Model 8639-OEV P-166)  
IBM PC Server 310 Model 8639-OXT (P-75)  
IBM PC Server 315 Model 8638-PJV (PP-180)  
IBM PC Server 315 Model 8638-PSV (PP-200)  
IBM PC Server 320 Model 8640-EEV (P-166)  
IBM PC Server 320 Model 8640-ODO (P-133)  
IBM PC Server 320 Model 8640-ODV (P-133)  
IBM PC Server 320 Model 8640-ONJ (486DX2-66)  
IBM PC Server 320 Model 8640-OPT (P-180)

---

---

**Single Processor Systems (Continued)**

---

**IBM, cont.**

IBM PC Server 325 Model 8640-ES0 (PP-200)  
IBM PC Server 325 Model 8639-EJO (PP-180)  
IBM PC Server 325 Model 8640-ESV (PP-200)  
IBM PC Server 330 Model 8640-EM2 (PP-200)  
IBM PC Server 330 Model 8640-ESS (PP-200)  
IBM PC Server 500 Model 8641-OYT (P-90)  
IBM PC Server 500 Model 8641-OYT (P-90)  
IBM Personal Computer 300 Series Model 6571  
IBM Personal Computer 300 Series Model 6575  
IBM Personal Computer 300 Series Model 6581  
IBM Personal Computer 300 Series Model 6585  
IBM Personal Computer 300 XL Model 6588-10U (PII-233)  
IBM Personal Computer 330 Model 6576 (P-75)  
IBM Personal Computer 330 Model 6576 (P-133)  
IBM Personal Computer 340 Model 6560-79M (P-133)  
IBM Personal Computer 350 Model 6587-LBV (P-200  
MMX)  
IBM Personal Computer 350-100DX4  
IBM Personal Computer 360 Model 6589 (PP-200)  
IBM Personal Computer 360 Model 6589-12U (PP-200)  
IBM Personal Computer 360 Model 6598 (PP-150)  
IBM Personal Computer 365 Model 6589-10U (PP-200)  
IBM Personal Computer 365 Model 6589-12U (PP-200)  
IBM Personal Computer 700 Series Model 6875  
IBM Personal Computer 730 Model 6877-KAZ (P-100)  
IBM Personal Computer 750 Model 6885 (P-75)  
IBM Personal Computer 750 Model 6885-35H (P-75)  
IBM Personal Computer 750 Model 6885-JOM (P-90)  
IBM PS/2 Model 76 (9576-xxx)  
IBM PS/2 Model 95 XP486 (9595-OL)  
IBM PS/2 Model 95 XP486 (9595-OM)  
IBM PS/2 Server 95 (9595-3QT)<sup>6</sup>  
IBM PS/2 Server 95 (9595-OPT)<sup>6</sup>  
IBM PS/ValuePoint 466DX2/D  
IBM PS/ValuePoint P60/D  
IBM PS/ValuePoint Performance Series 486 DX2/66 Dp  
  
Industrial CPU Systems PC (P-133)

---



---

**Single Processor Systems (Continued)**

---

Infotel Ultra P-75 PCI  
Infotel Ultra P-90 PCI Minitower  
Infotel Ultra P-100 PCI  
Infotel Ultra P-120 PCI  
  
Intel Advanced/AL (Aladdin-Triton) (P-90)  
Intel Advanced/AS (Atlantis) (P-166)  
Intel Advanced/ATX  
Intel Advanced/EV Pentium/100  
Intel Advanced/EV (Endeavor) (P-75)  
Intel Advanced/EV (Endeavor) (P-90)  
Intel Advanced/EV (Endeavor) (P-100)  
Intel Advanced/EV (Endeavor) (P-120)  
Intel Advanced/EV (Endeavor) (P-133)  
Intel Advanced/EV (Endeavor) (P-150)  
Intel Advanced/EV (Endeavor) (P-166)  
Intel Advanced/ML (Marl) (P-133)  
Intel Advanced/MN (Morrison) (P-100)  
Intel Advanced/PO (P-133)  
Intel Advanced/RH (Rhinstone) (P-133)  
Intel Advanced/RH (Rhinstone) (P-200)  
Intel Advanced/RH (Rhinstone) (P-200 MMX)  
Intel Advanced/VS (Venus) (PP-180)  
Intel Advanced/VS (Venus) (PP-200)  
Intel Advanced/ZE Mini-tower (P-100)  
Intel Advanced/ZP (Zappa-Triton) (P-90)  
Intel ALTserver Altair (P-150)  
Intel ALTserver Altair (P-166)  
Intel AP450GX MP Server (1 CPU version) (PP-200)  
Intel Express 486/DX33  
Intel Express Pentium/60  
Intel Express Pentium/90  
Intel L486-Series Professional GX (486DX2-66)  
Intel Pentium Pro Performance/AU  
Intel Pentium Pro Performance/AU ATX  
Intel Performance/AU (PP-180)  
Intel Performance/AU (PP-200)  
Intel Premiere/PCI LX (Plato) (P-90)  
Intel R440FX UP Server (PP-200)  
Intel RC440FX UP Server (PP-200)

---

---

**Single Processor Systems (Continued)**

---

Intergraph TD-1 (486DX2-66)  
Intergraph TD-2 (P-66)  
Intergraph TD-3 (P-90)  
Intergraph TD-3 (P-100)  
Intergraph TD-30 (P-90)<sup>13</sup>  
Intergraph TD-300 (PP-150)  
Intergraph TD-300 (PP-200)  
Intergraph TD-310 (PP-200)  
Intergraph TD-320 (PP-200)  
Intergraph TD-325 (PII-266)  
  
Inves BS-486-VS i486 DX2-50  
  
IPEX Desktop Model PCI-I-133 (P-133)  
  
Leading Edge Fortiva Series 3000 (486DX2-50)  
Leading Edge Fortiva Series 4000 (Cyrix 486DLC-40)<sup>1</sup>  
Leading Edge Fortiva Series 5000 (486DX2-66)  
Leading Edge MT 6000 (P-90)  
Leading Edge MT 6000 Tower (P-90)  
Leading Edge Valience Desktop DT4000  
  
Metrologie P60 Tower (Intel Express P-60)  
Metrologie Premiere/PCI P60 Desktop (Intel Mercury)  
  
Microbus European Data Systems iBOX (486DX-33)<sup>14</sup>

---



---

**Single Processor Systems (Continued)**

---

Micron 486PCI MAGNUM (486 DX4-100)  
Micron ClientPro MTA 200 (P-200)  
Micron ClientPro MTE 200 MMX (IDE)  
Micron ClientPro MTE 200 MMX BusLogic SCSI  
Micron ClientPro XLU (PII-233)  
Micron Home MPC (P-90)  
Micron Home MPC (P-166)  
Micron Magnum Plus Pro200 IDE version (PP-200)  
Micron Magnum Plus Pro200 SCSI version (PP-200)  
Micron Magnum Plus Pro200 2940U SCSI version  
(PP-200)  
Micron Millennia (P-100)  
Micron Millennia (P-166)  
Micron Millennia MME (P-200 MMX IDE)  
Micron Millennia Plus (P-133)  
Micron Millennia Pro Plus (P-200)  
Micron P90PCI PowerStation<sup>15</sup>  
Micron P90PCI PowerStation Mini-Tower, Plug and Play  
(P-90)  
  
Midwest Micro P5-75 PCI  
Midwest Micro P5-100 PCI  
Midwest Micro P5-120 PCI  
Midwest Micro Desktop 486DX2-66 (486DX2/66)  
Midwest Micro Minitower P5-90  
  
Mitsubishi Electric FT2200 (PP-200)  
Mitsubishi Electric FT2400 (PP-200+RAID)  
  
NCR 3333 (486DX2/66)  
NCR 3269-200 (PP-200)  
NCR 3269-300 (PP-200)  
  
NEC Express 5800 (P-120)  
NEC Express 5800/120Pro (PP-200)  
NEC PowerMate Pro-2200 (PP-200)  
NEC PowerMate VE (P-133)  
  
NJA Triton T-01W (P-133)

---

---

**Single Processor Systems (Continued)**

---

Olivetti M4-82<sup>16</sup>  
Olivetti M6-420  
Olivetti M6-440<sup>17</sup>  
Olivetti M6-450<sup>17</sup>  
Olivetti M6-460<sup>17</sup>  
Olivetti M6-640<sup>6</sup>  
Olivetti M6-750<sup>16, 18</sup>  
Olivetti M6-760<sup>16, 18</sup>  
Olivetti M6-770<sup>16, 18</sup>  
Olivetti M6-850<sup>1,6</sup>  
Olivetti M6-860<sup>6</sup>  
Olivetti M6-880<sup>6</sup>  
Olivetti NETSTRADA 1000 Pro 200 M1 (PP-200)  
Olivetti NETSTRADA 1000 Pro 200 M1 (PP-200+RAID)  
Olivetti NETSTRADA 3000 Pro 200 M1 (PP-200)  
Olivetti NETSTRADA 3000 Pro 200 M32+ (PP-200+RAID)  
Olivetti NETSTRADA 5000 Pro 200 (PP-200+RAID)  
Olivetti NETSTRADA 7000 Pro 200  
Olivetti SNX-140<sup>1,6</sup>  
Olivetti SNX-160UP (P-90)  
  
OMEGABYTE SolarSTATION XP 75 (P-75)  
OMEGABYTE SolarSTATION XP 90 (P-90)  
OMEGABYTE SolarSTATION XP 100 (P-100)  
OMEGABYTE SolarSTATION XP 120 (P-120)  
OMEGABYTE SolarSTATION XP 133 (P-133)  
OMEGABYTE SolarSTATION XP 166 (P-166)  
OMEGABYTE SolarSTATION XPR 150 (PP-150)  
OMEGABYTE SolarSTATION XPR 200 (PP-200)  
  
Pacific Micro Data Mast Workgroup 800 RAID Subsystem  
(P-100, 512K)  
  
Packard Bell Axcel Series<sup>19</sup>  
Packard Bell Executive Series<sup>19</sup>  
Packard Bell Force Series<sup>19</sup>  
Packard Bell Legend Series<sup>19</sup>  
Packard Bell Pack-Mate Series<sup>19</sup>  
Packard Bell PRO Series<sup>19</sup>  
  
Packard Bell NEC MultiMedia F170 (P-166)  
Packard Bell NEC Z-Station GT Pro (PP-200)

---



---

**Single Processor Systems (Continued)**

---

Peacock-AG AT 486 DX-40 Professional Plus Desktop  
Peacock-AG LAN-Station AT 486 DX-40 LN4

Research Machines PC-425S (486SX/25)  
Research Machines PC-450S Accelerator (486SX2-50)  
Research Machines PC-560 Accelerator (P-60)  
Research Machines PC-590 Professional (P-90)<sup>20</sup>

R Style Proxima (P-90)

Samsung Magic Power SPC8500(P-90)  
Samsung Magic Power SPC8500 (P-133)  
Samsung Magic Power SPC8500PA (P-133)  
Samsung SWS 520/90 (P-90)  
Samsung SWS 520/100 (P-100)  
Samsung SWS 520/133 (P-133)

Siemens ANL Siix Server 1 (486 DX2-50)

Siemens Nixdorf AG PCD-5H (P-133 Desktop)  
Siemens Nixdorf AG PRIMERGY 150 (P-120)  
Siemens Nixdorf AG PRIMERGY 151 (P-166)  
Siemens Nixdorf AG PRIMERGY 060 (PII-266)  
Siemens Nixdorf AG PRIMERGY 160 (PP-200)  
Siemens Nixdorf AG PRIMERGY 160 (K423-V7xx)  
(PP-200)

Siemens Nixdorf AG Scenic Pro C5 (P-166)  
Siemens Nixdorf AG Scenic Pro C6 (PP-200)  
Siemens Nixdorf AG Scenic Pro M5 (P-200)  
Siemens Nixdorf AG Scenic Pro M6 (PP-200)  
Siemens Nixdorf AG Scenic Pro M6 (PII-266)  
Siemens Nixdorf PCD-4H/VL (486DX2-50)  
Siemens Nixdorf PCD-4H/VL (486DX2-66)  
Siemens Nixdorf PCD-4H/PCI (486DX2-66)  
Siemens Nixdorf PCD-5H (P-60 PCI)<sup>21</sup>  
Siemens Nixdorf PCD-5H (P-90)  
Siemens Nixdorf PCD-5T  
Siemens Nixdorf PCE-5S

TAGRAM Platinum (P-66)  
TAGRAM ThunderBolt (P-66)

---

---

**Single Processor Systems (Continued)**

---

TAKAOKA Electric MiNT PC5133s3  
TAKAOKA Electric MiNT PC590d2 Desktop (P-90)  
TAKAOKA Electric MiNT PC590t2 Tower (P-90)  
TAKAOKA Electric MiNT PC5166d4 Desktop (P-166)  
TAKAOKA Electric MiNT PC5166t4 Tower (P-166)  
TAKAOKA Electric MiNT PC5200d4 Desktop (P-200)  
TAKAOKA Electric MiNT PC5200t4 Tower (P-200)  
TAKAOKA Electric MiNT PC6200d Desktop (PP-200)

Toshiba Desktop BREZZA 5200MB PV1010JA (P-200)  
Toshiba Desktop Equium 5200D (P-200 MMX)  
Toshiba GS700 S200 (PP-200)  
Toshiba J-3100 PV (486SX-25 ODP)  
Toshiba J-3100 PV2 (486DX2-66)

Triton Data TE-01W440FXUP (PP-200)

Tulip 4-Series DE PCI (486DX2-66)  
Tulip 5-Series DE PCI (P-90)  
Tulip 4-Series DE EISA (486DX2-66)  
Tulip 4-Series DS PCI (486DX2-66)  
Tulip 5-Series DS PCI (P-90)  
Tulip 4-Series DS EISA (486DX2-66)  
Tulip 4-Series DT ISA (486DX2-66)  
Tulip 4-Series DT PCI (486DX2-66)  
Tulip 5-Series DT PCI (P-90)  
Tulip 4-Series TR EISA (486DX2-66)  
Tulip Vision Line DE5-200 (PP-200)<sup>22</sup>  
Tulip Vision Line DS6-200 (PP-200)<sup>23</sup>  
Tulip Vision Line DS6-200S (PP-200)<sup>24</sup>  
Tulip Vision Line DT5-133 (P-133)<sup>25</sup>  
Tulip Vision Line DT5-133S (P-133)<sup>26</sup>  
Tulip Vision Line TR6-SMP1 (PP-200)<sup>27</sup>

---



---

**Single Processor Systems (Continued)**

---

Unisys Aquanta DM II-CMT 57574 (P-75)  
Unisys Aquanta DM II-CMT 515074 (P-150)  
Unisys Aquanta DM II-CMT 520074 (P-200)  
Unisys Aquanta DM/6 II-CMT 618072 (PP-180)  
Unisys Aquanta DM/6 II-CMT 620072 (PP-200)  
Unisys Model SVD-II P166 with 2940SCSI  
Unisys Model SVD-II P166 with int7870SCSI  
Unisys U6000/DT2  
Unisys U6000/100  
Unisys U6000/300

Viglen Contender Professional 4DX266  
Viglen Genie 2 (PII-266 MMX)  
Viglen Genie PCI (P-133)  
Viglen Genie PCI Pro 200  
Viglen Genie PCI Professional 4DX266  
Viglen Genie PCI Tower (P-90)  
Viglen LX Server (P-200)  
Viglen LX Server Pro (PP-200)  
Viglen XX Pro Server (PP-200)

WellStone EZ-Go Type-1 Tower (P-90)  
WellStone EZ-Go Type-2 Tower (P-120)  
WellStone SWS 5090 (P-90)  
WellStone SWS 6200 Tower (PP-200)

Wyse Decision 486se  
Wyse Decision 486Gsi (DX2/66)  
Wyse Series 6000i Model 650  
Wyse Series 6000i Model 665

---

---

**Single Processor Systems (Continued)**

---

Zenith Data Systems Z-Select 100 XE Minitower  
(486DX2-66)  
Zenith Data Systems Z-Select PT (P-60)  
Zenith Data Systems Z-Server EL Pro (PP-200)  
Zenith Data Systems Z-Server EX P90E Model 1000  
Zenith Data Systems Z-Server EX P90E Model 1000A  
Zenith Data Systems Z-Server LT 433DE Model 1000  
Zenith Data Systems Z-Server LT 433DE Model 1000A  
Zenith Data Systems Z-Server LT 450DE Model 1000  
Zenith Data Systems Z-Server LT 450DE Model 1000A  
Zenith Data Systems Z-Server LT 466XE Model 1000  
Zenith Data Systems Z-Server LT P60E Model 1000  
Zenith Data Systems Z-Server LT P60E Model 1000A  
Zenith Data Systems Z-Server MX (P-100)  
Zenith Data Systems Z-Server MX+Mylex (P-100)  
Zenith Data Systems Z-Server WG P90 (P-90)  
Zenith Data Systems Z-Station 510 Minitower  
(486DX4-100)  
Zenith Data Systems Z-Station EL (P-133)  
Zenith Data Systems Z-Station EX Model II (P-90)  
Zenith Data Systems Z-Station GT-575 (P-75)  
Zenith Data Systems Z-Station GT-5100  
Zenith Data Systems Z-Station GT-5120  
Zenith Data Systems Z-Station GT-5133 (P-133)  
Zenith Data Systems Z-Station GT-5150  
Zenith Data Systems Z-Station GT-5166  
Zenith Data Systems Z-Station GT Pro (IDE) (PP-200)  
Zenith Data Systems Z-Station GT Pro-S (SCSI) (PP-200)  
Zenith Data Systems Z-Station LX Pro (PP-180)  
Zenith Data Systems Z-Station LX Pro-S (PP-180)  
Zenith Data Systems Z-Station LX Pro (PP-200)  
Zenith Data Systems Z-Station LX Pro-S (SCSI) (PP-200)  
Zenith Data Systems Z-Station VP (486DX4/100)  
Zenith Data Systems Z-Station VP (P-90)  
Zenith Data Systems Z-Station VP (P-100)  
Zenith Data Systems Z-Station VP (P-120)  
Zenith Data Systems Z-Station VP (P-133)

---

1. Requires substituting the video card with one supported by Solaris 2.5/2.5.1.
2. Requires substituting the network card with one supported by Solaris 2.5/2.5.1.
3. Must use a CD-ROM drive supported by Solaris 2.5/2.5.1.



4. This model is an MP server but has only been tested with one CPU.
5. Additional configuration is required to install Solaris 2.5/2.5.1 on this system; refer to the notes on "Memory Mapping Problems" in *x86: Solaris 2.5x Installation Notes* for information.
6. Server System. Integrated video currently only works in 640x480 VGA mode.
7. Refer to the certification report for this system at <http://access1.sun.com/certify/reports/DEC/>.
8. Requires non-default BIOS settings for proper operation.
9. The three-disk CD-ROM changer is not supported at this time.
10. Select "Trident 9000" when configuring the display adapter, and be sure to upgrade the video RAM on the motherboard.
11. System must be upgraded to a minimum of 1-Mbyte video memory and a minimum of 32-Mbytes system memory.
12. Due to a manufacturer's part change, integrated video not supported on some versions at time of certification test.
13. PC Card support not available at time of system certification.
14. The design of the Cache controller requires that you map out the memory range used by the SCSI controller, or the system will not work; the on-board hardware watchdog circuit R39 must also be disabled.
15. Warning: FLASH BIOS must be write-protected *before* attempting to install the Solaris software; remove jumper JP9 on the motherboard and use BIOS revision -10 or later.
16. Only tested with vendor's ATI Mach32 video option.
17. Integrated audio chip not currently supported.
18. Must set Adaptec SCSI BIOS to address CC000.
19. This series of machines comes in various models and configurations. If the FCC ID label on the back panel of your machine contains one of the three-digit codes 430, 450, 470, 520, or 550, then it is based on a platform that was tested for compatibility and should run Solaris 2.5/2.5.1 x86. However, ensure that other optional equipment and subsystems on your specific model are listed in this document.
20. The newer version of this system had BIOS compatibility issues at the time of test. Also, attach the CD-ROM to the primary IDE channel.
21. Built-in ATI video card currently only supported in 43-Hz mode.
22. For Solaris compatibility, specify an STB S3 Trio video system by requesting option DE-15-200-2-SFC12-E16/1-DU-3P4I-U at time of order.
23. For Solaris compatibility, specify an STB S3 Trio video system by requesting option DS-16-200-1.2-IFC8-E32/1S-DF-4P4I-U at time of order.
24. For Solaris compatibility, specify an STB S3 Trio video system by requesting option DS-16-200-2-SFC8-E32/1S-DF-4P4I-U at time of order.
25. For Solaris compatibility, specify an STB S3 Trio video system by requesting option DT-15-133-1.2-IFC8-E16/1S-CU-2P2I-U at time of order.
26. For Solaris compatibility, specify an STB S3 Trio video system by requesting option DT-15-133-2-SFC8-E16/1S-CU-2P2I-U at time of order.
27. For Solaris compatibility, specify an STB S3 Trio video system by requesting option TR-16-200-4.0W-SFC4-P64/1S-4P2I-U at time of order.

---

## Multiprocessor Systems (SMP)<sup>1</sup>

---

- Acer AcerAltos 7000/P (2 CPUs, P-90)
  - Acer AcerAltos 9000/Pro-200 SMP (2 CPUs, PP-200)
  - Acer AcerAltos 19000 SMP (2 CPUs, PP-200)
  - Acer AcerAltos 19000 SMP Plus Raid (2 CPUs, PP-200)
  - Acer AcerFrame Model 3000MP (2 CPUs)
  
  - ALR Evolution (2 CPUs, PP-200)
  - ALR Evolution Dual6 (2 CPUs, PP-200)
  - ALR Evolution V STe/75 (2 CPUs, P-75)
  - ALR Evolution Q/MP2 100 (2 CPUs, P-100)
  - ALR Proveisa SMP (2 CPUs)
  - ALR Rack Mountable Revolution Quad6-200 w/ 256 cache (4 CPUs, PP-200)
  - ALR Revolution 6X6 (3 CPUs, PP-200)
  - ALR Revolution 6X6 (6 CPUs, PP-200)
  - ALR Revolution Dual6 (2 CPUs, PP-200)
  - ALR Revolution MP 100 (2 CPUs, P-100)
  - ALR Revolution MP 166 (2 CPUs, P-166)
  - ALR Revolution MP II (2 CPUs, P-166)
  - ALR Revolution MP II (2 CPUs, P-200)
  - ALR Revolution MP Pentium 90 (2 CPUs)
  - ALR Revolution Q-SMP PCI-Version (2 CPUs, P-100)
  - ALR Revolution Q-SMP PCI-Version (4 CPUs, P-166)
  - ALR Revolution Q-SMP Pentium/90 (2, 3, & 4 CPUs)
  - ALR Revolution Q-SMP Pentium/100 (2 CPUs)
  - ALR Revolution Q-SMP Pentium/100 (4 CPUs)
  - ALR Revolution Quad6-200 (2 CPUs, PP-200)
  - ALR Revolution Quad6-200 (3 CPUs, PP-200)
  - ALR Revolution Quad6-200 (4 CPUs, PP-200)
  - ALR Revolution VQ/4SMP (4 CPUs, P-166)
  
  - Amdahl Envista Server (4 CPUs, PP-166)
  
  - American Megatrends Titan-II PCI EISA (2 CPUs)
  
  - AMG Pro200SMP-2N Server (2 CPUs, PP-200)
-



---

**Multiprocessor Systems (SMP)<sup>1</sup> (Continued)**

---

AST Manhattan SMP 486/33 (4 CPUs)  
AST Manhattan SMP P/60 (4 CPUs)  
AST Manhattan P5090 (2 CPUs, P-90)<sup>2</sup>  
AST Manhattan P5100 (2 CPUs)  
AST Manhattan P5133 (2 CPUs)  
AST Manhattan S6200 Model 2003LC (2 CPUs, PP-200)  
AST Manhattan V5090 (2 CPUs, P-90)<sup>2, 3</sup>  
AST Manhattan V5100 (2 CPUs)  
AST Premmia GX (2 CPUs, P-90) Integrated E-IDE  
AST Premmia GX (2 CPUs, P-90) Integrated SCSI<sup>3</sup>  
AST Premmia GX (2 CPUs, P-100)  
AST Premmia GX (2 CPUs, P-133)  
  
AT&T GIS Globalyst S40 (4 CPUs, P-100)  
  
Austin Direct Affinity SE (2 CPUs, P-90)  
  
C&S Vertriebs GmbH (2 CPUs, P-90, EISA/PCI)  
C&S Vertriebs GmbH AMICUS Strategy (2 CPUs, P-133)  
  
Compaq Professional Workstation 5000 (2 CPUs, PP-200)  
Compaq Professional Workstation 6000 (2 CPUs, PII-266)  
Compaq Professional Workstation 8000 (2 CPUs, PP-200)  
Compaq ProLiant 800 (2 CPUs, P6-200)  
Compaq ProLiant 850R (2 CPUs, PP-200)  
Compaq ProLiant 1500 (2 CPUs, P-133)  
Compaq ProLiant 1500 (2 CPUs, PP-200)  
Compaq ProLiant 2000 (2 CPUs, P-90)  
Compaq ProLiant 2500 (2 CPUs, PP-200)  
Compaq ProLiant 4000 (4 CPUs, P-90)  
Compaq ProLiant Server 4500/166 (2 CPUs, P-166)  
Compaq ProLiant Server 4500/166 (4 CPUs, P-166)  
Compaq ProLiant 5000 (4 CPUs, PP-166)<sup>4</sup>  
Compaq ProLiant 6000 (2 CPUs, PP-200)  
Compaq ProLiant 6000 (4 CPUs, PP-200)  
  
Data General Aviion 3000 Server (2 CPUs, P-100)

---

---

**Multiprocessor Systems (SMP)<sup>1</sup> (Continued)**

---

DEC Celebris XL 590DP (2 CPUs, P-90)  
DEC Celebris XL 5166DP (2 CPUs, P-166)  
DEC Prioris HX 590DP (2 CPUs, P-90)  
DEC Prioris MX 6200 (2 CPUs, PP-200)<sup>5</sup>  
DEC Prioris MX 6200 (2 CPUs, PP-200, 512K)<sup>5</sup>  
DEC Prioris MX 6200 (2 CPUs, PP-200+RAID)<sup>5</sup>  
DEC Prioris MX 6200 (2 CPUs, PP-200+RAID, 512K)<sup>5</sup>  
DEC Prioris XL Server 5200DP (2 CPUs, PP-200)  
DEC Prioris ZX 6166 MP2 (2 CPUs, PP-166)  
DEC Prioris ZX 6200 MP2 (2 CPUs, PP-200)  
  
Dell OptiPlex DGX 590 (2 CPUs, P-90)  
Dell OptiPlex DGX 5100 (2 CPUs, P-100)  
Dell OptiPlex DGX 5120 (2 CPUs, P-120)  
Dell OptiPlex DGX 5133 (2 CPUs, P-133)  
Dell OptiPlex DGX 5166 (2 CPUs, P-166)  
Dell OptiPlex GX Pro 180 (2 CPUs, PP-180)  
Dell OptiPlex GX Pro 200 (2 CPUs, PP-200)  
Dell PowerEdge 4100 (2 CPUs, PP-180)  
Dell PowerEdge 4100 (2 CPUs, PP-200)  
Dell PowerEdge SP 5100 (2 CPUs, P-100)  
Dell PowerEdge XE 590-2 with DSA (2 CPUs, P-90)  
  
Diversified Technologies (DTI) LBE-4520 DP  
(2 CPUs, P-90)  
  
DTK QUIN-52M DP90 (2 CPUs, P-90)  
  
EIS Computers Mega Developer 200-4 (4 CPUs, PP-200)  
EIS Computers Monster Developer Pro (2 CPUs, PP-200)  
EIS Computers Monster Developer Pro (4 CPUs, PP-200,  
512K)  
EIS Computers Super Developer Pro (2 CPUs, PP-200)  
EIS Computers Super Developer Pro II (2 CPUs, PP-200,  
512K)  
EIS Computers "The Developer" (2 CPUs, P-90 MP)  
EIS Computers "The Developer" (2 CPUs, P-100 MP)  
EIS Computers "The Developer-Pro 200" (2 CPUs,  
PP-200)  
EIS Computers "The Server" (2 CPUs, P-90 MP)  
EIS Computers "The Server" (2 CPUs, P-100 MP)  
  
Elonex MT-5133-I (2 CPUs, P-133)  
Elonex MTX 62200 (2 CPUs, PP-200)

---



---

**Multiprocessor Systems (SMP)<sup>1</sup> (Continued)**

---

Everex Step DP (2 CPUs, P-90)  
Everex Step DPi (2 CPUs, P-133)  
  
Fujitsu GranPower5000 Model 560S (2 CPUs, PP-200)  
Fujitsu GranPower5000 Model 760 (2 CPUs, PP-200)  
  
Hitachi FLORA 3010DV (2 CPUs, P-90)  
Hitachi FLORA 3100BP (2 CPUs, P-90)  
Hitachi FLORA 3100LP (4 CPUs, P-133)  
Hitachi FLORA 3100LP (8 CPUs, P-100)  
Hitachi FLORA 3100SP (2 CPUs, P-90)<sup>6</sup>  
Hitachi FLORA SB1 (2 CPUs, PP-200)  
Hitachi FLORA SM1 PC 6SM01 1800HA (2 CPUs, PP-180)  
Hitachi FLORA SM1 PC 6SM01 18080A (2 CPUs, PP-180  
+ RAID)  
Hitachi FLORA SM2 (2 CPUs, PP-200)  
Hitachi FLORA SR1 (2 CPUs, PP-200)  
Hitachi FLORA SS1 (2 CPUs, PP-200)  
  
HP NetServer 5/66 LM-2 (2 CPUs)<sup>2</sup>  
HP Vectra XU 5/90C PC (2 CPUs, P-90)<sup>7</sup>  
HP Vectra XU 5/133C PC w/Matrox Video (2 CPUs,  
P-133)  
HP Vectra XU 6/150 PC (2 CPUs, P-150)

---

---

**Multiprocessor Systems (SMP)<sup>1</sup> (Continued)**

---

IBM PC Server 320 Model 8640-EE0 (2 CPUs, P-166)  
IBM PC Server 320 Model 8640-EEV (2 CPUs, P-166)  
IBM PC Server 320 Model 8640-0Z0 (2 CPUs, P-100)  
IBM PC Server 320 Model 8640-0ZV (2 CPUs, P-100)  
IBM PC Server 320 Model 8640-1D0 (2 CPUs, P-133)  
IBM PC Server 320 Model 8640-1DS (2 CPUs, P-133)  
IBM PC Server 320 Model 8640-1Z0 (2 CPUs, P-100)  
IBM PC Server 320 Model 8640-MDO (2 CPUs, P-133)  
IBM PC Server 320 Model 8640-MDS (2 CPUs, P-133)  
IBM PC Server 320 Model 8640-MDV (2 CPUs, P-133)  
IBM PC Server 320 Model 8640-MXO (2 CPUs, P-75)  
IBM PC Server 320 Model 8640-MXT (2 CPUs, P-75)  
IBM PC Server 320 Model 8640-OXO (2 CPUs, P-75)  
IBM PC Server 320 Model 8640-OXT (2 CPUs, P-75)  
IBM PC Server 320 Model 8640-OYT (2 CPUs, P-90)  
IBM PC Server 325 Model 8639-EJO (2 CPUs, PP-180)  
IBM PC Server 325 Model 8639-ES0 (2 CPUs, P-200)  
IBM PC Server 325 Model 8639-ES0 (2 CPUs, PP-200)  
IBM PC Server 325 Model 8639-ESV (2 CPUs, P-200)  
IBM PC Server 325 Model 8639-ESV (2 CPUs, PP-200)  
IBM PC Server 325 Model 8639-RS0 (2 CPUs, P-200)  
IBM PC Server 325 Model 8639-RS0 (2 CPUs, PP-200)  
IBM PC Server 325 Model 8640-ESO (2 CPUs, PP-200)  
IBM PC Server 325 Model 8640-ESV (2 CPUs, PP-200)  
IBM PC Server 330 Model 8640-EM2 (2 CPUs, PP-200)  
IBM PC Server 330 Model 8640-ESS (2 CPUs, PP-200)  
IBM PC Server 520 Model 8641-ED2 (2 CPUs, P-133)  
IBM PC Server 520 Model 8641-EDG (2 CPUs, P-133)  
IBM PC Server 520 Model 8641-EDV (2 CPUs, P-133)  
IBM PC Server 520 Model 8641-EZ1 (2 CPUs, P-100)  
IBM PC Server 520 Model 8641-EZE (2 CPUs, P-100)  
IBM PC Server 520 Model 8641-EZO (2 CPUs, P-100)  
IBM PC Server 520 Model 8641-EZS (2 CPUs, P-100)  
IBM PC Server 520 Model 8641-EZV (2 CPUs, P-100)  
IBM PC Server 520 Model 8641-MDV (2 CPUs, P-133)  
IBM PC Server 520 Model 8641-MZE (2 CPUs, P-100)  
IBM PC Server 520 Model 8641-MZL (2 CPUs, P-100)  
IBM PC Server 520 Model 8641-MZO (2 CPUs, P-100)  
IBM PC Server 520 Model 8641-MZS (2 CPUs, P-100)  
IBM PC Server 520 Model 8641-MZV (2 CPUs, P-100)

---



---

**Multiprocessor Systems (SMP)<sup>1</sup> (Continued)**

---

**IBM, cont.**

IBM PC Server 704 Model 8650-6MM (4 CPUs, PP-200)  
IBM PC Server 704 Model 8650-12U (4 CPUs, PP-166)  
IBM PC Server 720 Model 8642-1ZO (2 CPUs, P-100)  
IBM PC Server 720 Model 8642-4ZS (2 CPUs, P-100)  
IBM PC Server 720 Model 8642-OZO (2 CPUs, P-100)  
IBM Personal Computer 300 Model 6589-12U (2 CPUs, PP-200)

Intel Advanced EV Endeavour (2 CPUs, P-166)  
Intel ALTserver Altair (2 CPUs, P-100)  
Intel AP450GX MP Server (4 CPUs, PP-166)  
Intel AP450GX MP Server (4 CPUs, PP-200)  
Intel BB440FX Server (Buckeye) (2 CPUs, PP-200)  
Intel BC440FX DP Server (2 CPUs, PP-200)  
Intel Express (4 CPUs, P-100)  
Intel Express Dual Pentium 60 (2 CPUs)  
Intel Express Dual Pentium 66 (2 CPUs)  
Intel OEM Xtended Xpress (4 CPUs, P-100)  
Intel PR440FX (2 CPUs, PP-180)  
Intel Xtended Xpress Server (2 CPUs, P-133)  
Intel Xtended Xpress Server (2 CPUs, P-166)  
Intel Xtended Xpress Server (4 CPUs, P-166)

Intergraph ISP32 (2 CPUs, P-90)  
Intergraph ISMP22 (2 CPUs, P-90)  
Intergraph ISMP32 (2 CPUs, P-90)  
Intergraph ISMP6 (6 CPUs, P-100)  
Intergraph ISMP620 (2 CPUs, PP-150) (server)  
Intergraph ISMP640 (4 CPUs, PP-200)  
Intergraph TD-4 (2 CPUs, P-90)  
Intergraph TD-4 (2 CPUs, P-100)  
Intergraph TD-30 (2 CPUs, P-100)  
Intergraph TD-40 (2 CPUs, P-100)  
Intergraph TD-400 (2 CPUs, PP-150)  
Intergraph TD-410 (2 CPUs, PP-200)  
Intergraph TD-420 (2 CPUs, PP-200)  
Intergraph TD-425 (2 CPUs, PII-266)  
Intergraph TD-5 (2 CPUs, P-90)

---

---

**Multiprocessor Systems (SMP)<sup>1</sup> (Continued)**

---

Micron Millennia Pro2-400-Plus (2 CPUs, PP-200)  
Micron PowerServer SMP (P-90)  
Micron PowerServer SMP (P-133)  
Micron PowerServer SMP P-266 (2 CPUs, P-133)  
Micron Vetix 2LXI (2 CPUs, PP-200)  
Micron Vetix 2MXI (2 CPUs, PP-200)  
Micron Vetix EL 2000 (2 CPUs, PP-200)  
Micron Vetix EL 2000 IDE Version (2 CPUs, PP-200)

Mitsubishi Electric FT2200 (2 CPUs, PP-200+RAID)  
Mitsubishi Electric FT4200 (2 CPUs, PP-200+RAID)  
Mitsubishi Electric FT4200 (4 CPUs, PP-200)

NCR WorldMark 4300 (4 CPUs, PP-166)

Olivetti NETSTRADA 5000 Pro 200 Dual (2 CPUs, PP-200+RAID)  
Olivetti NETSTRADA 7000 Pro 200 Quad (4 CPUs, PP-200)  
Olivetti SNX-160MP (2 CPUs, P-90)  
Olivetti SNX-400RS (4 CPUs, P-133)

OMEGABYTE SolarSERVER XPR180/D (2 CPUs, PP-180)  
OMEGABYTE SolarSERVER XPR200/D (2 CPUs, PP-200)

Peacock AG LAN Server Model SSE 8332 (Dual Pentium 66 Intel Express)

Samsung Magic Power SPC 8500-P (2 CPUs, P-90)  
Samsung Magic Power SPC 8500-P (2 CPUs, P-100)  
Samsung Magic Power SPC 8500-P (2 CPUs, P-133)  
Samsung SmartNet Server Model 625 (2 CPUs, PP-200)  
Samsung SmartNet Server Model 645 (4 CPUs, PP-200)  
Samsung Smart Station 620 (2 CPUs, PP-180)  
Samsung SWS 520/90 (2 CPUs, P-90)  
Samsung SWS 520/100 (2 CPUs, P-100)  
Samsung SWS 520/133 (2 CPUs, P-133)

---



---

## Multiprocessor Systems (SMP)<sup>1</sup> (Continued)

---

Siemens Nixdorf AG PCD-5T (2 CPUs, P-100)  
Siemens Nixdorf AG PCE-5Smp (4 CPUs, P-133)  
Siemens Nixdorf AG PRIMERGY 350 (2 CPUs, P-90)  
Siemens Nixdorf AG PRIMERGY 351 (2 CPUs, P-133)  
Siemens Nixdorf AG PRIMERGY 360 (2 CPUs, PP-200)  
Siemens Nixdorf AG PRIMERGY 550 (2 CPUs, P-133)  
Siemens Nixdorf AG PRIMERGY 551 (2 CPUs, P-200)  
Siemens Nixdorf AG PRIMERGY 560 (4 CPUs, PP-200)  
Siemens Nixdorf AG PRIMERGY 561 (2 CPUs, PP-200)  
Siemens Nixdorf PCD-5T/PCI90de (2 CPUs, P-90)  
Siemens Nixdorf PCE-5Smp (4 CPUs, P-100)  
Siemens Nixdorf PCE-5Smp (4 CPUs, P-133)  
Toshiba SV3000 100HM (2 CPUs, P-100)  
Tricord PowerFrame Enterprise Server ES3000<sup>8</sup> (4 CPUs)  
Tricord PowerFrame Enterprise Server ES4000<sup>8</sup> (6 CPUs)  
Tricord PowerFrame Enterprise Server ES5000<sup>8</sup> (6 CPUs)  
Tulip Vision Line TR6-SMP2 (2 CPUs, PP-200)<sup>9</sup>  
Unisys 5400 (2 CPUs, P-100)  
Unisys 6000/500 Model 20 (2 CPUs)<sup>10</sup>  
Unisys Model SFE (4 CPUs, PP-166)  
Unisys Model SVD-II (2 CPUs, P-166)  
Viglen ProPenta Server (4 CPUs, PP-200)  
Viglen LX Server Pro (2 CPUs, PP-200)  
Viglen XX Pro Server (2 CPUs, PP-200)  
Viglen XX-Server-ZX (2 CPUs, P-100)  
Wyse Series 7000i, Model 760MP (4 CPUs)  
Wyse 7000-760MP DX2-66 (3 CPUs)  
Wyse 7000-765MP P66 (2 CPUs)  
Zenith Data Systems Z-Server EX DP66E Model 1000  
(2 CPUs)  
Zenith Data Systems Z-Server MX Dual P-133 (2 CPUs,  
P-133)  
Zenith Data Systems Z-Server MX Dual P-166 (2 CPUs,  
P-166)  
Zenith Data Systems Z-Server MX Quad P-166 (4 CPUs,  
P-166)  
Zenith Data Systems Z-Server WG P90 (2 CPUs, P-90)

---

1. The number of CPUs following each entry indicates the number of processors in the MP system as tested.
2. Only tested in VGA mode due to integrated video memory size.
3. Additional configuration is required to install Solaris 2.5x on this system; refer to the notes on "Memory Mapping Problems" in *x86: Solaris 2.5x Installation Notes* for information.
4. Before installing Solaris on a ProLiant 5000, you must run the EISA configuration utility that came with your computer to enable APIC mode. For additional information, call your vendor's technical support number.
5. Refer to the certification report for this system at <http://access1.sun.com/certify/reports/DEC/>.
6. Must use a CD-ROM drive supported by Solaris 2.5/2.5.1.
7. Due to a manufacturer's part change, integrated video not supported on some versions at time of certification test.
8. Requires custom Solaris boot diskette to be supplied by Tricord.
9. For Solaris compatibility, specify an STB S3 Trio video system by requesting option TR-16T-200-4.0W-SFC4-P64/1S-4P4I-U at time of order.
10. Must upgrade the system BIOS to V3.03.



---

### Notebook Computers (Prior to March 1996)

---

*The following notebook computers have been certified for standard Solaris operation. Although some specific portable/nomadic computing capabilities have been provided in Solaris, not all of the features and devices found on these notebooks are currently supported. Many of these notebooks were tested prior to the development of the formal notebook test plan now in use, so some functionality may be limited. For additional information on using notebooks with the Solaris product, see the online document Solaris 2.5 x86 Notebook Supplement Guide, part number 802-5028-10 (available through the Internet and other locations; call your technical support provider). Note that installation (booting) using PCMCIA devices is not currently supported.*

Ambra SN425C<sup>1</sup>  
AST Ascentia 800N 486SX/33  
AST Ascentia 900N 4/50  
AST Ascentia 900N 4/75  
AST Ascentia 910N (486DX2-50)  
AST Power Exec 4/33 ColorPlus  
Compaq LTE 4/25C  
Compaq LTE 4/33  
Compaq LTE Elite  
Dell Latitude XP (DX4-100)  
Ergo Powerbrick PN312/TFT (486DX4-100)  
Everex StepNote (486DX4-100)  
Fujitsu FMV-450NL/S (SL DX2-50)  
Fujitsu FMV-5120 NAW  
Gateway 2000 ColorBook 486DX4-75  
IBM Model 755cx TFT Video (P-75)  
IBM ThinkPad 750  
IBM ThinkPad 750C  
IBM ThinkPad 755C DX2/50

---

---

### Notebook Computers (Prior to March 1996)

---

NEC Versa/33  
NEC Versa/50  
NEC Versa/P  
Panasonic CF-V21P  
SiO Technologies FT-500 DX2/66  
Tadpole 1000  
Texas Instruments 4000E  
Texas Instruments 5000  
Toshiba 2400CT  
Toshiba T1950CT  
Toshiba T3400<sup>2</sup>  
Toshiba T3600  
Toshiba T4400C<sup>3</sup>  
Toshiba T4600<sup>3</sup>  
Toshiba T4700C<sup>3</sup>  
Toshiba T4850CT (486DX4-100)  
Toshiba T4800<sup>2</sup>  
Toshiba T4900CT (P-75)<sup>4</sup>  
Toshiba DynaBook SS475 051CT (486DX4-75)  
Toshiba DynaBook SS475-JP  
Toshiba Portege 610CT  
Toshiba Satellite Pro T2150CDT (486DX4-75)<sup>4</sup>  
Toshiba Satellite Pro T2450CT (486DX4-75)<sup>4</sup>  
Twinhead Slimnote II (486E)  
Zenith Data Systems Z-Note  
Zenith Data Systems Z-Noteflex

---

1. Keyboard controller problem affects installation. Refer to the patch file included in the SUNWx86 package located on the Solaris CD.
2. Requires special configuration to install Solaris; only comes with a 120-Mbyte disk.
3. Some hardware configuration may be required to install Solaris.
4. CAUTION: Some third-party memory expansion (PC Card) has been found to fail with the Solaris environment. Use actual Toshiba or high-grade third-party memory.



## Notebook Computers Certified After March 1996

A test plan for notebook computers that more accurately represents the status and support of a given model is now used.

The following matrix is *not* intended to show which features a particular notebook model has, but rather, which of the listed features currently works with Solaris x86. Models listed in the previous table, Notebook Computers, have been tested for basic compatibility, but will not be retested to provide the more specific information given in the table below.

For more detail, see the test reports on <http://access1.sun.com/certify/reports/reports.html>. For additional information on video support, see the table Notebook Display Video Support at the end of this document.

**Notebook Certification Matrix (After March 1996)**

Manufacturer/ Model	CPU	CD- ROM Int/Ext	Audio	Modem Int/PC Card	✓ mark or letters in a box=Supported DS=Dual scan Int or Ext=Internal or external NT=Not tested NS=Not supported at this time N/A=Not applicable TFT=Active matrix				
					Display Type TFT/DS	Tested Display Resolution	Dock Bay	Port Repli- cator	Network <sup>1</sup>
Compaq ARMADA 4120	P-120	Int	✓	PC Cd	TFT	800x600	NT	NT	✓
LTE 5250	P-120	NT	✓	PC Cd	TFT	800x600	NT	NT	✓
Fujitsu LifeBook 555Tx	P-150 MMX	Int	✓	PC Cd	TFT	800x600	N/A	N/A	✓
LifeBook 655Tx	P-150 MMX	Ext	✓	Int	TFT	800x600	N/A	✓	✓



**Notebook Certification Matrix (After March 1996) (Continued)**

✓ mark or letters in a box=Supported DS=Dual scan Int or Ext=Internal or external NT=Not tested NS=Not supported at this time N/A=Not applicable TFT=Active matrix									
Manufacturer/ Model	CPU	CD- ROM Int/Ext	Audio	Modem Int/PC Card	Display Type TFT/DS	Tested Display Resolution	Dock Bay	Port Repli- cator	Network <sup>1</sup>
<b>IBM</b>									
ThinkPad 760CD	P-90	N/A	NS	Int/NS	TFT	800x600	NT	NT	✓
ThinkPad 760ED	P-133	N/A	NS	Int/NS	TFT	800x600	NT	NT	✓
<b>HP</b>									
Omnibook 5500CT	P-133	N/A	NS	PC Cd	TFT	800x600	NT	NT	✓
<b>Toshiba</b>									
Portege 650CT	P-133	N/A	NS	Int	TFT	800x600	NT	NT	✓
Satellite Pro 420CDT	P-100	Int	✓	N/A	TFT	800x600	NT	NT	✓
Satellite Pro 425CDT	P-100	Int	✓	N/A	TFT	800x600	NT	NT	✓
Tecra 500CDT	P-120	Int	NS	Int	TFT	800x600	NT	NT	✓
Tecra 720CDT	P-133	Int	NS	Int	TFT	1024x768	NT	NT	✓
Tecra 730CDT	P-150	Int	NS	Int	TFT	1024x768	NT	NT	✓
Tecra 700CT	P-120	Int	✓	PC Cd.	TFT	800x600	NT	N/A	✓

1. Tested with 3Com EtherLink PC Card (PCMCIA) 3C589.



## Supported Devices

Devices listed in this section have been successfully tested with Solaris 2.5/2.5.1 x86 in a varied but limited number of hardware configurations. While a complete system composed of the devices listed in this section should enable you to install and run the Solaris software, some combinations of devices may not be usable or may require additional configuration.

### SCSI Host Bus Adapters

Vendor	Model
Acculogic	PCIpport Model 20
Adaptec	AHA-1510A AHA-1520A AHA-1522A AHA-1530P/1532P AHA-1540B/1542B AHA-1540C/1542C AHA-1540CF/1542CF AHA-1540CP/1542CP AHA-1640/1642 AHA-1740/1742A AHA-2740/2742 AHA-2740A/2742A AHA-2740T/2742T AHA-2740AT/2742AT AHA-2740W AHA-2840A/2842A AHA-2840VL/2842VL AHA-2940/2940W AHA-2940AU AHA-2940U/2940UW AHA-2944UW AHA-2944W AHA-3940/3940W AHA-3940U/3940UW AIC-6260 AIC-6360

### SCSI Host Bus Adapters (Continued)

Vendor	Model
<i>Adaptec, cont.</i>	AIC-7770, AIC-7770 Rev. E AIC-7850 AIC-7860 AIC-7870 AIC-7880 APA-348 MiniSCSI (LPT/SCSI)
AdvanSys	ABP510/5150-Bus-Master ISA ABP5140-Bus-Master ISA PnP ABP5142-Bus-Master ISA PnP w/floppy ABP920-Bus-Master PCI ABP930-Bus-Master PCI ABP930U-Bus-Master PCI Ultra ABP960-Bus-Master PCI MAC/PC ABP960U-Bus-Master PCI MAC/PC Ultra ABP542-Bus-Master ISA w/floppy ABP742-Bus-Master EISA ABP842-Bus-Master VL ABP940-Bus-Master PCI ABP940U-Bus-Master PCI Ultra ABP970-Bus-Master PCI MAC/PC ABP970U-Bus-Master PCI MAC/PC Ultra ABP752-Dual Channel Bus-Master EISA ABP852-Dual Channel Bus-Master VL ABP950-Dual Channel Bus-Master PCI
AMD	PCscsi PCscsi II PCnet-SCSI



---

**SCSI Host Bus Adapters (Continued)**

<b>Vendor</b>	<b>Model</b>
BusLogic	BT-440C (VLB)
	BT-445C (VLB)
	BT-445S (VLB)
	BT-542B (ISA)
	BT-545C (ISA)
	BT-545S (ISA)
	BT-742A (EISA)
	BT-746C (EISA)
	BT-747C (EISA)
	BT-747S (EISA)
	BT-757C (EISA)
	BT-757CD (EISA)
	BT-757S (EISA)
	BT-946C (PCI)
	BT-948 (PCI)
	BT-956C (PCI)
	BT-956CD (PCI)
	BT-958 (PCI)
	BT-958D (PCI)
	FlashPoint DL Dual Channel Ultra SCSI (BT-932) (PCI)
	FlashPoint DW Dual Channel Ultra & Wide SCSI (BT-952) (PCI)
	FlashPoint LT Ultra SCSI (BT-930) (PCI)
	FlashPoint LW Ultra & Wide SCSI (BT-950) (PCI)

---

**SCSI Host Bus Adapters (Continued)**

<b>Vendor</b>	<b>Model</b>
Compaq	32-bit Fast-SCSI-2
	32-bit Fast-Wide SCSI-2/E
	32-bit Fast-Wide SCSI-2/P
	Dual Channel Wide-Ultra SCSI-3
	Integrated 32-bit Fast-SCSI-2
	Integrated 32-bit Fast SCSI-2/P
	Integrated 32-bit Fast-Wide SCSI- 2/E
	Integrated 32-bit Fast-Wide SCSI- 2/P
	Integrated Wide-Ultra SCSI Controller (PCI)
	Wide-Ultra SCSI Controller (PCI)
	Creative Labs
DPT	PM-2011 (EISA)
	PM-2012B (EISA)
	PM-2021 (ISA) <sup>1</sup>
	PM-2022 (EISA) <sup>1</sup>
	PM-2024 (PCI) <sup>1</sup>
	PM-2041 (ISA) <sup>1</sup>
	PM-2041W (ISA) <sup>1</sup>
	PM-2042 (EISA) <sup>1</sup>
	PM-2042W (EISA) <sup>1</sup>
	PM-2044UW (PCI) <sup>1</sup>
	PM-2044W (PCI) <sup>1</sup>
	PM-2122 (EISA) <sup>1</sup>
	PM-2124 (PCI) <sup>1</sup>
	PM-2142W (EISA) <sup>1</sup>
	PM-2144UW (PCI) <sup>1</sup>
PM-2144W (PCI) <sup>1</sup>	
PM-3021 (ISA)	
DTC	DTC-3130 (PCI) <sup>2</sup>
	DTC-3130B (PCI)
Hitachi	PC-CS7210 (PCI)
IBM	PS/2 Micro Channel SCSI SCSI-2 Fast/Wide Adapter/A

---



---

**SCSI Host Bus Adapters (Continued)**

<b>Vendor</b>	<b>Model</b>
Intel	PCISCSI (NCR 53C825) <sup>3</sup> PCISCSINR (NCR 53C810)
P.E. Logic Corp	PEL-1620 <sup>4</sup>
QLogic	PCI IQ/QLA91x/QLA1xxx SCSI Host Adapter Family QLA510
Siemens Nixdorf	PCE-5S (NCR 53C710)
Symbios Logic	NCR 53C810 NCR 53C810A NCR 53C815 NCR 53C820 <sup>3</sup> NCR 53C825 <sup>3</sup> NCR 53C825A <sup>5</sup>
Trantor	T348 MiniSCSI Plus Parallel
Tricord	Intelligent SCSI Subsystem Controller

- 
1. This adapter can be made RAID-capable with the addition of a Hardware Disk Array module.
  2. This adapter does not have the SDMS BIOS on board. It should be used only on a system that contains the SCSI BIOS as part of its main system BIOS.
  3. Wide SCSI not yet supported in Solaris driver.
  4. Configure as an Adaptec AHA-1520A.



---

**SCSI RAID Controllers**

<b>Vendor</b>	<b>Model</b>
American Megatrends (AMI)	MegaRAID 428 (PCI)
Compaq	SMART SCSI Array Controller SMART-2 EISA/PCI Array SMART-2DH Controller SMART-2SL Controller
DEC	Digital Storage Works RAID Array (EISA)
DPT	PM-2044UW (PCI) PM-2144UW (PCI) PM-3222 (EISA) PM-3222UW (EISA) PM-3224 (PCI) PM-3224W (PCI) PM-3332UW (EISA) PM-3334UW (PCI) PM-3334W (PCI)
HP	HP Disk Array/HP Disk System
IBM	PC ServeRAID Adapter (Copperhead) SCSI-2 Fast/Wide Streaming RAID Adapter (MCA) SCSI-2 Fast/Wide PCI RAID Adapter
Mylex	DAC960E (EISA) DAC960M (Micro Channel) DAC960P (PCI) DAC960PD (PCI) DAC960PD-Ultra (PCI) DAC960PL (PCI)

---

---

**Solid State SCSI Disk Devices**

<b>Vendor</b>	<b>Model</b>
ATTO Technology	Silicon Disk II (SCSI F/W)
Imperial Technology	MegaRam (268 MB version)

---



---

**CD-ROM Drives**

<b>Vendor</b>	<b>Model</b>	<b>Type</b>
Chinon	CDS435	SCSI
	CDS-525	SCSI
	CDS535 <sup>1</sup>	SCSI
GoldStar	CRD-8160B 16x	ATAPI/IDE
	GCD-R320B	SCSI
	GCD-R520B	ATAPI/IDE
	GCD-R580B 8x	ATAPI/IDE
Hitachi	CDR-1900S	SCSI
	CDR-3750	SCSI
	CDR-6750	SCSI
	CDR-7730	ATAPI/IDE
	CDR-7930 8x	ATAPI/IDE
	CDR-8130 16x	ATAPI/IDE
	MaxPC-UC5240 4x	SCSI
Lion Optics	XC200SI	SCSI
LMSI	CM214	SCSI
	CM215	SCSI
Mitsumi	CRMC-FX001IDE	ATAPI/IDE
	CRMC-FX400	ATAPI/IDE

---

**CD-ROM Drives (Continued)**

<b>Vendor</b>	<b>Model</b>	<b>Type</b>	
NEC	MultiSpin 2Vi	ATAPI/IDE	
	MultiSpin 3Xe <sup>2</sup>	SCSI	
	MultiSpin 3Xi <sup>2</sup>	SCSI	
	MultiSpin 3Xp Plus	SCSI	
	MultiSpin 4Xe <sup>1, 2</sup>	SCSI	
	MultiSpin 4Xi <sup>1, 2</sup>	SCSI	
	MultiSpin 6Xi	SCSI	
	Intersect CDR-74	SCSI	
	Intersect CDR-84	SCSI	
	CDR-210 <sup>2</sup>	SCSI	
	CDR-211	SCSI	
	CDR-250	ATAPI/IDE	
	CDR-260	ATAPI/IDE	
	CDR-260R	ATAPI/IDE	
	CDR-271	ATAPI/IDE	
	CDR-272 (4x speed)	ATAPI/IDE	
	CDR-272 Rev. 4.15	ATAPI/IDE	
	CDR-273 (6x speed)	ATAPI/IDE	
	CDR-280	ATAPI/IDE	
	CDR-510	SCSI	
	CDR-1400 (8x speed)	ATAPI/IDE	
	CDR-1410A (8x speed)	SCSI-2	
	CDR-1600A (12/16x speed)	ATAPI/IDE	
	CDR-1610A (12/16x speed)	SCSI	
	Optics Storage	8422IDE	ATAPI/IDE
	Panasonic	LK-MC509S	SCSI
		LK-MC579B	ATAPI/IDE
LK-MC608B 8x		SCSI	
LK-MC688B 8x		ATAPI/IDE	
Panasonic/ Matsushita	CR-504B 4x	SCSI	
	CR-572B	ATAPI/IDE	
Philips	CM207	ATAPI/IDE	
	CM215	SCSI	
	CM425A	SCSI	

---



---

**CD-ROM Drives (Continued)**

Vendor	Model	Type
Pioneer	DR-U12X 12x	SCSI
	DR-466 12x	SCSI
	DRM-604X <sup>1, 3</sup>	SCSI
	DRM-624X <sup>1, 3</sup>	SCSI
Plextor	DM3028	SCSI
	PX-12CSi	SCSI
	PX-12TSi	SCSI
	PX-43CE (4.5 Plex)	SCSI
	PX-43CH (4 Plex)	SCSI
	PX-43CS	SCSI
	PX-45CH	SCSI
	PX-45CS	SCSI
	PX-63CS (6 Plex)	SCSI
	PX-65CS (6 Plex)	SCSI
PX-83CS (8 Plex)	SCSI	
Reveal	4X Internal	ATAPI/IDE
Sanyo	CRD-254P	ATAPI/IDE
	CDR-H93RMV	SCSI
	CDR-400I	SCSI
Sanyo-TORiSAN	CDR-S1G	ATAPI/IDE
	CDR-S18	ATAPI/IDE
Sony	CDU-55E	ATAPI/IDE
	CDU-55S <sup>4</sup>	SCSI
	CDU-561	SCSI
	CDU-76E	ATAPI/IDE
	CDU-76S	SCSI
	CDU-77E	ATAPI/IDE
	CDU-6211	SCSI
	CDU-6811	SCSI
	CDU-7211	SCSI
	CDU-7811	SCSI
CDU-8012	SCSI	
Sun Microsystems	SunCD	SCSI
Tae II Media Co.	TechMedia CDD-6100 10X	ATAPI/IDE
TEAC	CD-56E	ATAPI/IDE

---

**CD-ROM Drives (Continued)**

Vendor	Model	Type
Texel	DM3024	SCSI
	DM3028	SCSI
	DM5021	SCSI
	DM5024	SCSI
	DM5028	SCSI
Toshiba	4101-TA	SCSI
	5201B	SCSI
	TXM-3201	SCSI
	TXM-3301	SCSI
	TXM-3401	SCSI
	TXM-3701-D1	SCSI
	XM-3501B	SCSI
	XM-3601B	SCSI
	XM-5302B	ATAPI/IDE
XM-5522B	ATAPI/IDE	
XM-5602B (8x)	ATAPI/IDE	
XM-5701TA	SCSI	
XM-5702B (12x)	ATAPI/IDE	
Wearnes	CDD-120 <sup>5</sup>	ATAPI/IDE

1. Various CD-ROM players may not be fully SCSI-compliant in their handling of the `CDROMREADHEADER` command. This may cause failures from `void` not mounting an eligible CD-ROM. The workaround is to mount the CD-ROM manually.
2. Early versions of NEC firmware were not fully SCSI-compliant; thus these drives may only work if synchronous negotiation and disconnect are disabled on the SCSI adapter used with the CD-ROM drive, or if the drive is jumpered to use `scsi-1` commands, as appropriate.
3. Only the first CD-ROM in the Pioneer DRM-6x4X CD-ROM changer is supported by default.
4. This drive does not work with the Adaptec AHA-2940 SCSI HBA.
5. Must have BIOS 1.0 or later.



---

### Printing Devices

Vendor	Model
Lexmark International	Optra C color laser printer Optra N network laser printer Optra R+ laser printer Optra Rt+ laser printer Optra Lx+ laser printer Optra Lxi+ laser printer Color Jetprinter PS 4079 plus printer

---

### Audio Devices

Vendor	Model
Analog Devices	AD1848 & compatibles
Compaq	Business Audio
Creative Labs	Sound Blaster 16 Sound Blaster 16 SCSI-2 Sound Blaster AWE32 Sound Blaster Pro Sound Blaster Pro-2 Sound Blaster Vibra 16
Various Other Boards and Devices	Drivers and support for a large number of additional sound boards and devices are available using a software driver package from 4Front Technologies. To obtain it, contact the vendor: Tel: (310) 820-7365 USA Fax: (310) 826-2465 USA Email: info@4front-tech.com Web: <a href="http://www.4front-tech.com">http://www.4front-tech.com</a>



---

**Telephony Products**

<b>Vendor</b>	<b>Model</b>	<b>Description</b>
Dialogic Corporation <sup>1</sup>	D/21D	2 POTS lines voice and tone recognition
	D/41D	4 POTS lines voice and tone recognition
	D/41E	4 POTS lines
	D/121A	12-port voice and tone recognition, and processing board
	D/121B	12-port voice and tone recognition, and processing board
	D/240SC	24-channel voice store and forward
	D/320SC	32-channel voice store and forward
	D/240SC-T1	32-channel voice store and forward, with T-1
	FAX/40	Fax daughtercard, 4 channel, for D/41
	FAX/120	12-channel Fax for D/121 boards
	VR/40	Multiline speech recognition daughterboard, 4 port
	VR/121	Multiline speech recognition daughterboard, 12 port
	VR/160	Multiline speech recognition daughterboard, 16 port
	VR/160C	Multiline speech recognition daughterboard, 16 port
	DTI/211	Digital Trunk Interface, North American T-1
	DTI/212	Digital Trunk Interface, European E-1
	LSI/120	Loop Start Interface board
	LSI/180	Loop Start Interface board
DMX	Digital Multiplexor Expansion boards	
MSI	Modular Station Interface board, 24 port	

1. Device driver software and support are supplied by the vendor.



---

**Multiport Serial Adapters**

<b>Vendor</b>	<b>Model</b>
Aurora <sup>1</sup>	401A (ISA 4 Port) Aries 8000P (PCI 8 Port) Aries 1600P (PCI 16 Port)
CHASE <sup>1</sup>	IOPRO (ISA 8 Port)
COMPUTONE <sup>1</sup>	IntelliServer SVR-16DB (16 Port)
COMTROL <sup>1</sup>	Rocketport (16 Port)
Digi International (DigiBoard) <sup>1</sup>	AccelePort (ISA) C/X Intelligent Clusters (ISA, EISA) EPC/X Intelligent Clusters (ISA, EISA) PC/8e (ISA) PC/8eVe PC/16em (16 db25 port) PC/Xe Intelligent Serial Adapters PC/Xem (ISA, EISA) PC/Xi Intelligent Serial Adapters PCI/8r (PCI) PCI/16em (16 db25 port) PCI/Xem Xem Intelligent Asynchronous Adapters Xr Intelligent Asynchronous Adapters
MILAN <sup>1</sup>	FastPort 3100CX PrintServer FastPort 3200C PrintServer FastPort 3400C PrintServer
Moxa <sup>1</sup>	MOXA-C218 (ISA 8 Port) MOXA-C320 (ISA 32 Port)

---

**Multiport Serial Adapters (Continued)**

<b>Vendor</b>	<b>Model</b>
Specialix <sup>1</sup>	SI/8 AT XIO/8 AT
Stallion <sup>1</sup>	EasyServer II Terminal Server
System <sup>1</sup>	Parallex SCS-2008I (ISA 8 Port) RCS-4008 Network Terminal Server RCS-4008 TCP Terminal Server 8-port RCS-4108 TCP Terminal Server 8-port

---

1. Solaris drivers for this vendor's devices are available directly from the vendor.



---

**Network Adapters—Ethernet**

<b>Vendor</b>	<b>Name/Model</b>
3Com	EtherLink II, II/16 (3C503, 3C503-16) EtherLink 16, 16TP (3C507, 3C507-TP) EtherLink III (3C509, 3C509B <sup>1</sup> , 3C529, 3C59x) EtherLink III PCMCIA (3C562, 3C589, 3C589B, 3C589C, 3C589D) EtherLink III PCI Bus Master (3C590) EtherLink III EISA Bus Master (3C592) EtherLink XL (3C900-TPO, 3C900-COMBO) Fast EtherLink 10/100 PCI (3C595 TX) Fast EtherLink 10/100 EISA (3C597 TX) Fast EtherLink XL (3C905)
Accton	EN1625 (ISA) EtherCombo-16 (ISA) <sup>2</sup>
Adaptec	ANA-6901 (PCI) ANA-6901/C (PCI) ANA-6904 (PCI) ANA-6911A/C ANA-6911A/TX ANA-6911/TX (PCI) ANA-6944A 10/100 TX 4-port (PCI)
Allied Telesyn	AT-1500 (ISA) AT-1500T-Plus (ISA) AT-1500BT-Plus (ISA) AT-2450 10 T (PCI) AT-2560 10/100 TX (PCI)
Alta	EtherCombo-16 T/C (ISA) <sup>2, 3</sup>
AMD	PCnet-ISA controller chip PCnet-PCI controller chip PCnet-PCI-II controller chip
Asante	AsanteFAST 10/100 (PCI) <sup>4</sup>
Cabletron	E-2210 (ISA)
CNet	CN970EBT (PCI) PowerNIC CN935E (PCI) <sup>4</sup>

---

**Network Adapters—Ethernet (Continued)**

<b>Vendor</b>	<b>Name/Model</b>
Cogent	EM110 T4 <sup>4</sup> EM110TX (PCI) <sup>4</sup> EM440 QUAD (PCI) <sup>4</sup> EM960C (PCI) <sup>4, 5</sup> EM960TP (PCI) <sup>4</sup> EM964 QUAD (PCI) <sup>4</sup>
Compaq	Deskpro 4000 Integrated NetFlex-3 10/100 Deskpro 6000 Integrated NetFlex-3 10/100 Netelligent 10T PCI <sup>6</sup> Netelligent 10/100 TX PCI <sup>6</sup> NetFlex-2 DualPort ENET NetFlex-2 ENET-TR Controller (Ethernet only) NetFlex-3 DualPort 10/100TX PCI UTP NetFlex-3/E <sup>6</sup> NetFlex-3/P <sup>6</sup> Professional Workstation Integrated NetFlex-3 10/100 ProLiant 800 Integrated NetFlex-3 10/100 ProLiant 2500 Integrated NetFlex-3 10/100
Compex	ENET32-PCI ReadyLINK ENET32 <sup>4</sup>
DEC	EtherWORKS 10/100 <sup>4</sup> EtherWORKS PCI 10/100 <sup>4</sup>
Diversified Technologies (DTI)	LBC5025 <sup>4, 5</sup>
D-Link	DE-530CT (PCI) <sup>4</sup> DE-530CT+ (PCI) <sup>4</sup> DFE-500TX (Revision B1) (PCI)
Fujitsu	FMV-183 (ISA)
Genius	GE2000III (ISA)
HP	PC LAN NC/16 TP J2405A

---



---

**Network Adapters—Ethernet (Continued)**

<b>Vendor</b>	<b>Name/Model</b>
IBM	IBM 100/10 PCI Ethernet Adapter IBM LAN Adapter for Ethernet Combo (ISA) IBM LAN Adapter for Ethernet CX (ISA) IBM LAN Adapter for Ethernet TP (ISA)
Intel	EtherExpress16 (PCLA8110) EtherExpress16 TP (PCLA8120) EtherExpress16C (PCLA8100) EtherExpress 32 (EILA8215) (EISA) EtherExpress Flash32 (EILA8225A) (EISA) EtherExpress FlashC (PCLA8105) EtherExpress MCA (MCLA8110) EtherExpress MCA TP (MCLA8120) EtherExpress PRO (ISA) EtherExpress PRO/10+ (ISA) EtherExpress PRO/10+ (PILA8400/8420) (PCI) EtherExpress PRO/100 (EILA8265F) (EISA) EtherExpress PRO/100 (PILA8465) (PCI) EtherExpress PRO/100B (82557) (PCI)
Kingston	KNE40BT <sup>4</sup> KNE-100TX (PCI) <sup>4</sup> KNE-2000T+ (ISA) <sup>3</sup> KNE-2002+ (ISA) <sup>3</sup> KNE-2031+ (ISA) <sup>3</sup> KNE-2121+ (ISA) KNE-2121H (ISA)
Linksys	LNE100TX (PCI) <sup>4</sup> LNEPCI (PCI)
Microdyne	NE2000 (ISA) NE2500plus (ISA)
Mitron	LX2100p (PCI)
National Semicond.	Infomover NE2000 Plus (ISA) <sup>3</sup>
NetGear	FA310TX 10T/100TX (PCI)

---

**Network Adapters—Ethernet (Continued)**

<b>Vendor</b>	<b>Name/Model</b>
Novell/ Eagle Tech.	NE2000 (ISA) NE2000 Plus (ISA) <sup>3</sup> NE3200 (EISA)
Olicom	EtherCom ISA/II <sup>3</sup>
Racal InterLan	ES3210/ES3210 TP Ethernet <sup>7</sup> PCI T2-STR
Rockwell	RNS 2300 <sup>4</sup> RNS 2340 QUAD <sup>4, 5</sup>
Samsung	SEB-3000C (PCI)
SMC	Elite32 (8033 EISA) Elite32C Ultra (8232 EISA) Ether10/100 (9232) (EISA) EtherCard PLUS (8003) EtherCard PLUS Elite (8013) EtherCard PLUS Elite16 (8013) EtherCard Elite16 Ultra (8216) EtherCard Elite32T (8033T) EtherEZ (8416) EtherPower 8432BT (PCI) <sup>4</sup> EtherPower 8432BTA (PCI) <sup>4</sup> EtherPower 8432T (PCI) <sup>4</sup> EtherPower 10/100 (9332BDT) (PCI) <sup>4</sup> EtherPower 10/100 (9334BDT DUAL) (PCI) <sup>4</sup> EtherPower 10/100 (9332DST) (PCI) <sup>4, 5</sup>
SVEC	ETHER-100TX (PN 100TX 10/100TX) (PCI) FD0421-P Rev. A-1 (ISA) FD0455 EtherBoard-PCI NE2100 (ISA)
Texas Instru- ments	ThunderLAN 10/100 TX (PCI)
Thomas Conrad	NE2000 (ISA)

---



---

**Network Adapters—Ethernet (Continued)**

Vendor	Name/Model
Unisys	EISA Ethernet controller (Intel 82596) U6000/DT2 integrated Ethernet controller (Intel 82596)
Xircom	Pocket Ethernet Adapter III (PE3)
Znyx	NetBlaster ZX314 QUAD <sup>4</sup> NetBlaster ZX315 DUAL <sup>4</sup> NetBlaster ZX345 <sup>4</sup> NetBlaster ZX346 QUAD <sup>4, 5</sup> NetBlaster ZX348 DUAL <sup>4</sup> ZX311 <sup>4</sup> ZX312 (PCI) <sup>4, 5</sup> ZX342 10/100 (PCI) <sup>4, 5</sup> ZX344 QUAD <sup>4</sup>

1. Cards with ASSY 03-0021-000, REV A printed on them do not work with the Solaris software.
2. Card misdetects 8-bit slot.
3. Some NE2000plus clones may only work in I/O or shared memory mode, depending on the system or configuration, while running Solaris software.
4. Because certain board revisions have been found not to work, refer to the table in the “DEC 21040, 21041, 21140 Ethernet” Device Reference Page in the current *Solaris 2.5/2.5.1 x86 Driver Update Guide* for part/version numbers and chipsets of supported adapters.
5. Special configuration required; refer to the “DEC 21040, 21041, 21140 Ethernet” Device Reference Page in the current *Solaris 2.5/2.5.1 x86 Driver Update Guide* for additional information.
6. Refer to the “Compaq NetFlex-3, Netelligent Controllers” Device Reference Page in the current *Solaris 2.5/2.5.1 x86 Driver Update Guide* for tested chipsets.
7. Only the newer versions of these cards are supported. The versions successfully tested have stickers with the numbers 625-0367-00 and 625-0369-00; older versions of the card, for example, those with the number 625-0136-00, do not work.

---

**Network Adapters—Fast Ethernet**

Vendor	Name/Model
3Com	Fast EtherLink 10/100 (3C595 TX) (PCI) Fast EtherLink 10/100 (3C597 TX) (EISA) Fast EtherLink XL (3C905)
Adaptec	ANA-6901 (PCI) ANA-6901/C (PCI) ANA-6904 (PCI) ANA-6910/TX (PCI) ANA-6911A/C ANA-6911A/TX ANA-6911/TX (PCI) ANA-6940/TX (PCI) ANA-6944A 10/100 TX 4-port (PCI)
Allied	AT-1500 (ISA)
Telesyn	AT-2560 10/100 TX (PCI)
AMD	PCnet-Fast
Asante	AsanteFAST 10/100(PCI) <sup>1</sup>
Cogent	EM100 (PCI) <sup>1</sup> EM100TX (PCI) <sup>1</sup> EM110T4 (PCI) <sup>1</sup> EM110TX (PCI) <sup>1</sup> EM400 QUAD (PCI) <sup>1</sup> EM440 QUAD (PCI) <sup>1</sup>



---

**Network Adapters—Fast Ethernet (Continued)**

<b>Vendor</b>	<b>Name/Model</b>	
Compaq	Deskpro 4000 Integrated NetFlex-3 10/100	
	Deskpro 6000 Integrated NetFlex-3 10/100	
	Netelligent 10/100 TX PCI <sup>2</sup>	
	NetFlex-3 DUAL Port 10/100TX PCI UTP	
	NetFlex-3/E w/100Base-TX UTP Module w/100VG-AnyLAN UTP Module w/100Base-FX Module	
	NetFlex-3/P w/100Base-TX UTP Module w/100VG-AnyLAN UTP Module w/100Base-FX Module	
	Professional Workstation Integrated NetFlex-3 10/100	
	ProLiant 800 Integrated NetFlex-3 10/100	
	ProLiant 2500 Integrated NetFlex-3 10/100	
	DEC	EtherWORKS 10/100 <sup>1</sup> EtherWORKS PCI 10/100 <sup>1</sup>
	Diversified Technologies (DTI)	LBC5025 <sup>1, 3</sup>
	IBM	IBM 100/10 PCI Ethernet Adapter
	Intel	EtherExpress PRO/100 (82556) EtherExpress PRO/100B (82557) (PCI)
	Kingston	KNE-100TX (PCI) <sup>1</sup>
Linksys	LNE100TX (PCI) <sup>1</sup>	
NetGear	FA310TX 10T/100TX (PCI)	
Rockwell	RNS 2300 <sup>1</sup> RNS 2340 QUAD <sup>1, 3</sup>	

---

**Network Adapters—Fast Ethernet (Continued)**

<b>Vendor</b>	<b>Name/Model</b>
SMC	Ether 10/100 (9232) (EISA) EtherPower 10/100 (9332BDT) (PCI) <sup>1</sup> EtherPower 10/100 (9334BDT DUAL) (PCI) <sup>1</sup>
	EtherPower 10/100 (9332DST) (PCI) <sup>1, 3</sup>
	SVEC
Texas Instruments	ThunderLAN 10/100 TX (PCI)
Znyx	ZX342 10/100 (PCI) <sup>1, 3</sup> ZX344 QUAD <sup>1</sup> NetBlaster ZX345 <sup>1</sup> NetBlaster ZX346 QUAD <sup>1, 3</sup> NetBlaster ZX348 DUAL <sup>1</sup>

1. Because certain board revisions have been found not to work, refer to the table in the "DEC 21040, 21041, 21140 Ethernet" Device Reference Page in the current *Solaris 2.5/2.5.1 x86 Driver Update Guide* for part/version numbers and chipsets of supported adapters.

2. Refer to the "Compaq NetFlex-3, Netelligent Controllers" Device Reference Page in the current *Solaris 2.5/2.5.1 x86 Driver Update Guide* for tested chipsets.

3. Special configuration required; refer to the "DEC 21040, 21041, 21140 Ethernet" Device Reference Page in the current *Solaris 2.5/2.5.1 x86 Driver Update Guide* for additional information.



---

**Network Adapters—FDDI**

Vendor	Name/Model
Rockwell	RNS-2200

---

**Network Adapters—Token Ring**

Vendor	Name/Model
3Com	TokenLink III (3C619, 3C629, 3C679)
IBM	Auto 16/4 Token Ring (ISA, MCA) Token Ring 16/4 Adapter/A (ISA) Turbo 16/4 Token Ring (ISA)
Madge	PCI Presto Smart 16/4 AT Plus Smart 16/4 AT PnP Smart 16/4 EISA Smart 16/4 ISA Client Plus Smart 16/4 ISA Client PnP Smart 16/4 PCI BM Mk1 Smart 16/4 PCI Mk2

---

**Network Adapters—WAN**

Vendor	Name/Model
TSG (The Software Group)	NetcomHighway/572 (PCI) <sup>1</sup>

1. Driver software and support for this device are available directly from the vendor.

---

**AT-ISDN Adapters**

Vendor	Name/Model
Digi International	Digi Datafire-U <sup>1</sup> Digi Datafire S/T <sup>1</sup>

1. Driver software and support for this device are available directly from the vendor.

---

**High-Speed Networking**

Vendor	Name/Model
ADAX	APC-EIX T-1 Network Interface Board (EISA) <sup>1</sup>

1. Driver software and support for this device are available directly from the vendor.

---

**PC Card (PCMCIA)—Add-On Boards**

Vendor	Name/Model
ATI Technologies	14400 ETC-EXPRESS AX/Data Modem
Hytec	HCD 22
SCM	SwapBox Classic
Microsys.	SwapBox Premium

---

**PC Card (PCMCIA)—GPS and Navigation Devices**

Vendor	Name/Model
Centennial Technologies	SatNav GPS Card—NMEA <sup>1</sup> SatNav GPS Card—Binary <sup>1</sup>

1. Tested only at the device level: Application software is available from various third-party vendors.



---

**PC Card (PCMCIA)—Modems**

<b>Vendor</b>	<b>Name/Model</b>
ActionTec	MD28801 (V.34 Fax/Modem)
APEX Data	PCA-1414 (Data/Fax)
AT&T Paradyne	371-B1-001 (14.4 Data/Fax)
Boca- Modem	m144pa (14.4bps V32bis Data/Fax)
Centennial Tech.	PM50003 (CT 14.4 Fax/Modem)
Compaq	SpeedPaq 192
DataRace	RediCard Version 1 (V.32bis/V.42/V.42bis Fax/Data) RediCard Version 2 (V.32bis/V.42/V.42bis Fax/Data)
Hayes	5361US (Accura 336 T2 + Fax) (33.6Kbps V.34) Optima 144
IBM	24TTMOD-W14 (14.4 Data/Fax) 87G9800 (V.32bis/V.42/V.42bis Fax/Data)
Intel	110-US (2400 Data)
Kingston	DataRex 87G9851 (V.32bis/V.42/V.42bis Fax/Data)
Megahertz	CC3144 (V.32bis/V.42/V.42bis Fax/Data) XJ114 (V.32bis/V.42/V.42bis Fax/Data) XJ124FM (V.32bis/V.42/V.42bis Fax/Data) XJ214 (V.32bis/V.42/V.42bis Fax/Data) XJ2288 (V.32bis/V.42/V.42bis Fax/Data)
Motorola	Montana 33.6 (V.34 Fax/Modem)

---

**PC Card (PCMCIA)—Modems (Continued)**

<b>Vendor</b>	<b>Name/Model</b>
SMART Modular Tech.	SmartExchange 9624 Fax/Modem
Supra	COMcard 144 (V.32bis/V.42/V.42bis Fax/Data)
US Robotics	Sun/USR WorldPort (V.32bis/V.42/V.42bis Fax/Data/Voice)

---



---

**PC Card (PCMCIA)—Serial Cards**

<b>Vendor</b>	<b>Name/Model</b>
IBM	IBM RS-332 Serial Card
Socket Communication	SL0700 (RS-332)

---

---

**PC Card (PCMCIA)—SRAM Memory Cards**

<b>Vendor</b>	<b>Name/Model</b>
Centennial Technologies	SRAM Card (256 KB) SRAM Card (512 KB) SRAM Card (1 MB) SRAM Card (2 MB) SR04M-15-11192-01 52795 (4 MB Recharge)
Epson	NB70-004268 NB70-004269 NB70-004270
IBM	0.5 MB SRAM Card 1 MB SRAM Card 0933155 (2 MB SRAM)
Magic Ram	SR1MBP100 SR2MBP100
Mitsubishi	MF3513-LCDAT MF31M1-LCDAT MF32M1-LCDAT
SMART Modular Technologies	SM9SRD512KP3 SM9SRD1MP3 SM9SRD2MP3 SM9SRDA1MP3 SM9SRDA2MP3

---

---

**Pointing Devices**

<b>Vendor</b>	<b>Model</b>
Appoint	Thumbelina <sup>1</sup> MousePen Pro <sup>1</sup>
CH Products	RollerMouse
Dyna Point	DynaTrak <sup>1</sup>
IBM	PS/2 2-button Easy Options Mouse <sup>1</sup>
Interlink	PortaPoint <sup>1</sup>
Kraft Systems	MicroTrack <sup>1</sup>
Logitech	C7 serial and bus mouse devices C9 serial and bus mouse devices 2-Button <sup>1</sup> MouseMan serial and bus mouse devices MouseMan cordless TrackMan serial and bus mouse devices
Microsoft	Serial, bus, and PS/2 mouse devices
MicroSpeed	MicroTRAC trackball
Mouse Systems	Mouse! New Mouse PC Mouse II

---

1. Select "Microsoft 2-button mouse" during installation of Solaris software.



---

**Tape Drives—SCSI<sup>1</sup>**

<b>Vendor</b>	<b>Model</b>
Archive	2150S 150 MB 2525 QIC-525 4320 4mm 4324 4mm Python 28454 4mm Python 28388 4mm Viper
Compaq	DLT 4000 DLT 7000
Conner	CTD 2004 CTD 4004 CTD 8004H
DEC	DLT 2000
Exabyte	EXB-4200 4mm EXB-8200 8mm EXB-8500 8mm EXB-8505 8mm EXB-8505XL 7/14GB 8mm 8705 Eliant 8mm EXB-8900 Mammoth 20/40 GB 8mm
HP	1557A DDS3 autoloader <sup>2</sup> Colorado Memory Systems PowerTape 1100 QIC Colorado Memory Systems PowerTape 2400 QIC Colorado Memory Systems PowerTape 4000 QIC Colorado Memory Systems PowerDAT <sup>3</sup> 6000 4mm 35470A DDS 4mm 35480A DDS/Data Compression 4mm C1528E 4mm C1533-00100 DDS2/Data Compression 4mm C1534A DDS Tape Drive 4mm

---

**Tape Drives—SCSI<sup>1</sup> (Continued)**

<b>Vendor</b>	<b>Model</b>
<b>HP, cont.</b>	C1536A DDS/Data 4mm C1537 DDS3 4mm C1520F SureStore Tape 2000e 4mm C1525F SureStore Tape 2000i 4mm C1521F SureStore Tape 5000e 4mm C1526F SureStore Tape 5000i 4mm C1551A SureStore Tape 5000eU 4mm C1529F SureStore Tape 6000e 4mm C1528F SureStore Tape 6000i 4mm C1552A SureStore Tape 6000eU 4mm C1520E JetStore 2000e 4mm C1520E JetStore 2000i 4mm C1526E JetStore 5000i 4mm C1529A JetStore 5000i 4mm JetStore 5000e 4mm SureStore DAT8 <sup>3</sup> SureStore DAT24 <sup>3</sup> SureStore DAT24x6e <sup>3</sup> SureStore T4
Quantum	DLT 4000 DLT 7000
Sony	SDT 5000 4mm SDT 5200 4mm SDT 7000 DDS2 SDT 9000 DDS3

---



---

**Tape Drives—SCSI<sup>1</sup> (Continued)**

<b>Vendor</b>	<b>Model</b>
Sun Microsystems	DLT drives, all shipping models up to DLT 7000 x660A 150 MB QIC x814A 5.0 GB 8mm x822A 4mm x6101A 2.5 GB QIC SCSI x6102A 2.5 GB QIC SCSI x6103A 2.5 GB QIC SCSI
Tecmar	TS-420
Tandberg	Panther 525S TDC 3820 TDC 4120 TDC 4220 TDC 4222 TDC 6122
WangDAT	3400DX DDS-2 4mm 3800 DDS-2 4mm
Wangtek	51000 QIC 52000 QIC 5525ES QIC 9500DC QIC

---

**SCSI RAID Tape**

<b>Vendor</b>	<b>Model</b>
ANDATACO	Rapid Tape Array

---

1. The tape drives in this table have been tested with the `st` tape driver software. The tape drives were tested using the Legato Tape Exerciser program to verify basic functionality and general compatibility with Solaris 2.5/2.5.1 x86.
2. Requires third-party control software.
3. Testing has shown that these switch settings are best: Switches 1 through 8: set to 11001100.



---

**Uninterruptable Power Supplies (UPS)**

---

*The following UPS products have been tested in the vendor's labs. SunSoft has tested the software on selected models to ensure basic operation under Solaris 2.5/2.5.1 x86.*

APC Back-UPS 200  
APC Back-UPS 280  
APC Back-UPS 400  
APC Back-UPS 450  
APC Back-UPS 600  
APC Back-UPS 900  
APC Back-UPS 1250

---

---

**Uninterruptable Power Supplies (UPS)**

---

APC Back-UPS Pro 280  
APC Back-UPS Pro 420  
APC Back-UPS Pro 650  
APC Back-UPS Pro 1000  
APC Back-UPS Pro 1400  
  
APC Matrix-UPS 3000  
APC Matrix-UPS 3000XR  
APC Matrix-UPS 5000\*  
APC Matrix-UPS 5000XR  
  
APC Smart-UPS 250  
APC Smart-UPS 400  
APC Smart-UPS 450  
APC Smart-UPS 600  
APC Smart-UPS 700  
APC Smart-UPS 700PM  
APC Smart-UPS 700RM  
APC Smart-UPS 700XL  
APC Smart-UPS 750  
APC Smart-UPS 900  
APC Smart-UPS 1000  
APC Smart-UPS 1000RM  
APC Smart-UPS 1000XL  
APC Smart-UPS 1250  
APC Smart-UPS 1400  
APC Smart-UPS 1400RM  
APC Smart-UPS 1400RMXL  
APC Smart-UPS 1400XLT  
APC Smart-UPS 2000  
APC Smart-UPS 2200  
APC Smart-UPS 2200RM  
APC Smart-UPS 2200RMXL  
APC Smart-UPS 2200XL  
APC Smart-UPS 2200XLT  
APC Smart-UPS 3000  
APC Smart-UPS 3000RM

---



---

**Motherboards**

*These are individual motherboards that have been tested as components; see page 7 for a list of System Platforms.*

AIR 486ET VESA/EISA (Sis chipset)  
AIR 54CEP (P-90/100)  
AIR 54CDP (2 CPUs, P-90/100)  
AIR 54TPI (P-133)  
AIR 54TPI (P-200)  
AIR P6NPI (PP-200)

American Megatrends Titan-II PCI EISA (2 CPUs)

AMI Atlas PCI (P-100)  
AMI Voyager with 486DX2-66 CPU  
AMI Super Voyager PCI  
AMI Super Voyager II VLB  
AMI Titan II (2 CPUs, P-90)  
AMI Enterprise III with 486DX2-66 CPU  
AMI Enterprise IV

---

---

**Motherboards (Continued)**

ASUS HX97 (P-200 MMX)  
ASUS KL97 XV (PII-300)  
ASUS KN97 X (PII-233)  
ASUS P2L97-DS (2 CPUs, PII-300)  
ASUS PCI/E-P54NP4 (2 CPUs, P-90)  
ASUS PCI/I-486SP3G (DX33, SX, DX2-66, OverDrives)  
ASUS PCI/I-P5SP4 (P-60)  
ASUS PCI/I-P54NP4 (2 CPUs, P-90)  
ASUS PCI/I-P54NP4D (P-100)  
ASUS PCI/I-P54NP4D (P-133)  
ASUS PCI/I-P54SP4 (P-75, 90, 100)  
ASUS PCI/I-P54TP4 (P-100)  
ASUS PCI/I-P55TP4 (Triton) (P-90)  
ASUS PCI/I-P55TP4XE (P-90)  
ASUS PCI/I-P55TP4XE (P-133)  
ASUS P/E P55T2P4D (2 CPUs, P-133)  
ASUS P/E P55T2P4S (P-133)  
ASUS P/E P55T2P4S (P-200)  
ASUS P/I AP55TV (P-166)  
ASUS P/I AP6N (PP-200)  
ASUS P/I P55T2P4 (P-200 MMX)  
ASUS P/I P55T2P4S (P-133)  
ASUS P/I P55T2P4S (K6-233)  
ASUS P/I P55T2P4S (P-200)  
ASUS P/I P55TVP4 (P-200 MMX)  
ASUS P/I P55TXP4 (P-200 MMX)  
ASUS P/I P65UP5 (PP-200)  
ASUS P/I P65UP5 (2 CPUs, PP-200)  
ASUS P/I P6RP4 (PP-150)  
ASUS P/I P6RP4 (PP-200)  
ASUS P/I XP55T2P4 (P-200 MMX)  
ASUS P/I XP55TVP4 (P-200 MMX)  
ASUS P/I XP55TXP4 (P-200 MMX)  
ASUS P/I XP6NP5 (PP-200)  
ASUS P/I XPKNP (PII-233)  
ASUS P/I XPKNP5 (PII-233)  
ASUS PVI-486AP4 (486SX/DX/DX2)  
ASUS PVI-486SP3 (DX33, SX, DX2-66, OverDrives)  
ASUS TX98-XV (P-233 MMX)  
ASUS TX97-X (P-200 MMX)  
ASUS TX97 (P-200 MMX)

---



---

**Motherboards (Continued)**

---

**ASUS, cont.**

ASUS VL/EISA-486SV1 (DX33, SX, DX2-66,  
OverDrives)

ASUS VL/I-486SV2G (486SX/DX/DX2)

ASUS VX97 (P-200 MMX)

ASUS VX97-X (P-200 MMX)

DFI G586-VPM (P-90)

DTK FEAT-39 (DX4-100)

DTK PKM0038e

DTK QUIN-54/I (P-133)

FIC PA-2002 (P-75)

FIC PA-2002 (P-100)

FIC PA-2002 (P-133)

FIC PT-2003 (P-75)

FIC PT-2003 (P-120)

FIC PT-2003 (P-150)

FIC PT-2003 (P-166)

GenoaTurbo Express 486VL

GenoaTurbo Express 586 PCI-4

GenoaTurbo Express 586VL

---

---

**Motherboards (Continued)**

---

Intel Advanced/AL (Aladdin-Triton) (P-90)

Intel Advanced/AS (Atlantis) (P-166)

Intel Advanced/ATX

Intel Advanced/EV (Endeavor) (P-75)

Intel Advanced/EV (Endeavor) (P-90)

Intel Advanced/EV (Endeavor) (P-100)

Intel Advanced/EV (Endeavor) (P-120)

Intel Advanced/EV (Endeavor) (P-133)

Intel Advanced/EV (Endeavor) (P-150)

Intel Advanced/EV (Endeavor) (P-166)

Intel Advanced/ML (P-133)

Intel Advanced/MN (Morrison) (P-100)

Intel Advanced/PO (P-133)

Intel Advanced/RH (P-133)

Intel Advanced/VS (Venus) (PP-180)

Intel Advanced/ZE Minitower (P-100)

Intel Advanced/ZP (Zappa-Triton) (P-90)

Intel ALTserver (Altair) (P-150)

Intel ALTserver (Altair) (P-166)

Intel ALTserver (Altair) (2 CPUs, P-100)

Intel AP440FX (PP-200)

Intel CN430TX (P-233 MMX)

Intel DB440FX (PII-233)

Intel Express (2 CPUs, P-60)

Intel Express (2 CPUs, P-66)

Intel Express (2 CPUs, P-90)

Intel Xtended Xpress (2 CPUs, P-100)

Intel Xtended Xpress (4 CPUs, P-100)

Intel NP30HX (P-166)

Intel PD440FX (PP-266 MMX)

Intel Performance AU (PP-180)

Intel Performance AU (PP-200)

Intel Premiere/PCI II Baby AT Board (P-90)

(sometimes referred to as Plato)<sup>1</sup>

Intel Premiere PCI II (P-100)

Intel RU430HX (P-150)

Intel RU430HX (P-166)

Intel RU430HX (P-233 MMX)

Intel TE430VX (P-166 MMX)

Intel TE430VX (P-200 MMX)

Intel TE430VX (P-233 MMX)

Intel VS440FX (PP-200)

Intel YM430TX (P-233 MMX)

---



---

**Motherboards (Continued)**

---

Micronics EISA 486DX (30, 50, 66 CPU)  
Micronics EISA VLB 486DX (30, 50, 66 CPU)  
Micronics EISA VLB 486DX2 (30, 50, 66 CPU)  
Micronics ISA VLB 486DX2  
Micronics JX30 WB (486DX4-100)  
Micronics LPH54 (P-75)  
Micronics LPH54 (P-90)  
Micronics LPH54 (P-100)  
Micronics LPH54 (P-120)  
Micronics LPH54 (P-133)  
Micronics LX30 WB (486SX33)  
Micronics M5PE (P-66)  
Micronics M5PI (P-66)  
Micronics M54HI Plus (P-90)  
Micronics M54HI Plus (P-100)  
Micronics M54HI Plus (P-120)  
Micronics M54HI Plus (P-133)  
Micronics M54HI Plus (P-150)  
Micronics M54HI Plus (P-166)  
Micronics M54HI Triton (P-100)  
Micronics M54PE (1 CPU, P-90)  
Micronics M54PE (1 CPU, P-100)  
Micronics M54PE (1 CPU, P-133)  
Micronics M54PE (2 CPUs, P-90)  
Micronics M54PE (2 CPUs, P-100)  
Micronics M54PE (2 CPUs, P-133)  
Micronics M54PE (2 CPUs, P-150)  
Micronics M54PE (2 CPUs, P-166)  
Micronics M54PI (P-90 or P-75)  
Micronics M54SI (P-75)  
Micronics M54SI (P-90)  
Micronics M54SI (P-100)  
Micronics M54LI-1B (P-90)  
Micronics M54LI-1B (P-133)  
Micronics Mpower 4 plus (486DX2-66)

SuperMicro P55CMS  
SuperMicro P5STE (P-133)  
SuperMicro P5STE (P-166)  
SuperMicro P6DNE (2 CPUs, PP-200)  
SuperMicro P6DNF (2 CPUs, PP-200)

---

---

**Motherboards (Continued)**

---

Suria SC-4SIO (486DX-Cyrix)  
Suria SC-4SIO (486DX2-80-AMD)  
Suria SC-4SIO (486DX4-100)  
Suria SC-5TIO (P-75)  
Suria SC-5TIO (P-133)  
Suria SC-5TIO (P-166)  
Suria SC-5TIO PB (P-133)  
  
Tulip TC32 (486DX2-66)  
Tulip TC40 (486DX2-66)  
Tulip TC42 (P-90)  
Tulip TC43 (P-90)  
  
Tyan S1462 (P-120)  
Tyan S1462 (P-150)  
Tyan S1462 (P-166)  
Tyan S1462 (2 CPUs, P-133)  
Tyan S1468 (P-120)  
Tyan S1470 (P-166)  
Tyan S1470 (P-200)  
Tyan S1472 ATK (P-166)  
Tyan S1472 ATK (P-200)  
Tyan S1563D (P-166)  
Tyan S1563D (P-200)  
Tyan S1563D (2 CPUs, P-166)  
Tyan S1563D (2 CPUs, P-200)  
Tyan S1662D (PP-200)  
Tyan S1668 (2 CPUs, PP-200)  
Tyan S1672 (PP-200)  
  
VEGA 486F-3VL with Symphony SL1287, SL82C461,  
SL82C362 chipset and 486DX2-66 CPU

---

1. Only the version that uses Neptune-2 stepping of the PCI chipset has been tested and certified.



### Video Display Adapters

Vendor	Model	Bus	Chipset <sup>23</sup>	Resolution and Color Depth																
				800x600		1024x768		1152x900		1280x1024		1600x1200								
				8	24	8	24	8	24	8	24	8	24							
Acer	ET4000/W32 <sup>1</sup>	ISA	Tseng ET4000/W32	✓		✓														
ALR	Flyer	VL	WD90C33			✓														
AST	Manhattan 5090P <sup>2</sup>	—	Cirrus Logic GD5424	✓																
ATI	3D Pro Turbo PC2TV	PCI	ATI 3D RAGE II+	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	3D RAGE <sup>3</sup>	—	ATI 3D RAGE	✓	✓	✓		✓		✓		✓								
	3D RAGE II <sup>3</sup>	—	ATI 3D RAGE II	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	3D RAGE II+ <sup>3</sup>	—	ATI 3D RAGE II+	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	3D RAGE PRO <sup>3</sup>	—	ATI 3D RAGE PRO	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	3D Xpression	PCI	ATI 3D RAGE	✓	✓	✓		✓		✓		✓								
	3D Xpression+ PC2TV	PCI	ATI 3D RAGE II	✓	✓	✓		✓		✓		✓								
	8514 Ultra	ISA	ATI Mach8			✓														
	All-in-Wonder	PCI	ATI 3D RAGE II+	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Graphics Pro Turbo <sup>4</sup>	PCI	ATI Mach64	✓	✓	✓	✓	✓		✓		✓								
	Graphics Pro Turbo <sup>4</sup>	VLB	ATI Mach64	✓	✓	✓	✓	✓		✓		✓								
	Graphics Pro Turbo 1600	PCI	ATI Mach64	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Graphics Ultra	ISA	ATI Mach8			✓														
	Graphics Ultra+	ISA	ATI Mach32	✓		✓														
	Graphics Ultra Pro	ISA	ATI Mach32	✓		✓		✓		✓		✓								
	Graphics Ultra Pro	PCI	ATI Mach32	✓		✓		✓		✓		✓								
	Graphics Ultra Pro	VLB	ATI Mach32	✓		✓		✓		✓		✓								
	Graphics Xpression <sup>4</sup>	PCI	ATI Mach64	✓	✓	✓		✓		✓		✓								
	Graphics Xpression <sup>4</sup>	VLB	ATI Mach64	✓	✓	✓		✓		✓		✓								
	Mach64 <sup>3, 4</sup>	—	ATI Mach64	✓		✓														
	Mach64CT <sup>3, 4</sup>	—	ATI Mach64CT	✓	✓	✓		✓		✓		✓								
	Mach64CT Rev. 2 <sup>3, 4</sup>	—	ATI Mach64CT	✓	✓	✓		✓		✓		✓								
	Mach64VT	PCI	ATI Mach64VT	✓	✓	✓		✓		✓		✓								
	VGA Wonder+	ISA	ATI Mach8			✓														
	VGA Wonder XL	ISA	ATI Mach8			✓														



**Video Display Adapters (Continued)**

Vendor	Model	Bus	Chipset <sup>23</sup>	Resolution and Color Depth											
				800x600		1024x768		1152x900		1280x1024		1600x1200			
				8	24	8	24	8	24	8	24	8	24		
ATI, cont.	VGA Wonder XL 24	ISA	ATI Mach8			✓									
	Video Expression	PCI	ATI Mach64VT	✓	✓	✓		✓		✓					
	Winturbo <sup>4, 5</sup>	PCI	ATI Mach64	✓	✓	✓		✓		✓					
	XPERT@Play	PCI/ AGP	ATI 3D RAGE PRO	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
	XPERT@Work	PCI/ AGP	ATI 3D RAGE PRO	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
Boca	Voyager 64	PCI	S3 Trio64	✓	✓	✓		✓		✓					
Chips & Technology	65540 <sup>3</sup>	—	F65540	✓		✓									
	65545 <sup>3</sup>	—	F65545	✓		✓		✓							
	65548 <sup>3</sup>	—	F65548	✓		✓		✓							
	65550 <sup>3</sup>	—	F65550	✓		✓		✓		✓					
Cirrus Logic	5420 chipset w/512Kbyte DRAM <sup>3</sup>		Cirrus Logic GD5420	✓											
	5424 chipset w/512Kbyte DRAM <sup>2, 3</sup>		Cirrus Logic GD5424	✓											
	5428 chipset <sup>3</sup>	—	Cirrus Logic GD5428	✓		✓		✓		✓					
	5428 chipset w/512Kbyte VRAM <sup>3</sup>		Cirrus Logic GD5428	✓											
	5429 chipset <sup>3</sup>	—	Cirrus Logic GD5429	✓		✓		✓		✓					
	542x chipset <sup>3</sup>			✓		✓		✓		✓					
	5430 chipset <sup>3</sup>		Cirrus Logic GD5430	✓		✓		✓		✓					
	5434 chipset <sup>3</sup>		Cirrus Logic GD5434	✓	✓	✓	✓	✓		✓					
	5436 chipset <sup>3</sup>	PCI	Cirrus Logic GD5436	✓	✓	✓		✓		✓					
	54M40 chipset <sup>3</sup>	—	Cirrus Logic GD54M40	✓	✓	✓		✓		✓					



**Video Display Adapters (Continued)**

Vendor	Model	Bus	Chipset <sup>23</sup>	Resolution and Color Depth									
				800x600		1024x768		1152x900		1280x1024		1600x1200	
				8	24	8	24	8	24	8	24	8	24
Cirrus Logic, cont.	5446 chipset <sup>3</sup>	PCI	Cirrus Logic GD5446	✓	✓	✓		✓		✓			
	5480 chipset <sup>3</sup>	PCI	Cirrus Logic GD5480	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	7543 chipset <sup>3</sup>	—	Cirrus Logic GD7543	✓		✓							
Compaq	Professional Workstation 5000	PCI	MGA2064W	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	ProLiant	—	Cirrus Logic GD5420	✓									
	ProLiant 800	—	Cirrus Logic GD5440	✓									
	ProLiant 1000	—	Cirrus Logic GD5420	✓									
	ProLiant 1500	—	Cirrus Logic GD5420	✓									
	ProLiant 2000	—	Cirrus Logic GD54M30	✓									
	ProLiant 2500	—	Cirrus Logic GD5420	✓									
	ProLiant 4000	—	Cirrus Logic GD5420	✓									
	ProLiant 4500	—	Cirrus Logic GD5424	✓									
	ProLiant 5000	—	Cirrus Logic GD5424	✓									
	ProLinea	ISA	Tseng ET4000			✓							
	ProSignia <sup>6</sup>	—	Cirrus Logic GD5420	✓									
	ProSignia 300	—	Cirrus Logic GD5424	✓									
ProSignia 300/500	—	Cirrus Logic GD5420	✓										



**Video Display Adapters (Continued)**

Vendor	Model	Bus	Chipset <sup>23</sup>	Resolution and Color Depth												
				800x600		1024x768		1152x900		1280x1024		1600x1200				
				8	24	8	24	8	24	8	24	8	24			
Compaq, cont.	ProSignia 300/500	—	Cirrus Logic GD5424	✓												
	QVision 1024/E	EISA	TRITON			✓										
	QVision 1024/I	ISA	TRITON			✓										
	QVision 1280 chipset <sup>7</sup>	EISA	ORION	✓	✓	✓		✓		✓						
	QVision 2000	PCI	Matrox MGA-2	✓	✓	✓		✓		✓						
	QVision 2000 (Rev. G)	PCI	Matrox MGA-3	✓	✓	✓		✓		✓						
CompuAdd	Hi-Res VGA	ISA	Tseng ET4000			✓										
DEC	DECpc XL 590	—	Cirrus Logic GD5428	✓												
Dell	DE Series	ISA	Tseng ET4000			✓										
	L Series		Tseng ET4000/W32			✓										
	L Series		Tseng ET4000/W32i			✓										
	M/ME Series		S3 805			✓										
	OptiPlex DGX 590	—	ATI Mach64	✓	✓	✓		✓		✓						
	OptiPlex XMT 590	—	S3 Vision 864	✓	✓	✓		✓		✓						
	PowerEdge SP5xx		ATI Mach32			✓										
Diamond	SpeedStar 24x	ISA	WD90C31			✓										
	SpeedStar 64/ SpeedStar 64 Graphics 2000XL Series	ISA/ PCI	Cirrus Logic GD5434	✓	✓	✓		✓		✓						
	SpeedStar Plus	ISA	Tseng ET4000			✓										
	SpeedStar Pro/ SpeedStar Pro 1100	ISA	Cirrus Logic GD5426			✓										
	Stealth 3D 2000	PCI	S3 ViRGE (86C325)	✓	✓	✓		✓		✓						
	Stealth 3D 2000/Pro	PCI	S3 ViRGE/DX (86C375)	✓	✓	✓	✓	✓		✓						
	Stealth 3D 3000	PCI	S3 ViRGE/VX (86C988)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓



**Video Display Adapters (Continued)**

Vendor	Model	Bus	Chipset <sup>23</sup>	Resolution and Color Depth											
				800x600		1024x768		1152x900		1280x1024		1600x1200			
				8	24	8	24	8	24	8	24	8	24		
Diamond, cont.	Stealth 24	ISA	S3 801			✓									
	Stealth 32	PCI	Tseng ET4000/W32p	✓	✓	✓		✓		✓					
	Stealth 32	VLB	Tseng ET4000/W32p	✓	✓	✓		✓		✓					
	Stealth 64 DRAM/ Stealth 64 Graphics 2000 Series	PCI/ VLB	S3 Vision 864	✓	✓	✓		✓		✓					
	Stealth 64 DRAM	PCI	S3 Trio64	✓	✓	✓		✓		✓					
	Stealth 64 VRAM	PCI	S3 Vision 964	✓	✓	✓	✓	✓	✓	✓					
	Stealth 64 VRAM	VLB	S3 Vision 964	✓	✓	✓	✓	✓	✓	✓					
	Stealth Video DRAM/ Stealth 64 Video 2000 Series	PCI/ VLB	S3 Vision 868	✓	✓	✓		✓		✓				✓	
	Stealth 64 Video 2001	PCI	S3 Vision 765	✓	✓	✓		✓		✓					
	Stealth Video VRAM/ Stealth 64 Video 3000 <sup>8</sup> Series	PCI	S3 Vision 968	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
	Stealth Pro	ISA	S3 928	✓		✓		✓		✓					
	Stealth SE	PCI	S3 Trio32	✓		✓		✓							
	Stealth VRAM	ISA	S3 911			✓									
	Viper PCI	PCI	Weitek Power 9000	✓		✓		✓		✓					
	Viper VLB	VLB	Weitek Power 9000	✓		✓		✓		✓					
	Viper Pro	PCI	Weitek Power 9100	✓		✓		✓		✓					
	Viper Pro	VLB	Weitek Power 9100	✓		✓		✓		✓					
	Viper SE <sup>9</sup>	PCI	Weitek Power 9100	✓		✓		✓		✓					
ELSA	Victory 3D	PCI	S3 ViRGE (86C325)	✓	✓	✓	✓	✓		✓					
	Winner 1000	VLB	S3 928	✓		✓		✓							
	Winner 1000 AVI	PCI	S3 Vision 868	✓	✓	✓		✓		✓					
	Winner 2000	VLB	S3 928	✓		✓		✓		✓					
	Winner 1000Pro-VL <sup>10</sup>	VLB	S3 Vision 864	✓	✓	✓		✓		✓					



**Video Display Adapters (Continued)**

Vendor	Model	Bus	Chipset <sup>23</sup>	Resolution and Color Depth									
				800x600		1024x768		1152x900		1280x1024		1600x1200	
				8	24	8	24	8	24	8	24	8	24
ELSA, cont.	Winner 2000Pro-PCI	PCI	S3 Vision 964	✓	✓	✓	✓	✓	✓	✓		✓	
	Winner 2000Pro-VL	VLB	S3 Vision 964	✓	✓	✓	✓	✓	✓	✓		✓	
	Winner 2000Pro-X	PCI	S3 Vision 968	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Winner 3000-S	PCI	S3 ViRGE (86C325)	✓	✓	✓		✓		✓			
Everex	FIC 864P	PCI	S3 Vision 864	✓	✓	✓		✓		✓			
	VGA Trio 64P	PCI	S3 Trio64	✓	✓	✓		✓		✓			
	ViewPoint 64P	PCI	S3 Vision 864	✓	✓	✓		✓		✓			
Genoa	SuperVGA 7000					✓							
Hercules	Dynamite 128/Video	PCI	Tseng ET6000	✓	✓	✓	✓	✓		✓			
Hewlett-Packard	HP NetServer LC/LE/LF		TVGA 9000i	✓									
	HP Vectra VL2		Cirrus Logic GD5428	✓		✓							
	HP Vectra XM2i		S3 Vision 864	✓		✓		✓					
	HP Vectra XU <sup>11</sup>	—	S3 Vision 864	✓	✓	✓		✓		✓			
IBM	Easy Options (VC550) <sup>12</sup>	ISA	Cirrus Logic GD5428			✓							
	PC 330—Model 6575	—	S3 Vision 864	✓	✓	✓		✓		✓			
	PC 330—Model 6576	—	S3 Trio64	✓		✓		✓					
	PC 350—Model 6581	—	Cirrus Logic GD5430	✓		✓		✓		✓			
	PC 360—Model 6598	—	Storm	✓	✓	✓	✓	✓	✓	✓		✓	
	PC 750—Model 6885-35H	—	S3 Vision 864 + S3 SDAC	✓	✓	✓		✓		✓			
	PC 750—Model 6885-J0M	—	S3 Vision 864 + S3 SDAC	✓	✓	✓		✓		✓			
	PC Series 300-486		Cirrus Logic GD5430	✓		✓							
	PC Series 300		S3 Vision 864	✓	✓	✓		✓		✓			
PC Series 700		S3 Vision 864	✓	✓	✓		✓		✓				



**Video Display Adapters (Continued)**

Vendor	Model	Bus	Chipset <sup>23</sup>	Resolution and Color Depth										
				800x600		1024x768		1152x900		1280x1024		1600x1200		
				8	24	8	24	8	24	8	24	8	24	
IBM, cont.	PC Server 310—Model 8639-0DT	—	S3 Vision 868	✓		✓		✓		✓				
	PC Server 310—Model 8639-0EO	—	S3 Trio64V+	✓		✓		✓						
	PC Server 310—Model 8639-0XT	—	S3 Vision 864	✓		✓		✓						
	PC Server 320—Model 8640-0DV	—	Cirrus Logic GD5428	✓		✓								
	PC Server 320—Model 8640-0NJ	—	Cirrus Logic GD5428	✓		✓								
	PC Server 320—Model 8640-0XT	—	Cirrus Logic GD5428	✓		✓								
	PC Server 320—Model 8640-0YT	—	Cirrus Logic GD5428	✓		✓								
	PC Server 320—Model 8640-MXT	—	Cirrus Logic GD5430	✓		✓								
	PC Server 325—Model 8639-ESO	—	Cirrus Logic GD5436	✓		✓		✓						
	PC Server 325—Model 8639-ESV	—	Cirrus Logic GD5436	✓		✓		✓						
	PC Server 500—Model 8641-0YR	—	Cirrus Logic GD5428	✓		✓								
	PC Server 500—Model 8641-0YT	—	Cirrus Logic GD5428	✓		✓								
	PC Server 520—Model 8641-ED2	—	Cirrus Logic GD5428	✓		✓								
	PC Server 520—Model 8641-EDG	—	Cirrus Logic GD5428	✓		✓								
	PC Server 520—Model 8641-EZS	—	Cirrus Logic GD5428	✓		✓								
	PC Server 520—Model 8641-EZV	—	Cirrus Logic GD5428	✓		✓								



**Video Display Adapters (Continued)**

Vendor	Model	Bus	Chipset <sup>23</sup>	Resolution and Color Depth										
				800x600		1024x768		1152x900		1280x1024		1600x1200		
				8	24	8	24	8	24	8	24	8	24	
IBM, cont.	PC Server 720—Model 8642-0ZO	—	Cirrus Logic GD5428	✓		✓								
	PS/Valuepoint		S3 805			✓								
	PS/ValuePoint Performance Series		S3 Vision 864	✓	✓	✓		✓		✓				
	VGA <sup>13</sup>	ISA	IBM VGA	✓	✓									
	XGA	MCA	XGA			✓								
	XGA-2	MCA	XGA-2			✓								
Intel	Professional/GX High Resolution		ATI Mach32	✓		✓		✓		✓				
	TMI/IPG	—	WD9031A	✓										
	Xpress VGA		WD90C31			✓								
Intergraph	TD-1 <sup>14</sup>		S3 928	✓		✓		✓		✓				
	TD-2, TD-3; (G90) <sup>15</sup>	PCI	Weitek Power 9000	✓		✓		✓		✓				
	G91 <sup>16</sup>	PCI	Weitek Power 9100			✓				✓		✓		
	G95 <sup>17</sup>	PCI	Storm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	ISMP (SMP 224) <sup>18</sup>		Cirrus Logic GD5434	✓	✓	✓	✓	✓		✓				
Matrox	MGA Impression	VLB	Matrox MGA-1	✓	✓	✓	✓	✓		✓		✓		
	MGA Impression Plus	PCI	Matrox MGA-3	✓		✓		✓		✓				
	MGA Ultima	VLB	Matrox MGA-2	✓	✓	✓		✓		✓				
	MGA Ultima Plus	PCI	Matrox MGA-2	✓	✓	✓		✓		✓		✓		
	MGA Ultima Plus 200	PCI	Matrox MGA-2	✓	✓	✓	✓	✓	✓	✓		✓		
	Millennium	PCI	MGA Storm-R1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Millennium 220	PCI	MGA Storm-R2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Millennium 220	PCI	MGA2064W-R2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Millennium 220	PCI	MGA2064W-R3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Millennium II	PCI/AGP	MGA2164W	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Mystique 220	PCI	MGA1064SG (-G or -H)	✓	✓	✓	✓	✓	✓	✓	✓	✓			



**Video Display Adapters (Continued)**

Vendor	Model	Bus	Chipset <sup>23</sup>	Resolution and Color Depth											
				800x600		1024x768		1152x900		1280x1024		1600x1200			
				8	24	8	24	8	24	8	24	8	24		
Micronics	Mpower 4 plus <sup>4</sup>	—	ATI Mach64	✓		✓									
Miro	miroCRYSTAL 20SD	PCI	S3 Vision 864 + S3 SDAC	✓	✓	✓		✓		✓					
	miroCRYSTAL 20SD	PCI	S3 Vision 864	✓	✓	✓		✓		✓					
	miroCRYSTAL 40SV	PCI	S3 Vision 964	✓	✓	✓	✓	✓	✓	✓					
	miroMagic	ISA	S3 805			✓				✓					
Nanao	EizoAccel AA51	ISA	CHIPS F82C480			✓				✓					
	Nanao HA50/HL50	ISA	S3 928			✓				✓			✓		
	Nanao HA60	ISA	S3 928			✓				✓			✓		
Number Nine	#9GXE <sup>19</sup>	ISA	S3 928	✓		✓		✓		✓					
	#9GXE <sup>19</sup>	VLB	S3 928	✓		✓		✓		✓					
	#9GXE64	PCI	S3 Vision 864	✓	✓	✓		✓		✓			✓		
	#9GXE64 Pro	PCI	S3 Vision 964	✓	✓	✓	✓	✓	✓	✓			✓		
	9FX Motion 331	PCI	S3 Trio64V+	✓	✓	✓		✓		✓					
	9FX Motion 531	PCI	S3 Vision 868	✓	✓			✓		✓					
	9FX Motion 771	PCI	S3 Vision 968	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	9FX Reality 332	PCI	S3 ViRGE (86C325)	✓	✓	✓		✓		✓					
	Imagine 128	PCI	Imagine 128	✓	✓	✓	✓	✓	✓	✓			✓		
	Imagine 128 Pro	PCI	Imagine 128	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Imagine 128 Series 2	PCI	Imagine 128 V2	✓	✓	✓	✓	✓	✓	✓			✓		
	Imagine 128 Series 2e	PCI	Imagine 128 V2	✓	✓	✓	✓	✓		✓			✓		
	Vision330 <sup>20</sup>	PCI	S3 Trio64	✓	✓	✓		✓		✓					
Oak Technology	OTI107	PCI	OTI107	✓	✓	✓		✓		✓					
	OTI111	PCI	OTI111	✓	✓	✓		✓		✓					
Orchid	Fahrenheit 1280	ISA	S3 924			✓									
	Fahrenheit 1280 Plus	ISA	S3 801			✓									
	Fahrenheit 1280 Plus	VLB	S3 801	✓		✓									
	Fahrenheit VA	ISA	S3 801			✓									
	Kelvin 64	PCI	Cirrus Logic GD5434	✓	✓	✓		✓		✓					



**Video Display Adapters (Continued)**

Vendor	Model	Bus	Chipset <sup>23</sup>	Resolution and Color Depth										
				800x600		1024x768		1152x900		1280x1024		1600x1200		
				8	24	8	24	8	24	8	24	8	24	
Orchid, cont.	Kelvin 64 <sup>21</sup>	VLB	Cirrus Logic GD5434	✓	✓	✓		✓		✓				
	Prodesigner IIs	ISA	Tseng ET4000			✓								
S3	928 <sup>3</sup>	—	S3 938	✓		✓		✓		✓				
	Trio32 <sup>3</sup>	—	S3 Trio32	✓		✓								
	Trio64 <sup>3</sup>	—	S3 Trio64	✓	✓	✓		✓		✓				
	Trio64V+ <sup>3</sup>	—	S3 Trio64V+	✓	✓	✓		✓		✓				
	Trio64V2/DX <sup>3</sup>	—	S3 Trio64V2/DX (86C775)	✓	✓	✓		✓		✓				
	ViRGE	—	S3 ViRGE (86C325)	✓	✓	✓	✓	✓		✓				
	ViRGE/DX <sup>3</sup>	—	S3 ViRGE/DX (86C375)	✓	✓	✓	✓	✓		✓				
	ViRGE/GX <sup>3</sup>	—	S3 ViRGE/GX (86C385)	✓	✓	✓	✓	✓		✓			✓	
	ViRGE/VX <sup>3</sup>	—	S3 ViRGE/VX (86C988)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Vision 864+SDAC chipset <sup>3</sup>		S3 Vision 864	✓	✓	✓		✓		✓				
	Vision 868 <sup>3</sup>	—	S3 Vision 868	✓		✓		✓		✓				
SPEA	V7-Mercury	ISA				✓								
	V7-Mirage P-64	PCI	S3 Vision 868	✓	✓	✓		✓		✓				
STB	Lightspeed 128	PCI	Tseng ET6000	✓	✓	✓		✓		✓				
	Lightspeed VL	VLB	Tseng ET4000/W32p	✓	✓	✓		✓		✓				
	Nitro 3D	PCI	S3 ViRGE/GX (86C385)	✓	✓	✓	✓	✓		✓			✓	
	Nitro 64 Video	PCI	Cirrus Logic GD5446	✓	✓	✓		✓		✓			✓	
	Nitro PCI	PCI	Cirrus Logic GD5434	✓	✓	✓	✓	✓		✓				
	PowerGraph 64	PCI	S3 Trio64	✓	✓	✓		✓		✓				
	PowerGraph 64 3D	PCI	S3 ViRGE (86C325)	✓	✓	✓		✓		✓			✓	



**Video Display Adapters (Continued)**

Vendor	Model	Bus	Chipset <sup>23</sup>	Resolution and Color Depth									
				800x600		1024x768		1152x900		1280x1024		1600x1200	
				8	24	8	24	8	24	8	24	8	24
STB, cont.	PowerGraph 64 Video	PCI	S3 Trio64V+	✓	✓	✓		✓		✓			
	PowerGraph ERGO	ISA	Tseng ET4000			✓							
	PowerGraph PRO PCI	PCI	S3 Vision 864	✓	✓	✓		✓		✓			
	Velocity 3D	PCI	S3 ViRGE/VX (86C988)	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Velocity 64V	PCI	S3 Vision 968	✓	✓	✓	✓	✓	✓	✓		✓	
Toshiba	J3100	—	Western Digital 90C31A	✓		✓							
Trident	9440 <sup>22</sup>	PCI	TGUI9440	✓		✓							
	9680	PCI	TGUI9680	✓		✓		✓		✓			
	9685	PCI	TGUI9685	✓		✓		✓		✓			
	TVGA 8900C	ISA	Trident 8900C			✓							
	TVGA 9000i		Trident 9000i	✓									
Tseng	ET 6000 <sup>3</sup>	—	Tseng ET 6000	✓	✓	✓		✓		✓			
Western Digital	Paradise Accelerator	ISA	WD90C31			✓							

- The ET4000/W32 video cards that are shipped with Acer machines are not all the same. If you encounter any display problems when the OpenWindows environment is running, try using a different add-on board that is compatible with the Solaris operating environment.
- Video adapters based on the Cirrus Logic GD5424 chipset with 512-Kbyte DRAM may not perform well in 800x600x256 mode, particularly if the selected monitor refresh rate is 60 Hz or higher.
- SunSoft does not guarantee that every video card with this chipset will work, but it is possible that your model will be one of a large number that can be used successfully.
- Support is provided for ATI cards with ATI Mach64 chips and these RAMDACs: ATT68860, ATT20C408, ATT20C491, ATT20C498, STG1702, and STG1703.
- The ATI Winturbo model is equivalent to the Gateway ATI GX Mach64 PCI video card.
- The ProSignia 300 systems and some models of the ProSignia Server systems with the Cirrus Logic 5424 graphics chip are supported. Choose one of the "Cirrus Logic 5424 (512k)" entries when configuring the window system using `kdmconfig`.
- Used on the Compaq QVision 1280/E Graphics Controller and in the Compaq Deskpro 590.
- For cards using the IBM or TI RAMDACs only.
- The Diamond Viper SE is not supported at 80 Hz in 1280x1024 resolution.
- The ELSA Winner 1000Pro with the ATT20C498 RAMDAC is supported.
- Both the STG1702 and the ATT21C498 RAMDACs are supported.
- Select "Cirrus Logic 542x" when configuring the display adapter during Solaris installation.
- 640x480, 16 colors. Any 256-Kbyte or better VGA adapter supporting standard IBM mode 0x12 graphics. For VGA with 800x600 virtual screen, select "16 color, 640x480 VGA panning @800x600 (for experts only, see docs)" when configuring the display adapter during Solaris installation. **Warning:** This selection enables panning mode on a standard VGA. This video mode supports a virtual resolution of 800x600, but is only capable of physically displaying 640x480 pixels at a time. This may be a preferred mode to use on small screens, but the use of panning may require some training. See *x86 Device Configuration Guide* for more information.



- 
14. To support 1152x900 or 1280x1024 resolution on the Intergraph TD-1 display adapter, you must select an interlaced monitor type when configuring the Solaris window system. Choose "Multifrequency 56kHz (up to 1280x1024 interlaced)" as the monitor type. See the documentation supplied with Driver Updates for more information.
  15. The Intergraph G90 is synonymous with the Diamond Viper video card.
  16. The Intergraph G91 also supports a resolution of 1600x1280 for 8-bit color.
  17. To support the Intergraph G95, select the graphics card "Matrox MGA Millenium" when configuring the Solaris window system.
  18. To support the Intergraph ISMP, select the graphics card "Cirrus Logic GD5434" when configuring the Solaris window system.
  19. The Number Nine #9GXE video display adapters (ISA and VESA local bus) support 24-bit color in 640x480 mode *only*.
  20. Select "#9GXE 64 (Trio64)" when configuring the display adapter during Solaris installation.
  21. Older versions of the Orchid Kelvin 64 VLB card have memory addressing limitations that may cause problems if your system contains 32 Mbytes or more of RAM. See the documentation supplied with Driver Updates for further information.
  22. This card does not work at the 1024x768 resolution with a 56-kHz refresh rate.
  23. The information in the chipset column does not guarantee that video boards made by another manufacturer using the same chipset will work. Only the specific models listed by Vendor, Model, Bus, and Chipset have been tested.
- "—" in the Bus column indicates a video controller model that is used on video display adapters and motherboards.



**Notebook Display Video Support**

Vendor	Model	Chipset	Resolution and Color Depth E=With External Monitor I=With Internal Monitor										
			640x480		800x600		1024x768		1280x1024				
			8	24	8	24	8	24	8	24			
Ambra	SN425C <sup>1</sup>	WD 90C24	I										
AST	Ascentia 950N w/SVGA Panel	Cirrus Logic GD7543	E,I		E,I		E						
	PowerExec 4/33SL	WD 90C26	I										
Chips & Technology	65550 <sup>2</sup>	65550	E,I		E,I		E,I						
Compaq	ARMADA 4120T	Cirrus Logic GD7548			E,I		E						
	LTE 4/25C	WD 90C24	I										
	LTE 4/33C	WD 90C24	I										
	LTE Elite 4/40C	WD 90C24	E,I		E		E						
	LTE 5100	Cirrus Logic GD7543	E,I		E,I		E						
	LTE 5200	Cirrus Logic GD7543	E,I		E,I		E						
Dell	Latitude LM P133ST	Neo Magic NM2070			E,I		E						
	Latitude XPi 75D	Cirrus Logic GD7543	E,I		E		E						
	Latitude XPi CD	Neo Magic NM2090			E,I		E						
	Latitude XPi P133ST	Neo Magic NM2070			E,I		E						
Ergo	Power Brick	WD 90C24	I										
HP	Omni 5550	Chips&Technology 65548	E,I		E,I		E						
IBM	ThinkPad 365XD <sup>3</sup>	Trident 9320			E,I		E						
	ThinkPad 750	WD 90C24	E,I										
	ThinkPad 750C	WD 90C24	I										
	ThinkPad 755C	WD 90C24	E,I		E		E						
	ThinkPad 755CD	WD 90C24	E,I		E		E						
	ThinkPad 755CV	WD 90C24	E,I		E		E						
	ThinkPad 755CX w/SVGA Panel	WD 90C24	E,I		E,I		E						
	ThinkPad 760CD	Trident 9320			E,I		E						



**Notebook Display Video Support (Continued)**

Vendor	Model	Chipset	Resolution and Color Depth E=With External Monitor I=With Internal Monitor							
			640x480		800x600		1024x768		1280x1024	
			8	24	8	24	8	24	8	24
IBM, cont.	ThinkPad 760ED	Trident 9385			E,I		E		E	
	ThinkPad 760ED w/XVGA	Trident 9385					E,I		E	
	ThinkPad 760EL	Trident 9385			E,I		E			
NEC	Versa/50	WD 90C24	I							
	Versa M75C	Chips&Technology 65540	E,I		E		E			
	Versa M75HC	Chips&Technology 65545	E,I		E,I		E			
	Versa UltraLite	WD 90C24	I							
Panasonic	CF-V211 <sup>1</sup>	WD 90C24	I							
TI	Extensa 560CDT	Cirrus Logic GD7543	E,I		E		E			
	TravelMate 4000E TFT	Cirrus Logic GD6440	I							
Toshiba	4800CT	WD 90C24	E,I		E		E			
	4850CT	WD 90C24	E,I		E		E			
	4900CT	Chips&Technology 65545	E,I		E		E			
	Portege 610CT	Chips&Technology 65546	E,I		E		E			
	Portege 650CT	Chips&Technology 65550			E,I		E		E	
	Portege 660CDT	Chips&Technology 65554			E,I		E		E	
	Satellite Pro 400CDT	Chips&Technology 65546	E,I		E		E			
	Satellite Pro 410CDT	Chips&Technology 65548	E,I		E,I		E			
	Satellite Pro 425CDT	Chips&Technology 65550	E,I		E,I		E		E	
	T3400	WD 90C24	I							
	T4400C	WD 90C30	I							
	T4600C	WD 90C26	I							
	T4700C	WD 90C24	I							
	Satellite 200CDS	Chips&Technology 65550			E,I		E		E	
	Satellite 220CDS	Chips&Technology 65554			E,I		E		E	
	Tecra 700CT	Chips&Technology 65548	E,I		E,I		E			
	Tecra 500CDT	Chips&Technology 65550	E,I		E,I		E		E	



**Notebook Display Video Support (Continued)**

Vendor	Model	Chipset	Resolution and Color Depth E=With External Monitor I=With Internal Monitor							
			640x480		800x600		1024x768		1280x1024	
			8	24	8	24	8	24	8	24
Toshiba, cont.	Tecra 520CDT	Chips&Technology 65555			E,I		E		E	
	Tecra 530CDT	Chips&Technology 65555					E,I		E	
	Tecra 720CDT	Chips&Technology 65550	E,I		E,I		E,I		E	
	Tecra 730CDT	Chips&Technology 65550	E,I		E,I		E,I		E	
	Tecra 740CDT <sup>3</sup>	Chips&Technology 65554					E,I		E	
Twinhead	Slimnote 486E	WD 90C24	I							
Zenith Data Systems	Z-Note GT	Chips&Technology 65548	E,I		E,I		E			
	Z-Noteflex	WD 90C24	E,I		E		E			

1. Select "T3400ct,T4700ct, Twinhead 486E, ThinkPad 750: WD90C24 w/1Mb" when configuring the display adapter during Solaris installation.
2. Both SVGA andXGA panels are supported.
3. Not tested by SunSoft, but reported to work. Panning is not supported for this notebook.

**Note** – For a list of Notebook Computers that have been tested with the Solaris 2.5/2.5.1 x86 operating environment, see page 22.