

Package ‘ToPASEq’

October 9, 2015

Type Package

Title Package for Topology-based Pathway Analysis of RNASeq data

Version 1.2.0

Date 2014-27-05

Author Ivana Ihnatova, Eva Budinska

Maintainer Ivana Ihnatova <ihnatova@iba.muni.cz>

Description Implementation of seven methods for topology-based pathway analysis of both RNASeq and microarray data: SPIA, DEGraph, TopologyGSA, TAPPA, TBS, PWEA and a visualization tool for a single pathway.

Depends graphite, gRbase, graph, locfit, Rgraphviz

Imports R.utils, methods, Biobase, parallel, edgeR, DESeq2, GenomicRanges, RBGL, DESeq, fields, limma, TeachingDemos, KEGGgraph, qgraph, clipper

Suggests RUnit, BiocGenerics, gageData, DEGraph, plotrix

LinkingTo Rcpp

LazyData yes

License AGPL-3

biocViews Software, GeneExpression, NetworkEnrichment, GraphAndNetwork, RNASeq, Visualization, Microarray, Pathways, DifferentialExpression,

NeedsCompilation yes

R topics documented:

ToPASEq-package	2
AdjacencyMatrix2pathway	3
Clipper	4
collectWeightsPRS	6
convertIdentifiersByVector	8
DEGraph	9

estimateCF	11
graphNEL2pathway	12
KEGG2pathway	13
makeDefaultEdgeData	14
pathway-class	15
preparePathways	17
PRS	18
PWEA	20
reduceGraph	22
res	23
SPIA	24
TAPPA	26
TopologyGSA	28

Index	30
--------------	-----------

ToPASEq-package	<i>Package for topology-based pathway analysis of microarray and RNASeq data</i>
-----------------	--

Description

The package implementats several methods for topology-based pathway analysis of microarray data. The methods present in here are: SPIA, TopologyGSA, DEGraph, Clipper, PWEA, TAPPA, TBS. SPIA, PWEA and TBS were also adapted for RNASeq data.

Details

Package: ToPASEq
 Type: Package
 Version: 1.0
 Date: 2014-03-04
 License: AGPL-3

Author(s)

Ivana Ihnatova

Maintainer: Ivana Ihnatova <ihnatova@iba.muni.cz>

Examples

```
## Not run:
if (require(DEGraph)) {
```

```

data("Loi2008_DEGraphVignette")
pathways<-biocarta[1:10]
SPIA(exprLoi2008, classLoi2008,pathways , type="MA", logFC.th=-1, IDs="entrez")
DEGraph(exprLoi2008, classLoi2008, pathways, type="MA")
TAPPA(exprLoi2008, classLoi2008, pathways, type="MA")
TopologyGSA(exprLoi2008, classLoi2008, pathways, type="MA", nperm=200)
Clipper( exprLoi2008, classLoi2008+1, pathways,type="MA", test="mean")
PWEA(exprLoi2008, classLoi2008, pathways, type="MA", nperm=100)
TBS( exprLoi2008, classLoi2008, pathways, type="MA", logFC.th=-1, nperm=100)
}
if (require(gageData)) {

data(hnrnp.cnts)
group<-c(rep("sample",4), rep("control",4))
SPIA( hnrnp.cnts, group, biocarta[1:10], type="RNASeq", logFC.th=-1, IDs="entrez", test="limma")
DEGraph(hnrnp.cnts, group, biocarta[1:10], type="RNASeq", norm.method="TMM")
TAPPA( hnrnp.cnts, group, biocarta[1:10], type="RNASeq", norm.method="TMM")
TopologyGSA(hnrnp.cnts, group, biocarta[1:10], type="RNASeq",nperm=200, norm.method="TMM")
Clipper(hnrnp.cnts, group,biocarta[1:10], type="RNASeq", norm.method="TMM")
PWEA(hnrnp.cnts, group, biocarta[1:10], type="RNASeq", test="limma", nperm=100)
TBS(hnrnp.cnts, group, biocarta[1:10], type="RNASeq", logFC.th=-1, nperm=100, test="limma")
}

## End(Not run)

```

AdjacencyMatrix2pathway

Function to coerce an adjacency matrix to a pathway

Description

The function coerces an adjacency matrix to a pathway. Two types of matrices are allowed. The first one, where 1 denotes an edge between two nodes and 0 otherwise. This matrix is coerced into a simply pathway were type of all edges is set to "process". The second type of adjacency matrix contains: 1 for an activation, -1 for an inhibition and 0 otherwise (=no edge between two nodes). In this case, activations are set to "process(activation)" and inhibition to "process(inhibition)". The symmetricity of the matrix is used to decide between directed and undirected graph. Symmetric matrix is expected for undirected graph and only the lower triangle of the matrix is used to extract the edges of the graph.

Usage

```
AdjacencyMatrix2pathway(adjmat, name = "pathway", ident = "unknown", database = "unknown", species = '

```

Arguments

adjmat	An adjacency matrix describing the pathway topology
name	A character, name of the pathway. Defaults to "pathway"

ident	A character, type of the identifiers, e.g "gene symbol"
database	A character, the name of the database the topology comes from
species	A character, the species to which the topology belong
date	A date, the date the topology was created

Value

An object of class pathway

Author(s)

Ivana Ihnatova

Examples

```
genes<-paste("gene", 1:10, sep="")
adjmat<-matrix(sample(c(0,0,0,0,1), 100, TRUE),10,10, dimnames=list(genes,genes))
p<-AdjacencyMatrix2pathway(adjmat)
head(edges(p))

adjmat<-matrix(sample(c(0,0,0,0,1,-1), 100, TRUE),10,10, dimnames=list(genes,genes))
p<-AdjacencyMatrix2pathway(adjmat)
head(edges(p))
```

Clipper

Function to use clipper method on microarray or RNA-Seq data

Description

clipper is a method for topological gene set analysis. It implements a two-step empirical approach based on the exploitation of graph decomposition into a junction tree to reconstruct the most relevant signal path. In the first step clipper selects significant pathways according to statistical tests on the means and the concentration matrices of the graphs derived from pathway topologies. Then, it "clips" the whole pathway identifying the signal paths having the greatest association with a specific phenotype.

Usage

```
Clipper(x, group, pathways, type, preparePaths=TRUE, norm.method=NULL, test.method=NULL, method="mea
  both.directions=TRUE, maxNodes=150, minEdges=0, commonTh=2, filterSPIA=FALSE, convertTo="none", co
```

Arguments

x	An ExpressionSet object or a gene expression data matrix or count matrix, rows refer to genes, columns to samples
group	Name or number of the phenoData column or a character vector or factor that contains required class assignments
pathways	A list of pathways in a form from graphite package or created by preparePathways()
type	Type of the input data, "MA" for microarray and "RNASeq" for RNA-Seq
preparePaths	Logical, by default the pathways are transformed with preparePathways(). Use FALSE, if you have done this transformation separately
norm.method	Character, the method to normalize RNAseq data. If NULL then TMM-normalization is performed. Possible values are: "TMM", "DESeq2", "rLog", "none"
test.method	Character, the method for differential expression analysis of RNAseq data. If NULL then "voomlimma" is used. Possible values are: "DESeq2", "voomlimma", "vstlimma", "edgeR". This analysis is needed only for the visualization.
method	Character, "mean" or "var", the kind of test to perform on the cliques
testCliques	Logical, if TRUE then the test is applied also on the cliques of the each pathway. It is a very time consuming calculation, especially for many or big pathways
nperm	Number of permutations
alphaV	Numeric, the threshold for variance test. The calculation of mean test depends on the result of variance test.
b	number of permutations for mean analysis
permute	always performs permutations in the concentration matrix test. If FALSE, the test is made using the asymptotic distribution of the log-likelihood ratio. This option should be use only if samples size is >=40 per class
both.directions, maxNodes, minEdges, commonTh, filterSPIA, convertTo, convertBy	Arguments for the preparePathways()

Value

A list,	
res	A list. First slot is a data frame containing p-values and q-values of mean and variance tests on pathways. The second slot is a list containing data.frames of the most affected paths in each pathway. The columns of the data frames contain: 1 - Index of the starting clique 2 - Index of the ending clique 3 - Index of the clique where the maximum value is reached 4 - length of the path 5 - maximum score of the path 6 - average score along the path 7 - percentage of path activation 8 - impact of the path on the entire pathway 9 - clique involved and significant 10 - clique forming the path 11 - genes forming the significant cliques 12 - genes forming the path
topo.sig	if testCliques=TRUE, a list where each slot contains the pvalues and a list of cliques in one pathway. NULL otherwise
degtest	A data.frame of gene-level differential expression statistics

Note

If there are NA's only in columns 3 to 7, then a junction tree could not be formed.

Author(s)

Ivana Ihnatova

References

Martini P, Sales G, Massa MS, Chiogna M, Romualdi C. Along signal paths: an empirical gene set approach exploiting pathway topology. *Nucleic Acids Res.* 2013 Jan 7;41(1):e19. doi: 10.1093/nar/gks866. Epub 2012 Sep 21. PubMed PMID: 23002139; PubMed Central PMCID: PMC3592432.

See Also

[preparePathways](#)

Examples

```
if (require(DEGraph)) {
  data("Loi2008_DEGraphVignette")
  pathways<-pathways("hsapiens", "kegg")[1]
  pathways<-lapply(pathways, function(p) as(p,"pathway"))
  Clipper( exprLoi2008, classLoi2008, pathways,type="MA", convertTo="none")
}

## Not run:
if (require(gageData)) {

  data(hnrnp.cnts)
  hnrnp.cnts<-hnrnp.cnts[rowSums(hnrnp.cnts)>0,]
  group<-c(rep("sample",4), rep("control",4))
  pathways<-pathways("hsapiens", "kegg")[1:3]
  pathways<-lapply(pathways, function(p) as(p,"pathway"))
  Clipper(hnrnp.cnts, group,pathways, type="RNASeq", norm.method="TMM", convertTo="none")
}

## End(Not run)
```

Description

The functions calculate gene-level weights defined in various topology-based pathway analysis methods (PRS, SPIA, PWEA). In PRS, it is the number of downstream differentially expressed genes. TIF, the statistic defined in PWEA, is related to the ratio of correlation and distance of genes. SPIA defines the so called net perturbation factors.

Usage

```
collectWeightsPRS(de, all, pathways)
collectWeightsSPIA(de, all, pathways)
prepareTIF(pathways, exprs, alpha)
```

Arguments

de	Named numeric vector, the log fold-changes of the differentially expressed genes
all	Character vector of all genes measured in the experiment
pathways	A list of pathways, each pathway is an object of class pathway transformed via preparePathways() for the particular method
exprs	A numeric matrix, gene expression data matrix, rows refer to genes, columns to samples
alpha	Numeric, a threshold to control the magnitude. In TIF calculation, the effect of a gene on a few nearby and tightly correlated genes can be washed out if the gene influences many other genes weakly. The threshold suppresses this washing-out

Value

A list, each slot is a vector of gene-level weights for one pathway

Author(s)

Ivana Ihnatova

Examples

```
pathways<-pathways("hsapiens", "kegg")[1:3]
pathways<-lapply(pathways, function(p) as(p, "pathway"))
de<-setNames(rnorm(30), sample(nodes(pathways[[1]]), 30))
all<-nodes(pathways[[1]])

path<-preparePathways(pathways[1:3], method="SPIA", genes=all, both.direction=TRUE, convertTo="none")
collectWeightsSPIA(de, all, path)
```

`convertIdentifiersByVector`*Function to convert identifiers in pathways by user specified vector*

Description

The function converts identifiers of nodes in a pathway. It uses the user specified named vector for the conversion.

Usage

```
convertIdentifiersByVector(pathway, conv.table, id.type="unknown")
```

Arguments

<code>pathway</code>	An object of class pathway
<code>conv.table</code>	A named vector in which names correspond to the identifiers present in the pathway and values are the new identifiers to which conversion happens
<code>id.type</code>	A character, the type of the identifiers provided e.g "TAIR" for TAIR numbers. This is for informative purposes only.

Value

A pathway in which identifiers have been converted

Author(s)

Ivana Ihnatova

See Also

[convertIdentifiers](#)

Examples

```
g<-kegg[["Asthma"]]  
g<-as(g, "pathway")  
conv<-setNames(paste("gene", 1:length(nodes(g)), sep=""), nodes(g))  
gc<-convertIdentifiersByVector(g, conv, "dummy")  
nodes(gc)  
edges(gc)
```


DEGraph

*Function to use DEGraph method on microarray or RNA-Seq data***Description**

DEGraph implements recent hypothesis testing methods which directly assess whether a particular gene network is differentially expressed between two conditions. It employs Graph Laplacian, Fourier transformation and multivariate T2-statistic

Usage

```
DEGraph(x, group, pathways, type, preparePaths=TRUE, norm.method=NULL, test.method=NULL, overall="big",
        both.directions=TRUE, maxNodes=150, minEdges=0, commonTh=2, filterSPIA=FALSE, convertTo="none", co
```

Arguments

x	An ExpressionSet object or a gene expression data matrix or count matrix, rows refer to genes, columns to samples
group	Name or number of the phenoData column or a character vector or factor that contains required class assignments
pathways	A list of pathways in a form from graphite package or created by preparePathways()
type	Type of the data, "MA" for microarray and "RNASeq" for RNA-Seq
preparePaths	Logical, by default the pathways are transformed with preparePathways(). Use FALSE, if you have done this transformation separately
norm.method	Character, the method to normalize RNAseq data. If NULL then TMM-normalization is performed. Possible values are: "TMM", "DESeq2", "rLog", "none"
test.method	Character, the method for differential expression analysis of RNAseq data. If NULL then "voomlimma" is used. Possible values are: "DESeq2", "voomlimma", "vstlimma", "edgeR". This analysis is needed only for the visualization.
overall	Character, how should the overall p-value for a pathway be calculated. The possible values are: "mean", "min", "biggest". "biggest" returns the p-value of the biggest connected component.
useInteractionSigns	Logical, should types of interaction be included in the analysis?
EdgeAttrs	A list containing two data.frames. See makeDefaultEdgeData() for the details. The interactions are assigned signs according to the beta column of the second data.frame. The procedure is similar to the SPIA method
both.directions, maxNodes, minEdges, commonTh, filterSPIA, convertTo, convertBy	Arguments for the preparePathways()

Value

A list:

<code>res</code>	Results from analysis of individual pathways. The first column refers to the overall p-value for a pathway. Then groups of four columns follows. One group refers to one connected component and contains a pair of p-values (without and with Fourier transformation), graph and number of Fourier componets used in the test. The number of groups is equal to the highest number of components in analysed pathways. Components are sorted in the decreasing order of their nodes number.
<code>topo.sig</code>	NULL, present for the compatibility with outputs from other methods
<code>degtest</code>	A data.frame of gene-level statistics of all genes in the dataset

Author(s)

Ivana Ihnatova

References

L. Jacob, P. Neuviail, and S. Dudoit. Gains in power from structured two-sample tests of means on graphs. Technical Report arXiv:q-bio/1009.5173v1, arXiv, 2010.

See Also

[preparePathways](#)

Examples

```
if (require(DEGraph)) {
  data("Loi2008_DEGraphVignette")
  pathways<-pathways("hsapiens", "biocarta")[1:10]
  pathways<-lapply(pathways, function(p) as(p, "pathway"))
  DEGraph(exprLoi2008, classLoi2008, pathways, type="MA")
}
## Not run:
if (require(gageData)) {

  data(hnrnp.cnts)
  hnrnp.cnts<-hnrnp.cnts[rowSums(hnrnp.cnts)>0,]
  group<-c(rep("sample",4), rep("control",4))
  pathways<-pathways("hsapiens", "biocarta")[1:10]
  pathways<-lapply(pathways, function(p) as(p, "pathway"))
  DEGraph(hnrnp.cnts, group, pathways, type="RNASeq", norm.method="TMM")
}

## End(Not run)
```

estimateCF	<i>Function to estimate multi-subunit protein complexes and gene families in a pathway</i>
------------	--

Description

Function estimates the multi-subunit protein complexes and gene families in a pathway. A protein complex consists of proteins connected by undirected binding interaction. A gene family is a set of nodes with same outgoing and/or incoming edges.

Usage

```
estimateCF(graph)
```

Arguments

graph	An object of class pathway
-------	----------------------------

Value

complexes	A list of estimated protein complexes'
-----------	--

families	A list of estimated gene families
----------	-----------------------------------

The function attempts to assign a representative name to each gene family. The representative name is a common part of the names of individual genes. This approach, however, may lead to ambiguities or missings. Then a general name in a form of family1, family2, etc. All the complexes are named analogously as complex1, complex2.

Author(s)

Ivana Ihnatova

See Also

[reduceGraph](#)

Examples

```
pathway<-as(kegg[[1]], "pathway")
estimateCF(pathway)
```

graphNEL2pathway *Function to coerce a graphNEL to a pathway*

Description

The function coerces a graphNEL to a pathway. It attempts to recover the edge types from "edgeType" attribute of edgeData. The result contains only the edge types present in the graph. If the edgeData do not contain this attribute, then "process(indirect effect)" is used in order to preserve directionality.

Usage

```
graphNEL2pathway(graph, name = "pathway", ident = "unknown", database = "unknown", species = "unknown")
```

Arguments

graph	A graphNEL object to be coerced.
name	A character, name of the pathway. Defaults to "pathway"
ident	A character, type of the identifiers, e.g "gene symbol"
database	A character, the name of the database the topology comes from
species	A character, the species to which the topology belong
date	A date, the date the topology was created

Value

A coerced pathway

Note

When this function is applied on x as reversed operation to as(x, "pathway") then the order of the edges may differ as well as the directionality of "process(indirect)" edges as they are set as undirected by graphNEL2Pathway.

Author(s)

Ivana Ihnatova

Examples

```
pathway<-kegg[[1]]
pathway<-as(pathway, "pathway")
as(pathway, "graphNEL")
graphNEL2pathway(as(pathway, "graphNEL"))

set.seed(123)
rg <- randomEGraph(LETTERS[1:20], edges = 30)
p<-graphNEL2pathway(rg)
```

```
p
head(edges(p))
```

 KEGG2pathway

Function to parse KEGG KGML file into a pathway

Description

The function parses a KGML file from KEGG into a pathway.

Usage

```
KEGG2pathway(file, expandGenes = TRUE, expandCom = TRUE, nongene = c("keep", "propagate", "discard"),
```

Arguments

file	Character, the name of the file to be parsed. Download manually or in bulk from KEGG
expandGenes	Logical, should multi-gene nodes be expanded into separate nodes?
expandCom	Logical, should undirected binding interactions be added between nodes from one group (usually multi-subunit protein complex, which is turned into a clique)
nongene	Character, how should be the non-gene nodes parsed? If "discard" they are removed from the pathway. If "propagate", they are removed but the interactions are preserved (e.g. if gene A interacts with compound c and compound c interacts with gene B, then the interaction between A and B is preserved. Otherwise, they are kept in the pathway topology)
ident	Character, the type of the node identifiers.
database	Character, the name of the database
species	Character, the three-letter code for the species-specific pathways. If NULL then, the first 3 letters from the file are used.

Value

A pathway

Author(s)

Ivana Ihnatova

makeDefaultEdgeData *Creates auxiliary data needed for SPIA method*

Description

This function creates a list containing auxiliary data needed in SPIA method for conversion between edge types and dividing interaction into three categories: positive, negative and neutral

Usage

```
makeDefaultEdgeData
```

Details

The first slot called `graphite2SPIA` contains a mapping table between edge types in topologies from `graphite` and edge types which are used in the implementation of SPIA in SPIA package. All of the edge types present in the topologies must be also covered by this table otherwise the method could not be applied.

The second slot called `beta` divides the 25 interaction types into three categories: positive ($\beta=1$), negative ($\beta=-1$) and neutral ($\beta=0$) in the sense of gene regulation. Only user familiar with all the details of SPIA should change this.

Value

A list of two data frames explained in the *Details*. The format is: List of 2 \$ graphite2SPIA: chr [1:26, 1:2] "L
 ..- attr(*, "dimnames")=List of 2\$: NULL\$: chr [1:2] "type" "spiaType"
 \$ beta : 'data.frame': 25 obs. of 2 variables: ..\$ rel : chr [1:25] "activation" "compound" "b
 ..\$ beta: num [1:25] 1 0 0 1 -1 1 0 -1 -1 0 ...

Source

The data are manually created from the unexported objects from `graphite` package version 1.10.1.

Examples

```
str(makeDefaultEdgeData())
```

pathway-class	Class "pathway"
---------------	-----------------

Description

This class represents a biological pathway. It is a class from the package `graphite` up to version 1.12. `changeInteraction` and `changeDirection` are a new generic function designed for pathway class

Value

A pathway

Slots

title: Object of class "vector".

nodes: Object of class "vector".

edges: Object of class "data.frame". The data.frame has one row for each edge and four columns: source node, destination node, edge direction and type.

ident: Object of class "vector". The type of identifiers used to label the nodes. The value of "native" means that the identifiers are those present in the original pathway definition.

See [convertIdentifiers](#) to convert them.

database: Object of class "vector". The name of the database from which the pathway was retrieved.

species: Object of class "character". The name of the species the pathway belongs to.

timestamp: Object of class "Date". The date when the pathway was retrieved.

Methods

edges signature(object = "pathway"): retrieves the data.frame describing the pathway edges.

nodes signature(object = "pathway"): retrieves the vector enumerating the identifiers of the pathway nodes.

The methods below perform basic topological analysis of a pathway. They were defined as generic in graph for graph class. They were implemented for pathway in this package

degree signature(object = "pathway", Nodes = "character") Returns the number of incoming or outgoing edges for nodes in Nodes

degree signature(object = "pathway", Nodes = "missing") Returns the number of incoming or outgoing edges for all nodes in object

numNoEdges signature(objGraph = "pathway") Returns the number of nodes without any edge

mostEdges signature(objGraph = "pathway") Returns the nodes with most edges

- acc** signature(object = "pathway", index = "character") Returns the set of nodes accessible from nodes in index. The undirected edges are considered as bidirected (directed in both directions)
- connComp** signature(object = "pathway") Returns the connected components present in a pathway. They are returned as list where each slot refers to one component and contains the relevant nodes. The undirected edges are considered as bidirected (directed in both directions)
- edges** signature(object = "pathway", which = "character") Returns the edges relevant to node(s) in which
- isAdjacent** signature(object = "pathway", from = "character", to = "character") Returns whether nodes in from and to are adjacent (there is an edge starting in from and ending in to)
- isConnected** signature(object = "pathway") Returns TRUE if a pathway contains only one connected component
- isDirected** signature(object = "pathway") Returns TRUE if all edges in a pathway are directed
- edgemode** signature(object = "pathway") Returns the type of edges in a pathway: directed, undirected or both
- numEdges** signature(object = "pathway") Returns the number of edges in a pathway
- numNodes** signature(object = "pathway") Returns the number of nodes in a pathway
- edgeNames** signature(object = "pathway") Returns the names of the edges in a following format: starting node ~ ending node

All of the methods below return an object of class pathway with modified topology.

- intersection** signature(x = "pathway", y = "pathway") compute the intersection of the two supplied graphs. They must have identical nodes.
- join** signature(x = "pathway", y = "pathway") returns the joining of the two graphs. It is similar to intersection but does not require the identical nodes
- union** signature(x = "pathway", y = "pathway") compute the union of the two supplied graphs. They must have identical nodes.
- subGraph** signature(nodes = "character", graph = "pathway") Given a set of nodes and a pathway this function creates and returns subgraph with only the supplied nodes and any edges between them
- clearNode** signature(node = "character", object = "pathway") Clears all edges incoming and outgoing edges from node
- removeEdge** signature(from = "character", to = "character", graph = "character") removes all directed edges starting in from and ending in to and undirected edges between from and to
- removeNode** signature(node = "character", object = "pathway") removes node(s) node from a pathway object
- nodes<-** signature(object = "pathway", value = "character") sets node labels of pathway object to value

preparePathways *Function to prepare pathways for topology-based pathway analysis*

Description

Functions transforms pathways from graphite package (stored as pathway-class) into formats required in the particular topology-based method implemented in this package. It also converts identifiers in the pathways and filters pathways according to several criteria.

Usage

```
preparePathways(pathways, method, both.directions, genes, maxNodes = 150, minEdges = 0, commonTh = 2,
```

Arguments

pathways	A list of pathways, individual pathways are objects of class pathway
method	A character, the pathways will be transformed according to the needs of the particular method. Possible values are: "TAPPA", "PRS", "PWEA", "TopologyGSA", "clipper", "DEGra
both.directions	Logical, indicates how should be the undirected edges directed. If TRUE, an undirected edge is substituted with two directed edges with opposite directions (e.g. A-B becomes A->B and B->A). If FALSE, then an undirected edge is substituted with one directed edge which preserves the order of nodes (e.g. A-B becomes A->B).
genes	Character vector, vector of gene identifiers in the expression data
maxNodes	Numeric, maximal number of nodes. Pathways with more nodes are filtered out.
minEdges	Numeric, minimal number of edges. Pathways with less edges are filtered out.
commonTh	Numeric, threshold for number of nodes present in the data. Pathways with less node-identifiers matching to genes are filtered out.
filterSPIA	Logical, if TRUE applies filter defined in the SPIA method (relates to the calculation of inversion matrix).
convertTo	Character, one of the "entrez", "symbol" or "none". If "none" no conversion is performed. Otherwise, the function converts node-identifiers in pathways from graphite into either EntrezIDs or gene symbols. Uses org.Hs.eg.db package for the mapping.
convertBy	Named character vector, names of the element must match the node-identifiers and the values are the new identifiers to be replaced. This is a more general option designed for pathways outside graphite.
EdgeAttrs	A list of two tables required for the filter from SPIA method. See makeDefaultEdgeData for the details.

Value

A list of the transformed pathways

Author(s)

Ivana Ihnatova

See Also[makeDefaultEdgeData](#)**Examples**

```
#Creating dummy set of genes
set.seed(123)
pathways<-pathways("hsapiens","kegg")[1:3]
  pathways<-lapply(pathways, function(p) as(p,"pathway"))
genes<-unname(unlist(lapply(pathways[1:3], nodes)))
genes<-sample(genes, length(genes)*0.9)

#Applying the function
paths<-preparePathways(pathways[1:3], "TAPPA", TRUE, genes, maxNodes=65, convertTo="none")
paths
```

 PRS

Function to use PRS method on microarray or RNA-Seq data

Description

A function runs PRS method on a gene expression data matrix or count matrix and vector dividing samples into two groups and a set of pathways from graphite package. The PRS method (please see Reference for the details) was adapted to graphite's graphs where each node is represented only by one gene.

Usage

```
PRS(x, group, pathways, type, preparePaths=TRUE, norm.method=NULL, test.method=NULL, p.th=0.05, logFC
  both.directions=TRUE, maxNodes=150, minEdges=0, commonTh=2, filterSPIA=FALSE, convertTo="none", conv
```

Arguments

x	An ExpressionSet object or a gene expression data matrix or count matrix, rows refer to genes, columns to samples
group	Name or number of the phenoData column or a character vector or factor that contains required class assignments
pathways	A list of pathways in a form from graphite package or created by preparePathways()
type	Type of the data, "MA" for microarray, "RNASeq" for RNA-Seq, DEtable data.frame from differential expression analysis, or DEGList a list of: log fold-changes of differentially expressed genes and names of the all genes analyses

<code>preparePaths</code>	Logical, by default the pathways are transformed with <code>preparePathways()</code> . Use FALSE, if you have done this transformation separately
<code>norm.method</code>	Character, the method to normalize RNAseq data. If NULL then TMM-normalization is performed. Possible values are: "TMM", "DESeq2", "rLog", "none". Ignored for type: "MA", "DEtable", "DElist"
<code>test.method</code>	Character, the method for differential expression analysis of RNAseq data. If NULL then "voomlimma" is used. Possible values are: "DESeq2", "voomlimma", "vstlimma", "edgeR". Ignored for type: "MA", "DEtable", "DElist"
<code>p.th</code>	Numeric, threshold for p-values of tests for differential expression of genes. Use 1 if you don't want any threshold to be applied
<code>logFC.th</code>	Numeric, threshold for log fold-change of a gene to identify the gene as differentially expressed. Use negative if you don't want any threshold to be applied
<code>nperm</code>	Numeric, number of permutations
<code>both.directions</code> , <code>maxNodes</code> , <code>minEdges</code> , <code>commonTh</code> , <code>filterSPIA</code> , <code>convertTo</code> , <code>convertBy</code>	Arguments for the <code>preparePathways()</code>

Value

	A list,
<code>res</code>	A data frame with normalized score, p-value and FDR-adjusted p-value for each pathway
<code>topo.sig</code>	A list with log fold-changes and number of downstream differentially expressed nodes for nodes of individual pathways
<code>degtest</code>	A named vector of statistics from testing the differential expression of genes

Author(s)

Ivana Ihnatova

References

Maysson Al-Haj Ibrahim, Sabah Jassim, Michael Anthony Cawthorne, and Kenneth Langlands. A Topology-Based Score for Pathway Enrichment, *Journal of Computational Biology*. May 2012, 19(5): 563-573

See Also

[preparePathways](#)

Examples

```
if (require(DEGraph)) {
  data("Loi2008_DEGraphVignette")
  pathways<-pathways("hsapiens", "biocarta")[1:10]
  pathways<-lapply(pathways, function(p) as(p, "pathway"))
  PRS( exprLoi2008, classLoi2008, pathways, type="MA", logFC.th=-1, nperm=100)
```

```

}
## Not run:
if (require(gageData)) {

  data(hnrnp.cnts)
  hnrnp.cnts<-hnrnp.cnts[rowSums(hnrnp.cnts)>0,]
  group<-c(rep("sample",4), rep("control",4))
  pathways<-pathways("hsapiens","biocarta")[1:10]
  pathways<-lapply(pathways, function(p) as(p,"pathway"))
  PRS(hnrnp.cnts, group, pathways, type="RNASeq", logFC.th=-1, nperm=100, test="vstlimma")
}

## End(Not run)

```

PWEA

Function to use PWEA method on microarray or RNA-Seq data

Description

The function runs PWEA method (please see References for the details) on gene expression data matrix, vector specifying to which group a sample belongs and a list of pathway graphs. Briefly, it is a weighted GSEA-like method. The weightes are based on the distance and Pearson's correlation between genes in a pathway.

Usage

```
PWEA(x, group, pathways, type, preparePaths=TRUE, norm.method=NULL, test.method=NULL, tif=NULL, alpha
      both.directions=TRUE, maxNodes=150, minEdges=0, commonTh=2, filterSPIA=FALSE, convertTo="none", cor
```

Arguments

x	An ExpressionSet object or a gene expression data matrix or count matrix, rows refer to genes, columns to samples. Or a list of two data.frames: observed and random (after group permutations) of statistics of differential expression of genes
group	Name or number of the phenoData column or a character vector or factor that contains required class assignments
pathways	A list of pathways in a form from graphite package or created by preparePathways()
type	Type of the data, "MA" for microarray, "RNASeq" for RNA-Seq or "DEtable" for a list of observed and random gene-level statistics
preparePaths	Logical, by default the pathways are transformed with preparePathways(). Use FALSE, if you have done this transformation separately
norm.method	Character, the method to normalize RNAseq data. If NULL then TMM-normalization is performed. Possible values are: "TMM", "DESeq2", "rLog", "none"
test.method	Character, the method for differentially expression analysis of RNAseq data. If NULL then "voomlimma" is used. Possible values are: "DESeq2", "voomlimma", "vstlimma", "edgeR"

tif	A list of Topology Influence Factor's. One slot refers to one pathway. Use <code>prepareTIF()</code> to create it. It is required only if <code>type=="DEtable"</code>
alpha	Numeric, a threshold value used during TIF calculation
nperm	Numeric, number of permutations. Used only if <code>x %in% c("MA", "RNASeq")</code>
ncores	Numeric, number of cores. Used only if <code>x %in% c("MA", "RNASeq")</code> . The permutations are calculated in parallel way
both.directions, maxNodes, minEdges, commonTh, filterSPIA, convertTo, convertBy	Arguments for the <code>preparePathways()</code>

Value

A list	
res	A data frame, rows refer to pathways. It contains: Enrichment score for a pathway, p-value and p-value adjusted for multiple hypothesis testing by Benjamini-Hochberg's FDR method. NA's if less than 2 nodes are present in the data
topo.sig	A list, topology influence factors for the genes in individual pathways. NULL if less than 2 nodes are present in the data
degtest	A named vector of statistics from testing the differential expression

Author(s)

Ivana Ihnatova

References

Hung, JH., Whitfield, T. W., Yang, TH., Hu, Z., Weng, Z., DeLisi, Ch. (2010) Identification of functional modules that correlate with phenotypic difference: the influence of network topology, *Genome Biology*, 11:R23

See Also

[preparePathways](#), [prepareTIF](#)

Examples

```
## Not run:
if (require(DEGraph)) {
  data("Loi2008_DEGraphVignette")
  pathways<-pathways("hsapiens","biocarta")[1:10]
  pathways<-lapply(pathways, function(p) as(p,"pathway"))
  PWEA(exprLoi2008, classLoi2008, pathways, type="MA", nperm=100)
}
```

```
if (require(gageData)) {
  data(hnrnp.cnts)
  hnrnp.cnts<-hnrnp.cnts[rowSums(hnrnp.cnts)>0,]
  group<-c(rep("sample",4), rep("control",4))
```

```

pathways<-pathways("hsapiens","biocarta")[1:10]
pathways<-lapply(pathways, function(p) as(p,"pathway"))
PWEA(hnrnp.cnts, group, pathways, type="RNASeq", test="vstlimma", nperm=100)
}

## End(Not run)

```

reduceGraph

Function to reduce the pathway graph

Description

Function simplifies a pathway graph topology. It merges a user specified nodes into a one. The specified set of nodes must be either a gene family or a protein complex. By a gene family we mean a set of genes with same outgoing or incoming edges. On the other hand, a protein complex is a set of nodes with only undirected binding edges between them and the number of edges is equal to the complex size.

Usage

```
reduceGraph(graph, reduction)
```

Arguments

graph	An object of class pathway, a pathway to be reduced
reduction	A named list of reductions to be made.

Value

A pathway

Author(s)

Ivana Ihnatova

Examples

```

pathways<-pathways("hsapiens","kegg")["Prolactin signaling pathway"]
pathways<-convertIdentifiers(pathways[[1]], "symbol")

```

```

gr<-as(pathways,"pathway")
red<-list(RAS=c("NRAS","KRAS","HRAS"), SHC=c("SHC1", "SHC4","SHC2","SHC3"))
reduced<-reduceGraph(gr, red)
reduced
par(mfrow=c(1,2))

```

```

nA<-list(fillcolor=c(NRAS="red", KRAS="red", HRAS="red", SHC1="green", SHC4="green", SHC2="green", SHC3="green"),
plot(as(gr,"graphNEL"), nodeAttrs=nA, attrs=list(node=list(fontsize=30, height=40)), main="Before")

```

```

plot(as(reduced,"graphNEL"),
     nodeAttrs=list(fillcolor=c(RAS="red", SHC="green")), attrs=list(node=list(fontsize=30, height=40)), main="After")

#this throws an error, "RELA", "FOS", "NFKB1" is not correct set of genes
## Not run:
pathways<-pathways("hsapiens","kegg")["Prolactin signaling pathway"]
pathways<-convertIdentifiers(pathways[[1]], "symbol")

gr<-as(pathways,"pathway")
gr<-convertIdentifiers(kegg[["Prolactin signaling pathway"]], "symbol")
red<-list(RAS=c("NRAS","KRAS","HRAS"), SHC=c("RELA", "FOS","NFKB1"))
reduced<-reduceGraph(gr, red)

## End(Not run)

pathways<-pathways("hsapiens","kegg")["p53 signaling pathway"]
pathways<-convertIdentifiers(pathways[[1]], "symbol")

gr<-as(pathways,"pathway")

reduced<-reduceGraph(gr, list(com=c("CCNE1", "CDK2", "CCNE2")))

par(mfrow=c(1,2))

nA<-list(fillcolor=c(CCNE1="red", CDK2="red", CCNE2="red"))
plot(as(gr,"graphNEL"), nodeAttrs=nA, attrs=list(node=list(fontsize=30, height=40)), main="Before")

plot(as(reduced,"graphNEL"),
     nodeAttrs=list(fillcolor=c(com="red")), attrs=list(node=list(fontsize=30, height=40)), main="After")

```

res

Function to extract parts of object

Description

Function extracts part of an object named "res", "topo.sig", "degtable"

Usage

```

res(object)
topo.sig(object)
degtable(object)

```

Arguments

object Object of defined class. Methods for topResult are available in this package

Value

Extracted parts of an object. Data type varies between parts and the origin of the object

Author(s)

Ivana Ihnatova

SPIA

Function to use SPIA method on microarray or RNA-Seq data

Description

The function runs SPIA method on microarray or RNA-Seq data. The implementation includes the identification of differentially expressed genes and transformation of pathways' topologies to an appropriate form. The SPIA method combines two independent p-values. One p-value comes from overrepresentation analysis and the other is so called perturbation factor.

Usage

```
SPIA(x, group, pathways, type, preparePaths=TRUE, norm.method=NULL, test.method=NULL, p.th=0.05, logFC.th=1,
both.directions=TRUE, maxNodes=150, minEdges=0, commonTh=2, filterSPIA=FALSE, convertTo="none", conv
```

Arguments

x	An ExpressionSet object or a gene expression data matrix or count matrix, rows refer to genes, columns to samples
group	Name or number of the phenoData column or a character vector or factor that contains required class assignments
pathways	A list of pathways in a form from graphite package or created by preparePathways()
type	Type of the data, "MA" for microarray, "RNASeq" for RNA-Seq, DEtable data.frame from differential expression analysis, or DEList a list of: log fold-changes of differentially expressed genes and names of the all genes analyses
preparePaths	Logical, by default the pathways are transformed with preparePathways(). Use FALSE, if you have done this transformation separately
norm.method	Character, the method to normalize RNAseq data. If NULL then TMM-normalization is performed. Possible values are: "TMM", "DESeq2", "rLog", "none". Ignored for type: "MA", "DEtable", "DElist"
test.method	Character, the method for differential expression analysis of RNAseq data. If NULL then "voomlimma" is used. Possible values are: "DESeq2", "voomlimma", "vstlimma", "edgeR". Ignored for type: "MA", "DEtable", "DElist"
p.th	Numeric, threshold for p-values of tests for differential expression of genes. Use 1 if you don't want any threshold to be applied
logFC.th	Numeric, threshold for log fold-change of a gene to identify the gene as differentially expressed. Use negative if you don't want any threshold to be applied

nperm	Numeric, number of permutations
combine	Character, the method to combine p-values. Defaults to "fisher" for Fisher's method. The other possible value is "norminv" for the normal inversion method.
both.directions, maxNodes, minEdges, commonTh, filterSPIA, convertTo, convertBy	Arguments for the preparePathways()

Value

A list:

res	A matrix with columns as described below: pSize - Pathway size, number of genes, NDE - Number of differentially expressed genes, pNDE - P-value of the overrepresentation part of the method, tA - The observed total perturbation accumulation in the pathway, pPERT - P-value of the perturbation part of the method, p - Combined p-value (overrepresentation and perturbation), pFdr - False discovery rate adjusted p, pFWER - FWER adjusted p, Status - If a pathway was identified as Activated or Inhibited
topo.sig	A list of accumulated perturbation factors and log fold-changes for genes in individual pathways
degtest	A numeric vector of gene-level differential expression statistics of all genes in the dataset

Author(s)

Ivana Ihnatova

References

Tarca AL, Draghici S, Khatri P, Hassan SS, Mittal P, Kim JS, Kim CJ, Kusanovic JP, Romero R. A novel signaling pathway impact analysis. *Bioinformatics*. 2009 Jan 1;25(1):75-82.

Adi L. Tarca, Sorin Draghici, Purvesh Khatri, et. al, A Signaling Pathway Impact Analysis for Microarray Experiments, 2008, *Bioinformatics*, 2009, 25(1):75-82.

Draghici, S., Khatri, P., Tarca, A.L., Amin, K., Done, A., Voichita, C., Georgescu, C., Romero, R.: A systems biology approach for pathway level analysis. *Genome Research*, 17, 2007.

See Also

[preparePathways](#)

Examples

```
if (require(DEGraph)) {
  data("Loi2008_DEGraphVignette")
  pathways<-pathways("hsapiens", "biocarta")[1:10]
  pathways<-lapply(pathways, function(p) as(p,"pathway"))
  SPIA(exprLoi2008, classLoi2008,pathways, type="MA", logFC.th=-1)
}
## Not run:
```

```

if (require(gageData)) {

  data(hnrnp.cnts)
  hnrnp.cnts<-hnrnp.cnts[rowSums(hnrnp.cnts)>0,]
  group<-c(rep("sample",4), rep("control",4))

  pathways<-pathways("hsapiens","biocarta")[1:10]
  pathways<-lapply(pathways, function(p) as(p,"pathway"))
  SPIA( hnrnp.cnts, group, pathways, type="RNASeq", logFC.th=-1, IDs="entrez", test="vstlimma")
}

## End(Not run)

```

TAPPA

*Function to use TAPPA method on microarray or RNA-Seq data***Description**

The functions analyses the differential expression of pathways via TAPPA method. Expression is compared between two groups of samples by Mann-Whitney test. P-values are later adjusted for multiple hypothesis testing by Benjamini-Hochberg's FDR method.

Usage

```
TAPPA(x, group, pathways, type, preparePaths=TRUE, norm.method=NULL, test.method=NULL, test=t.test,
      maxNodes=150, minEdges=0, commonTh=2, filterSPIA=FALSE, convertTo="none", convertBy=NULL)
```

Arguments

x	An ExpressionSet object or a gene expression data matrix or count matrix, rows refer to genes, columns to samples
group	Name or number of the phenoData column or a character vector or factor that contains required class assignments
pathways	A list of pathways in a form from graphite package or created by preparePathways()
type	Type of the input data, "MA" for microarray and "RNASeq" for RNA-Seq
preparePaths	Logical, by default the pathways are transformed with preparePathways(). Use FALSE, if you have done this transformation separately
norm.method	Character, the method to normalize RNAseq data. If NULL then TMM-normalization is performed. Possible values are: "TMM", "DESeq2", "rLog", "none"
test.method	Character, the method for differentiall expression analysis of RNAseq data. If NULL then "voomlimma" is used. Possible values are: "DESeq2", "voomlimma", "vstlimma", "edgeR". This analysis is needed only for the visualization.
test	Function implementing a statistical test comparing PCI scores between groups. It is employed as test(PCI~group)\$p.value, where PCI is a numeric vector of the same length as group
normalize	Logical, should data be normalized?

verbose Logical, if TRUE names of the pathways are printed as they are analysed
 both.directions, maxNodes, minEdges, commonTh, filterSPIA, convertTo, convertBy
 Arguments for the preparePathways()

Value

A list,
 res A data frame, rows refer to pathways. Columns contain: number of valid PCI-scores, median, min and max of the PCI scores for each group of samples, p-value of the test (`p.val`) and adjusted p-value (`p.adj`). If less than two nodes are present in the data, the function puts NA's in all columns.
 topo.sig NULL, it is preserved for the compatibility with other methods implemented in this package
 degtest A numeric vector of gene-level differential expression statistics

Author(s)

Ivana Ihnatova

References

Gao, S. and Wang, X. (2007) TAPPA: topological analysis of pathway phenotype association. *Bioinformatics*, 23, pages 3100-3102

See Also

[preparePathways](#)

Examples

```
if (require(DEGraph)) {
  data("Loi2008_DEGraphVignette")
  pathways<-pathways("hsapiens", "biocarta")[1:10]
  pathways<-lapply(pathways, function(p) as(p,"pathway"))
  TAPPA(exprLoi2008, classLoi2008, pathways, type="MA")
}

## Not run:
if (require(gageData)) {

  data(hnrnp.cnts)
  group<-c(rep("sample",4), rep("control",4))
  hnrnp.cnts<-hnrnp.cnts[rowSums(hnrnp.cnts)>0,]
  pathways<-pathways("hsapiens", "biocarta")[1:10]
  pathways<-lapply(pathways, function(p) as(p,"pathway"))
  TAPPA( hnrnp.cnts, group, pathways, type="RNASeq", norm.method="TMM")
}

## End(Not run)
```

TopologyGSA *Function to use TopologyGSA method on microarray or RNA-Seq data*

Description

TopologyGSA method uses graphical models to test the differential expression of a pathway. It also highlights pathway componenets involved in the deregulation.

Usage

```
TopologyGSA(x, group, pathways, type, preparePaths=TRUE, norm.method=NULL, test.method=NULL, method=
  both.directions=TRUE, maxNodes=150, minEdges=0, commonTh=2, filterSPIA=FALSE, convertTo="none", co
```

Arguments

x	An ExpressionSet object or a gene expression data matrix or count matrix, rows refer to genes, columns to samples
group	Name or number of the phenoData column or a character vector or factor that contains required class assignments
pathways	A list of pathways in a form from graphite package or created by preparePathways()
type	Type of the input data, "MA" for microarray and "RNASeq" for RNA-Seq
preparePaths	Logical, by default the pathways are transformed with preparePathways(). Use FALSE, if you have done this transformation separately
norm.method	Character, the method to normalize RNAseq data. If NULL then TMM-normalization is performed. Possible values are: "TMM", "DESeq2", "rLog", "none"
test.method	Character, the method for differentiaall expression analysis of RNAseq data. If NULL then "voomlimma" is used. Possible values are: "DESeq2", "voomlimma", "vstlimma", "edgeR". This analysis is needed only for the visualization.
method	Either "var" and "mean". Determine the type of test used by topologyGSA.
alpha	Numeric, threshold for statistical significance of variance test. It influences the method for the mean test
...	Other arguments to be passed to the method. See details for better explanation
both.directions, maxNodes, minEdges, commonTh, filterSPIA, convertTo, convertBy	Arguments for the preparePathways()

Details

The user can further specify for the mean test:

1. **perms** number of permutations of the test,
2. **paired**logical flag. If TRUE Hotelling test for paired samples is calculated and the test on the variances is not performed

Or for the variance test:

1. **variance** logical flag. If TRUE the estimates of the covariance matrices are included in the result.
2. **s1** First group covariance matrix estimation.
3. **s2** Second group covariance matrix estimation.

Value

A list

res a list with one entry for each successfully analyzed pathway

topo.sig if testCliques=TRUE, a list where each slot contains the pvalues and a list of cliques in one pathway. NULL otherwise

degtest A numeric vector of gene-level differential expression statistics

Author(s)

Ivana Ihnatova

References

Massa MS, Chiogna M, Romualdi C. Gene set analysis exploiting the topology of a pathway. *BMC System Biol.* 2010 Sep 1;4:121.

Examples

```
## Not run:
if (require(DEGraph)) {
  data("Loi2008_DEGraphVignette")
  pathways<-pathways("hsapiens", "biocarta")[1:10]
  pathways<-lapply(pathways, function(p) as(p,"pathway"))p<-biocarta[1:10]

  TopologyGSA(exprLoi2008, classLoi2008, pathways, type="MA", test="mean", alpha=0.05, perms=200)
}

if (require(gageData)) {

  data(hnrnp.cnts)
  group<-c(rep("sample",4), rep("control",4))
  hnrnp.cnts<-hnrnp.cnts[rowSums(hnrnp.cnts)>0,]
  pathways<-pathways("hsapiens", "biocarta")[1:10]
  pathways<-lapply(pathways, function(p) as(p,"pathway"))
  TopologyGSA(hnrnp.cnts, group,pathways, type="RNASeq",test="mean", alpha=0.05,
    nperm=200, norm.method="TMM")
}

## End(Not run)
```

Index

- *Topic **classes**
 - pathway-class, 15
- *Topic **htest**
 - Clipper, 4
 - DEGraph, 9
 - PRS, 18
 - PWEA, 20
 - SPIA, 24
 - TAPPA, 26
 - TopologyGSA, 28
- *Topic **manip**
 - AdjacencyMatrix2pathway, 3
 - convertIdentifiersByVector, 8
 - estimateCF, 11
 - graphNEL2pathway, 12
 - KEGG2pathway, 13
 - makeDefaultEdgeData, 14
 - preparePathways, 17
 - reduceGraph, 22
 - res, 23
- *Topic **package**
 - ToPASeq-package, 2
- *Topic **univar**
 - collectWeightsPRS, 6
- acc, pathway, character-method
(pathway-class), 15
- addEdge, character, character, pathway, numeric-method
(pathway-class), 15
- addNode, character, pathway, list-method
(pathway-class), 15
- AdjacencyMatrix2pathway, 3
- changeDirection (pathway-class), 15
- changeDirection, character, character, pathway, character-method
(pathway-class), 15
- changeInteraction (pathway-class), 15
- changeInteraction, character, character, pathway, character-method
(pathway-class), 15
- clearNode, character, pathway-method
(pathway-class), 15
- Clipper, 4
- collectWeightsPRS, 6
- collectWeightsSPIA (collectWeightsPRS),
6
- connComp, pathway-method
(pathway-class), 15
- convertIdentifiers, 8, 15
- convertIdentifiersByVector, 8
- DEGraph, 9
- degree, pathway, character-method
(pathway-class), 15
- degree, pathway, missing-method
(pathway-class), 15
- degtable (res), 23
- edgemode, pathway-method
(pathway-class), 15
- edgeNames, pathway-method
(pathway-class), 15
- edges, pathway, ANY-method
(pathway-class), 15
- edges, pathway, character-method
(pathway-class), 15
- estimateCF, 11
- graphNEL2pathway, 12
- intersection, pathway, pathway-method
(pathway-class), 15
- isAdjacent, pathway, character, character-method
(pathway-class), 15
- isConnected, pathway-method
(pathway-class), 15
- isDirected, pathway-method
(pathway-class), 15
- logRatios, pathway, pathway-method
(pathway-class), 15

KEGG2pathway, 13

makeDefaultEdgeData, 18

makeDefaultEdgeData
 (makeDefaultEdgeData), 14

makeDefaultEdgeData, 14

mostEdges, pathway-method
 (pathway-class), 15

nodes, pathway-method (pathway-class), 15

nodes<-, pathway, character-method
 (pathway-class), 15

numEdges, pathway-method
 (pathway-class), 15

numNodes, pathway-method
 (pathway-class), 15

numNoEdges, pathway-method
 (pathway-class), 15

pathway-class, 15

preparePathways, 6, 10, 17, 19, 21, 25, 27

prepareTIF, 21

prepareTIF (collectWeightsPRS), 6

PRS, 18

PWEA, 20

reduceGraph, 11, 22

removeEdge, character, character, pathway-method
 (pathway-class), 15

removeNode, character, pathway-method
 (pathway-class), 15

res, 23

show, pathway-method (pathway-class), 15

SPIA, 24

subGraph, character, pathway-method
 (pathway-class), 15

TAPPA, 26

ToPASeq (ToPASeq-package), 2

ToPASeq-package, 2

topo.sig (res), 23

TopologyGSA, 28

union, pathway, pathway-method
 (pathway-class), 15