

# How to Use pkgDepTools

Seth Falcon

May 15, 2022

## 1 Introduction

The `pkgDepTools` package provides tools for computing and analyzing dependency relationships among R packages. With it, you can build a graph-based representation of the dependencies among all packages in a list of CRAN-style package repositories. There are utilities for computing installation order of a given package and, if the `RCurl` package is available, estimating the download size required to install a given package and its dependencies.

This vignette demonstrates the basic features of the package.

## 2 Graph Basics

A graph consists of a set of nodes and a set of edges representing relationships between pairs of nodes. The relationships among the nodes of a graph are binary; either there is an edge between a pair of nodes or there is not. To model package dependencies using a graph, let the set of packages be the nodes of the graph with directed edges originating from a given package to each of its dependencies. Figure 1 shows a part of the Bioconductor dependency graph for the `Category` package. Since circular dependencies are not allowed, the resulting dependency graph will be a directed acyclic graph (DAG).

## 3 Building a Dependency Graph

```
> library("pkgDepTools")  
> library("Biobase")
```

```
> library("Rgraphviz")
```

The `makeDepGraph` function retrieves the meta data for all packages of a specified type (source, win.binary, or mac.binary) from each repository in a list of repository URLs and builds a *graphNEL*<sup>1</sup> instance representing the packages and their dependency relationships.

The function takes four arguments: 1) `repList` a character vector of CRAN-style package repository URLs; 2) `suggests.only` a logical value indicating whether the resulting graph should represent relations from the `Depends` field (`FALSE`, default) or the `Suggests` field (`TRUE`); 3) `type` a string indicating the type of packages to search for, the default is `getOption("pkgType")`; 4) `keep.builtin` which will keep packages that come with a standard R install in the dependency graph (the default is `FALSE`).

Here we use `makeDepGraph` to build dependency graphs of the BioC and CRAN packages. Each dependency graph is a *graphNEL* instance. The out-edges of a given node list its direct dependencies (as shown for package `annotate`). The node attribute “size” gives the size of the package in megabytes when the `dosize` argument is `TRUE` (this is the default). Obtaining the size of packages requires the `RCurl` package and can be time consuming for large repositories since a separate HTTP request must be made for each package. In the examples below, we set `dosize=FALSE` to speed the computations.

```
> library(BiocManager)
> biocUrl <- repositories()["BioCsoft"]
> biocDeps <- makeDepGraph(biocUrl, type="source", dosize=FALSE)
> biocDeps
```

A *graphNEL* graph with directed edges

Number of Nodes = 3344

Number of Edges = 18615

```
> edges(biocDeps)["annotate"]
```

```
$annotate
```

```
[1] "AnnotationDbi" "XML"          "Biobase"      "DBI"
[5] "xtable"        "BiocGenerics" "httr"
```

```
> ## if dosize=TRUE, size in MB is stored
> ## as a node attribute:
> ## nodeData(biocDeps, n="annotate", attr="size")
```

---

<sup>1</sup>See `help("graphNEL-class")`

## 4 Using the Dependency Graph

The dependencies of a given package can be visualized using the graph generated by `makeDepGraph` and the `Rgraphviz` package. The graph shown in Figure 1 was produced using the code shown below. The `acc` method from the `graph` package returns a vector of all nodes that are accessible from the given node. Here, it has been used to obtain the complete list of `Category`'s dependencies.

```
> categoryNodes <- c("Category",  
+                     names(acc(biocDeps, "Category")[[1]]))  
> categoryGraph <- subGraph(categoryNodes, biocDeps)  
> nn <- makeNodeAttrs(categoryGraph, shape="ellipse")  
> plot(categoryGraph, nodeAttrs=nn)
```

In R, there is no easy way to preview a given package's dependencies and estimate the amount of data that needs to be downloaded even though the `install.packages` function will search for and install package dependencies if you ask it to by specifying `dependencies=TRUE`. The `getInstallOrder` function provides such a "preview".

For computing installation order, it is useful to have a single graph representing the relationships among all packages in all available repositories. Below, we create such a graph combining all CRAN and Bioconductor packages.

```
> allDeps <- makeDepGraph(repositories(), type="source",  
+                          keep.builtin=TRUE, dosize=FALSE)  
>
```

Calling `getInstallOrder` for package `GOstats`, we see a listing of only those packages that need to be installed. Your results will be different based upon your installed packages.

```
> getInstallOrder("GOstats", allDeps)
```

```
$packages  
character(0)
```

```
$total.size  
numeric(0)
```

When `needed.only=FALSE`, the complete dependency list is returned regardless of what packages are currently installed.

```
> getInstallOrder("GOstats", allDeps, needed.only=FALSE)

$packages
  [1] "methods"          "utils"            "graphics"
  [4] "stats"            "BiocGenerics"     "Biobase"
  [7] "stats4"           "S4Vectors"        "IRanges"
 [10] "DBI"              "bit"              "bit64"
 [13] "rlang"            "glue"             "cli"
 [16] "vctrs"            "blob"             "fastmap"
 [19] "cachem"           "memoise"          "pkgconfig"
 [22] "Rcpp"             "plogr"             "RSQLite"
 [25] "curl"             "jsonlite"         "tools"
 [28] "mime"             "sys"              "askpass"
 [31] "openssl"          "R6"               "httr"
 [34] "png"              "zlibbioc"         "XVector"
 [37] "bitops"           "RCurl"            "GenomeInfoDbData"
 [40] "GenomeInfoDb"     "grDevices"        "crayon"
 [43] "Biostrings"       "KEGGREST"         "AnnotationDbi"
 [46] "grid"             "lattice"          "Matrix"
 [49] "graph"            "BH"               "RBGL"
 [52] "XML"              "xtable"           "annotate"
 [55] "GSEABase"         "splines"          "survival"
 [58] "genefilter"       "Category"         "GO.db"
 [61] "AnnotationForge"  "Rgraphviz"        "GOstats"

$total.size
[1] NA
```

The edge directions of the dependency graph can be reversed and the resulting graph used to determine the set of packages that make use of (even indirectly) a given package. For example, one might like to know which packages make use of the `methods` package. Here is one way to do that:

```
> allDepsOnMe <- reverseEdgeDirections(allDeps)
> usesMethods <- dijkstra.sp(allDepsOnMe, start="methods")$distance
> usesMethods <- usesMethods[is.finite(usesMethods)]
> length(usesMethods) - 1 ## don't count methods itself
```

```
[1] 17584
```

```
> table(usesMethods)
```

```
usesMethods
  0      1      2      3      4      5      6
1 5394 10917 1231   39    2    1
```

```
>
```

```
> toLatex(sessionInfo())
```

- R version 4.2.0 (2022-04-22), x86\_64-apple-darwin17.0
- Locale: C/en\_US.UTF-8/en\_US.UTF-8/C/en\_US.UTF-8/en\_US.UTF-8
- Running under: macOS Mojave 10.14.6
- Matrix products: default
- BLAS:  
/Library/Frameworks/R.framework/Versions/4.2/Resources/lib/libRblas.0.dylib
- LAPACK:  
/Library/Frameworks/R.framework/Versions/4.2/Resources/lib/libRlapack.dylib
- Base packages: base, datasets, grDevices, graphics, grid, methods,  
stats, utils
- Other packages: Biobase 2.56.0, BiocGenerics 0.42.0,  
BiocManager 1.30.17, RBGL 1.72.0, RCurl 1.98-1.6, Rgraphviz 2.40.0,  
graph 1.74.0, pkgDepTools 1.62.0
- Loaded via a namespace (and not attached): bitops 1.0-7,  
compiler 4.2.0, stats4 4.2.0, tools 4.2.0

