

# Package ‘MatrixGenerics’

April 10, 2023

**Title** S4 Generic Summary Statistic Functions that Operate on Matrix-Like Objects

**Description** S4 generic functions modeled after the 'matrixStats' API for alternative matrix implementations. Packages with alternative matrix implementation can depend on this package and implement the generic functions that are defined here for a useful set of row and column summary statistics. Other package developers can import this package and handle a different matrix implementations without worrying about incompatibilities.

**biocViews** Infrastructure, Software

**URL** <https://bioconductor.org/packages/MatrixGenerics>

**BugReports** <https://github.com/Bioconductor/MatrixGenerics/issues>

**Version** 1.10.0

**License** Artistic-2.0

**Encoding** UTF-8

**Depends** matrixStats (>= 0.60.1)

**Imports** methods

**Suggests** sparseMatrixStats, DelayedMatrixStats, SummarizedExperiment, testthat (>= 2.1.0), Matrix

**RoxygenNote** 7.2.0

**Roxygen** list(markdown = TRUE, old\_usage = TRUE)

**Collate** 'MatrixGenerics-package.R' 'rowAlls.R' 'rowAnyNAs.R' 'rowAnys.R' 'rowAvgPerColSet.R' 'rowCollapse.R' 'rowCounts.R' 'rowCummaxs.R' 'rowCummins.R' 'rowCumprods.R' 'rowCumsums.R' 'rowDiffs.R' 'rowIQRDiffs.R' 'rowIQRs.R' 'rowLogSumExps.R' 'rowMadDiffs.R' 'rowMads.R' 'rowMaxs.R' 'rowMeans2.R' 'rowMedians.R' 'rowMins.R' 'rowOrderStats.R' 'rowProds.R' 'rowQuantiles.R' 'rowRanges.R' 'rowRanks.R' 'rowSdDiffs.R' 'rowSds.R' 'rowSums2.R' 'rowTabulates.R' 'rowVarDiffs.R' 'rowVars.R' 'rowWeightedMads.R' 'rowWeightedMeans.R' 'rowWeightedMedians.R' 'rowWeightedSds.R' 'rowWeightedVars.R'

**git\_url** <https://git.bioconductor.org/packages/MatrixGenerics>  
**git\_branch** RELEASE\_3\_16  
**git\_last\_commit** 6d9d907  
**git\_last\_commit\_date** 2022-11-01  
**Date/Publication** 2023-04-10  
**Author** Constantin Ahlmann-Eltze [aut]  
 (<<https://orcid.org/0000-0002-3762-068X>>),  
 Peter Hickey [aut, cre] (<<https://orcid.org/0000-0002-8153-6258>>),  
 Hervé Pagès [aut]  
**Maintainer** Peter Hickey <peter.hickey@gmail.com>

## R topics documented:

MatrixGenerics-package	3
rowAlls	3
rowAnyNAs	5
rowAnys	6
rowAvsPerColSet	8
rowCollapse	9
rowCounts	11
rowCummaxs	12
rowCummins	14
rowCumprods	15
rowCumsums	17
rowDiffs	18
rowIQRDiffs	20
rowIQRs	21
rowLogSumExps	23
rowMadDiffs	24
rowMads	26
rowMaxs	27
rowMeans2	29
rowMedians	30
rowMins	32
rowOrderStats	33
rowProds	35
rowQuantiles	36
rowRanges	38
rowRanks	40
rowSdDiffs	42
rowSds	43
rowSums2	45
rowTabulates	47
rowVarDiffs	48
rowVars	50
rowWeightedMads	51

rowWeightedMeans . . . . .	53
rowWeightedMedians . . . . .	55
rowWeightedSds . . . . .	56
rowWeightedVars . . . . .	58

<b>Index</b>	<b>60</b>
--------------	-----------

---

MatrixGenerics-package

*The MatrixGenerics package*

---

## Description

The **MatrixGenerics** package defines S4 generic summary statistic functions that operate on matrix-Like objects.

---

rowAlls	<i>Check if all elements in a row (column) of a matrix-like object are equal to a value</i>
---------	---

---

## Description

Check if all elements in a row (column) of a matrix-like object are equal to a value.

## Usage

```
rowAlls(x, rows = NULL, cols = NULL, value = TRUE, na.rm = FALSE, ...,
        useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowAlls(x, rows = NULL,
        cols = NULL, value = TRUE, na.rm = FALSE, dim. = dim(x), ...,
        useNames = NA)
```

```
## S4 method for signature 'ANY'
rowAlls(x, rows = NULL, cols = NULL, value = TRUE,
        na.rm = FALSE, ..., useNames = NA)
```

```
colAlls(x, rows = NULL, cols = NULL, value = TRUE, na.rm = FALSE, ...,
        useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colAlls(x, rows = NULL,
        cols = NULL, value = TRUE, na.rm = FALSE, dim. = dim(x), ...,
        useNames = NA)
```

```
## S4 method for signature 'ANY'
colAlls(x, rows = NULL, cols = NULL, value = TRUE,
        na.rm = FALSE, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
value	The value to search for.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowAlls/matrixStats::colAlls`.

### Value

Returns a [logical vector](#) of length N (K).

### See Also

- `matrixStats::rowAlls()` and `matrixStats::colAlls()` which are used when the input is a [matrix](#) or [numeric](#) vector.
- For checks if *any* element is equal to a value, see `rowAnys()`.
- `base::all()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowAlls(mat)
colAlls(mat)
```

---

rowAnyNAs	<i>Check if any elements in a row (column) of a matrix-like object is missing</i>
-----------	---

---

### Description

Check if any elements in a row (column) of a matrix-like object is missing.

### Usage

```
rowAnyNAs(x, rows = NULL, cols = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowAnyNAs(x, rows = NULL, cols = NULL, ..., useNames = NA)

## S4 method for signature 'ANY'
rowAnyNAs(x, rows = NULL, cols = NULL, ..., useNames = NA)

colAnyNAs(x, rows = NULL, cols = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colAnyNAs(x, rows = NULL, cols = NULL, ..., useNames = NA)

## S4 method for signature 'ANY'
colAnyNAs(x, rows = NULL, cols = NULL, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.

### Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowAnyNAs / matrixStats::colAnyNAs`.

### Value

Returns a [logical vector](#) of length N (K).

**See Also**

- `matrixStats::rowAnyNAs()` and `matrixStats::colAnyNAs()` which are used when the input is a matrix or numeric vector.
- For checks if any element is equal to a value, see `rowAnys()`.
- `base::is.na()` and `base::any()`.

**Examples**

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowAnyNAs(mat)
colAnyNAs(mat)
```

---

rowAnys

*Check if any elements in a row (column) of a matrix-like object is equal to a value*

---

**Description**

Check if any elements in a row (column) of a matrix-like object is equal to a value.

**Usage**

```
rowAnys(x, rows = NULL, cols = NULL, value = TRUE, na.rm = FALSE, ...,
        useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowAnys(x, rows = NULL,
        cols = NULL, value = TRUE, na.rm = FALSE, dim. = dim(x), ...,
        useNames = NA)

## S4 method for signature 'ANY'
rowAnys(x, rows = NULL, cols = NULL, value = TRUE,
        na.rm = FALSE, ..., useNames = NA)

colAnys(x, rows = NULL, cols = NULL, value = TRUE, na.rm = FALSE, ...,
        useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colAnys(x, rows = NULL,
        cols = NULL, value = TRUE, na.rm = FALSE, dim. = dim(x), ...,
```

```

useNames = NA)

## S4 method for signature 'ANY'
colAnys(x, rows = NULL, cols = NULL, value = TRUE,
na.rm = FALSE, ..., useNames = NA)

```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
value	The value to search for.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowAnys/matrixStats::colAnys`.

### Value

Returns a [logical vector](#) of length N (K).

### See Also

- `matrixStats::rowAnys()` and `matrixStats::colAnys()` which are used when the input is a [matrix](#) or [numeric](#) vector.
- For checks if *all* elements are equal to a value, see `rowAlls()`.
- `base::any()`.

### Examples

```

mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowAnys(mat)
colAnys(mat)

```

---

rowAvsPerColSet	<i>Calculates for each row (column) a summary statistic for equally sized subsets of columns (rows)</i>
-----------------	---

---

### Description

Calculates for each row (column) a summary statistic for equally sized subsets of columns (rows).

### Usage

```
rowAvsPerColSet(X, W = NULL, rows = NULL, S, FUN = rowMeans, ...,
  na.rm = NA, tFUN = FALSE)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowAvsPerColSet(X, W = NULL,
  rows = NULL, S, FUN = rowMeans, ..., na.rm = NA, tFUN = FALSE)

## S4 method for signature 'ANY'
rowAvsPerColSet(X, W = NULL, rows = NULL, S,
  FUN = rowMeans, ..., na.rm = NA, tFUN = FALSE)

colAvsPerRowSet(X, W = NULL, cols = NULL, S, FUN = colMeans, ...,
  na.rm = NA, tFUN = FALSE)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colAvsPerRowSet(X, W = NULL,
  cols = NULL, S, FUN = colMeans, ..., na.rm = NA, tFUN = FALSE)

## S4 method for signature 'ANY'
colAvsPerRowSet(X, W = NULL, cols = NULL, S,
  FUN = colMeans, ..., na.rm = NA, tFUN = FALSE)
```

### Arguments

X	An NxM matrix-like object.
W	An optional numeric NxM matrix of weights.
rows, cols	A <a href="#">vector</a> indicating the subset (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
S	An <a href="#">integer</a> KxJ matrix that specifying the J subsets. Each column hold K column (row) indices for the corresponding subset. The range of values is [1, M] ([1,N]).
FUN	A row-by-row (column-by-column) summary statistic function. It is applied to to each column (row) subset of X that is specified by S.
...	Additional arguments passed to FUN.
na.rm	(logical) Argument passed to FUN() as <code>na.rm = na.rm</code> . If <code>NA</code> (default), then <code>na.rm = TRUE</code> is used if X or S holds missing values, otherwise <code>na.rm = FALSE</code> .
tFUN	If <code>TRUE</code> , X is transposed before it is passed to FUN.

**Details**

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowAvgPerColSet` / `matrixStats::colAvgPerRowSet`.

**Value**

Returns a numeric  $J \times N$  ( $M \times J$ ) matrix.

**See Also**

- `matrixStats::rowAvgPerColSet()` and `matrixStats::colAvgPerRowSet()` which are used when the input is a matrix or numeric vector.

**Examples**

```
mat <- matrix(rnorm(20), nrow = 5, ncol = 4)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0
```

```
print(mat)
```

```
S <- matrix(1:ncol(mat), ncol = 2)
print(S)
```

```
rowAvgPerColSet(mat, S = S, FUN = rowMeans)
rowAvgPerColSet(mat, S = S, FUN = rowVars)
```

---

rowCollapse

---

*Extract one cell from each row (column) of a matrix-like object*


---

**Description**

Extract one cell from each row (column) of a matrix-like object.

**Usage**

```
rowCollapse(x, idxs, rows = NULL, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowCollapse(x, idxs, rows = NULL, dim. = dim(x), ..., useNames = NA)
```

```
## S4 method for signature 'ANY'
rowCollapse(x, idxs, rows = NULL, ..., useNames = NA)
```

```
colCollapse(x, idxs = idxs, cols = NULL, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colCollapse(x, idxs, cols = NULL, dim. = dim(x), ..., useNames = NA)
```

```
## S4 method for signature 'ANY'
colCollapse(x, idxs = idxs, cols = NULL, ..., useNames = NA)
```

### Arguments

<code>x</code>	An <code>NxK</code> matrix-like object.
<code>idxs</code>	An index <a href="#">vector</a> with the position to extract. It is recycled to match the number of rows (column)
<code>rows, cols</code>	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.
<code>dim.</code>	An <a href="#">integer vector</a> of length two specifying the dimension of <code>x</code> , essential when <code>x</code> is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for `x` of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowCollapse` / `matrixStats::colCollapse`.

### Value

Returns a [numeric vector](#) of length `N` (`K`).

### See Also

- `matrixStats::rowCollapse()` and `matrixStats::colCollapse()` which are used when the input is a [matrix](#) or [numeric](#) vector.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowCollapse(mat, idxs = 2)
rowCollapse(mat, idxs = c(1,1,2,3,2))

colCollapse (mat, idxs = 4)
```

---

rowCounts	<i>Count how often an element in a row (column) of a matrix-like object is equal to a value</i>
-----------	---

---

## Description

Count how often an element in a row (column) of a matrix-like object is equal to a value.

## Usage

```
rowCounts(x, rows = NULL, cols = NULL, value = TRUE, na.rm = FALSE,
  ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowCounts(x, rows = NULL,
  cols = NULL, value = TRUE, na.rm = FALSE, dim. = dim(x), ...,
  useNames = NA)
```

```
## S4 method for signature 'ANY'
rowCounts(x, rows = NULL, cols = NULL, value = TRUE,
  na.rm = FALSE, ..., useNames = NA)
```

```
colCounts(x, rows = NULL, cols = NULL, value = TRUE, na.rm = FALSE,
  ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colCounts(x, rows = NULL,
  cols = NULL, value = TRUE, na.rm = FALSE, dim. = dim(x), ...,
  useNames = NA)
```

```
## S4 method for signature 'ANY'
colCounts(x, rows = NULL, cols = NULL, value = TRUE,
  na.rm = FALSE, ..., useNames = NA)
```

## Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
value	The value to search for.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.

`dim.` An **integer vector** of length two specifying the dimension of `x`, essential when `x` is a **numeric** vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for `x` of type **matrix**, **array**, or **numeric** call `matrixStats::rowCounts` / `matrixStats::colCounts`.

### Value

Returns a **integer vector** of length `N` (`K`).

### See Also

- `matrixStats::rowCounts()` and `matrixStats::colCounts()` which are used when the input is a **matrix** or **numeric** vector.
- For checks if any element is equal to a value, see `rowAnys()`. To check if all elements are equal, see `rowAlls()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowCounts(mat)
colCounts(mat)

rowCounts(mat, value = 0)
colCounts(mat, value = Inf, na.rm = TRUE)
```

---

rowCummaxs	<i>Calculates the cumulative maxima for each row (column) of a matrix-like object</i>
------------	---

---

### Description

Calculates the cumulative maxima for each row (column) of a matrix-like object.

### Usage

```
rowCummaxs(x, rows = NULL, cols = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowCummaxs(x, rows = NULL, cols = NULL, dim. = dim(x), ..., useNames = NA)
```

```
## S4 method for signature 'ANY'
rowCummaxs(x, rows = NULL, cols = NULL, ..., useNames = NA)

colCummaxs(x, rows = NULL, cols = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colCummaxs(x, rows = NULL, cols = NULL, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
colCummaxs(x, rows = NULL, cols = NULL, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowCummaxs / matrixStats::colCummaxs`.

### Value

Returns a [numeric matrix](#) with the same dimensions as x.

### See Also

- `matrixStats::rowCummaxs()` and `matrixStats::colCummaxs()` which are used when the input is a matrix or numeric vector.
- For single maximum estimates, see `rowMaxs()`.
- `base::cummax()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0
```

```
print(mat)

rowCummaxs(mat)
colCummaxs(mat)
```

---

rowCummins	<i>Calculates the cumulative minima for each row (column) of a matrix-like object</i>
------------	---

---

## Description

Calculates the cumulative minima for each row (column) of a matrix-like object.

## Usage

```
rowCummins(x, rows = NULL, cols = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowCummins(x, rows = NULL, cols = NULL, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
rowCummins(x, rows = NULL, cols = NULL, ..., useNames = NA)

colCummins(x, rows = NULL, cols = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colCummins(x, rows = NULL, cols = NULL, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
colCummins(x, rows = NULL, cols = NULL, ..., useNames = NA)
```

## Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

**Details**

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowCummins` / `matrixStats::colCummins`.

**Value**

Returns a `numeric matrix` with the same dimensions as `x`.

**See Also**

- `matrixStats::rowCummins()` and `matrixStats::colCummins()` which are used when the input is a `matrix` or `numeric` vector.
- For single minimum estimates, see `rowMins()`.
- `base::cummin()`.

**Examples**

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowCummins(mat)
colCummins(mat)
```

---

rowCumprods	<i>Calculates the cumulative product for each row (column) of a matrix-like object</i>
-------------	--

---

**Description**

Calculates the cumulative product for each row (column) of a matrix-like object.

**Usage**

```
rowCumprods(x, rows = NULL, cols = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowCumprods(x, rows = NULL, cols = NULL, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
rowCumprods(x, rows = NULL, cols = NULL, ..., useNames = NA)

colCumprods(x, rows = NULL, cols = NULL, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colCumprods(x, rows = NULL, cols = NULL, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
colCumprods(x, rows = NULL, cols = NULL, ..., useNames = NA)
```

### Arguments

<code>x</code>	An <code>NxK</code> matrix-like object.
<code>rows, cols</code>	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.
<code>dim.</code>	An <a href="#">integer vector</a> of length two specifying the dimension of <code>x</code> , essential when <code>x</code> is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for `x` of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowCumprods / matrixStats::colCumprods`.

### Value

Returns a [numeric matrix](#) with the same dimensions as `x`.

### See Also

- `matrixStats::rowCumprods()` and `matrixStats::colCumprods()` which are used when the input is a matrix or numeric vector.
- `base::cumprod()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowCumprods(mat)
colCumprods(mat)
```

---

rowCumsums	<i>Calculates the cumulative sum for each row (column) of a matrix-like object</i>
------------	--

---

### Description

Calculates the cumulative sum for each row (column) of a matrix-like object.

### Usage

```
rowCumsums(x, rows = NULL, cols = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowCumsums(x, rows = NULL, cols = NULL, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
rowCumsums(x, rows = NULL, cols = NULL, ..., useNames = NA)

colCumsums(x, rows = NULL, cols = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colCumsums(x, rows = NULL, cols = NULL, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
colCumsums(x, rows = NULL, cols = NULL, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowCumsums / matrixStats::colCumsums`.

### Value

Returns a [numeric matrix](#) with the same dimensions as x.

**See Also**

- `matrixStats::rowCumsums()` and `matrixStats::colCumsums()` which are used when the input is a matrix or numeric vector.
- `base::cumsum()`.

**Examples**

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowCumsums(mat)
colCumsums(mat)
```

---

rowDiffs

*Calculates the difference between each element of a row (column) of a matrix-like object*

---

**Description**

Calculates the difference between each element of a row (column) of a matrix-like object.

**Usage**

```
rowDiffs(x, rows = NULL, cols = NULL, lag = 1L, differences = 1L, ...,
         useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowDiffs(x, rows = NULL,
         cols = NULL, lag = 1L, differences = 1L, dim. = dim(x), ...,
         useNames = NA)

## S4 method for signature 'ANY'
rowDiffs(x, rows = NULL, cols = NULL, lag = 1L,
         differences = 1L, ..., useNames = NA)

colDiffs(x, rows = NULL, cols = NULL, lag = 1L, differences = 1L, ...,
         useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colDiffs(x, rows = NULL,
         cols = NULL, lag = 1L, differences = 1L, dim. = dim(x), ...,
         useNames = NA)
```

```
## S4 method for signature 'ANY'
colDiffs(x, rows = NULL, cols = NULL, lag = 1L,
         differences = 1L, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
lag	An integer specifying the lag.
differences	An integer specifying the order of difference.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowDiffs/matrixStats::colDiffs`.

### Value

Returns a [numeric matrix](#) with one column (row) less than x:  $Nx(K - 1)$  or  $(N - 1)xK$ .

### See Also

- `matrixStats::rowDiffs()` and `matrixStats::colDiffs()` which are used when the input is a [matrix](#) or [numeric](#) vector.
- `base::diff()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowDiffs(mat)
colDiffs(mat)
```

---

rowIQRDiffs	<i>Calculates the interquartile range of the difference between each element of a row (column) of a matrix-like object</i>
-------------	--

---

### Description

Calculates the interquartile range of the difference between each element of a row (column) of a matrix-like object.

### Usage

```
rowIQRDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE, diff = 1L,
            trim = 0, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowIQRDiffs(x, rows = NULL,
            cols = NULL, na.rm = FALSE, diff = 1L, trim = 0, ...,
            useNames = NA)
```

```
## S4 method for signature 'ANY'
rowIQRDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE,
            diff = 1L, trim = 0, ..., useNames = NA)
```

```
colIQRDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE, diff = 1L,
            trim = 0, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colIQRDiffs(x, rows = NULL,
            cols = NULL, na.rm = FALSE, diff = 1L, trim = 0, ...,
            useNames = NA)
```

```
## S4 method for signature 'ANY'
colIQRDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE,
            diff = 1L, trim = 0, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
diff	An integer specifying the order of difference.
trim	A double in $[0, 1/2]$ specifying the fraction of observations to be trimmed from each end of (sorted) x before estimation.
...	Additional arguments passed to specific methods.

`useNames` If `NA`, the default behavior of the function about naming support is remained. If `FALSE`, no naming support is done. Else if `TRUE`, names attributes of result are set.

### Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowIQRDiffs / matrixStats::colIQRDiffs`.

### Value

Returns a `numeric vector` of length `N (K)`.

### See Also

- `matrixStats::rowIQRDiffs()` and `matrixStats::colIQRDiffs()` which are used when the input is a `matrix` or `numeric vector`.
- For the direct interquartile range see also `rowIQRs`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowIQRDiffs(mat)
colIQRDiffs(mat)
```

---

rowIQRs	<i>Calculates the interquartile range for each row (column) of a matrix-like object</i>
---------	---

---

### Description

Calculates the interquartile range for each row (column) of a matrix-like object.

### Usage

```
rowIQRs(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowIQRs(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'ANY'
```

```

rowIQRs(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

colIQRs(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colIQRs(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'ANY'
colIQRs(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

```

### Arguments

<code>x</code>	An $N \times K$ matrix-like object.
<code>rows, cols</code>	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>na.rm</code>	If <code>TRUE</code> , <code>NA</code> s are excluded first, otherwise not.
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.

### Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowIQRs/matrixStats::colIQRs`.

### Value

Returns a [numeric vector](#) of length  $N$  ( $K$ ).

### See Also

- `matrixStats::rowIQRs()` and `matrixStats::colIQRs()` which are used when the input is a `matrix` or `numeric` vector.
- For a non-robust analog, see `rowSds()`. For a more robust version see `rowMads()`
- `stats::IQR()`.

### Examples

```

mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowIQRs(mat)
colIQRs(mat)

```

---

rowLogSumExps	<i>Accurately calculates the logarithm of the sum of exponentials for each row (column) of a matrix-like object</i>
---------------	---

---

### Description

Accurately calculates the logarithm of the sum of exponentials for each row (column) of a matrix-like object.

### Usage

```
rowLogSumExps(lx, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowLogSumExps(lx,
  rows = NULL, cols = NULL, na.rm = FALSE, dim. = dim(lx), ...,
  useNames = NA)

## S4 method for signature 'ANY'
rowLogSumExps(lx, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

colLogSumExps(lx, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colLogSumExps(lx,
  rows = NULL, cols = NULL, na.rm = FALSE, dim. = dim(lx), ...,
  useNames = NA)

## S4 method for signature 'ANY'
colLogSumExps(lx, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)
```

### Arguments

lx	An NxK matrix-like object. Typically lx are log(x) values.
rows, cols	A <a href="#">vector</a> indicating the subset (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

**Details**

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowLogSumExps / matrixStats::colLogSumExps`.

**Value**

Returns a `numeric vector` of length `N (K)`.

**See Also**

- `matrixStats::rowLogSumExps()` and `matrixStats::colLogSumExps()` which are used when the input is a `matrix` or `numeric vector`.
- `rowSums2()`

**Examples**

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowLogSumExps(mat)
colLogSumExps(mat)
```

---

rowMadDiffs

*Calculates the mean absolute deviation of the difference between each element of a row (column) of a matrix-like object*

---

**Description**

Calculates the mean absolute deviation of the difference between each element of a row (column) of a matrix-like object.

**Usage**

```
rowMadDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE, diff = 1L,
  trim = 0, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowMadDiffs(x, rows = NULL,
  cols = NULL, na.rm = FALSE, diff = 1L, trim = 0, ...,
  useNames = NA)

## S4 method for signature 'ANY'
rowMadDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE,
```

```

diff = 1L, trim = 0, ..., useNames = NA)

colMadDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE, diff = 1L,
  trim = 0, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colMadDiffs(x, rows = NULL,
  cols = NULL, na.rm = FALSE, diff = 1L, trim = 0, ...,
  useNames = NA)

## S4 method for signature 'ANY'
colMadDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE,
  diff = 1L, trim = 0, ..., useNames = NA)

```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
diff	An integer specifying the order of difference.
trim	A double in [0,1/2] specifying the fraction of observations to be trimmed from each end of (sorted) x before estimation.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.

### Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowMadDiffs / matrixStats::colMadDiffs`.

### Value

Returns a [numeric vector](#) of length N (K).

### See Also

- `matrixStats::rowMadDiffs()` and `matrixStats::colMadDiffs()` which are used when the input is a matrix or numeric vector.

### Examples

```

mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

```

```
print(mat)

rowMadDiffs(mat)
colMadDiffs(mat)
```

---

rowMads	<i>Calculates the median absolute deviation for each row (column) of a matrix-like object</i>
---------	---

---

### Description

Calculates the median absolute deviation for each row (column) of a matrix-like object.

### Usage

```
rowMads(x, rows = NULL, cols = NULL, center = NULL, constant = 1.4826,
        na.rm = FALSE, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowMads(x, rows = NULL,
        cols = NULL, center = NULL, constant = 1.4826, na.rm = FALSE,
        dim. = dim(x), ..., useNames = NA)
```

```
## S4 method for signature 'ANY'
rowMads(x, rows = NULL, cols = NULL, center = NULL,
        constant = 1.4826, na.rm = FALSE, ..., useNames = NA)
```

```
colMads(x, rows = NULL, cols = NULL, center = NULL, constant = 1.4826,
        na.rm = FALSE, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colMads(x, rows = NULL,
        cols = NULL, center = NULL, constant = 1.4826, na.rm = FALSE,
        dim. = dim(x), ..., useNames = NA)
```

```
## S4 method for signature 'ANY'
colMads(x, rows = NULL, cols = NULL, center = NULL,
        constant = 1.4826, na.rm = FALSE, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
center	(optional) the center, defaults to the row means

constant	A scale factor. See <code>stats::mad()</code> for details.
na.rm	If <code>TRUE</code> , <code>NA</code> s are excluded first, otherwise not.
...	Additional arguments passed to specific methods.
useNames	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.
dim.	An <code>integer vector</code> of length two specifying the dimension of <code>x</code> , essential when <code>x</code> is a <code>numeric</code> vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowMads` / `matrixStats::colMads`.

### Value

Returns a `numeric vector` of length `N (K)`.

### See Also

- `matrixStats::rowMads()` and `matrixStats::colMads()` which are used when the input is a `matrix` or `numeric` vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- For non-robust standard deviation estimates, see `rowSds()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowMads(mat)
colMads(mat)
```

---

rowMaxs

*Calculates the maximum for each row (column) of a matrix-like object*

---

### Description

Calculates the maximum for each row (column) of a matrix-like object.

**Usage**

```

rowMaxs(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowMaxs(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
rowMaxs(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

colMaxs(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colMaxs(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
colMaxs(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

```

**Arguments**

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

**Details**

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowMaxs` / `matrixStats::colMaxs`.

**Value**

Returns a [numeric vector](#) of length N (K).

**See Also**

- `matrixStats::rowMaxs()` and `matrixStats::colMaxs()` which are used when the input is a [matrix](#) or [numeric](#) vector.
- For min estimates, see `rowMins()`.

**Examples**

```

mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowMaxs(mat)
colMaxs(mat)

```

---

rowMeans2

*Calculates the mean for each row (column) of a matrix-like object*


---

**Description**

Calculates the mean for each row (column) of a matrix-like object.

**Usage**

```

rowMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowMeans2(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
rowMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

colMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colMeans2(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
colMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

```

**Arguments**

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
...	Additional arguments passed to specific methods.

useNames	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.
dim.	An <code>integer vector</code> of length two specifying the dimension of <code>x</code> , essential when <code>x</code> is a <code>numeric</code> vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowMeans2/matrixStats::colMeans2`.

### Value

Returns a `numeric vector` of length `N (K)`.

### See Also

- `matrixStats::rowMeans2()` and `matrixStats::colMeans2()` which are used when the input is a `matrix` or `numeric` vector.
- See also `rowMeans()` for the corresponding function in base R.
- For variance estimates, see `rowVars()`.
- See also the base R version `base::rowMeans()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowMeans2(mat)
colMeans2(mat)
```

---

rowMedians

*Calculates the median for each row (column) of a matrix-like object*

---

### Description

Calculates the median for each row (column) of a matrix-like object.

**Usage**

```

rowMedians(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowMedians(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
rowMedians(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

colMedians(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colMedians(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
colMedians(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

```

**Arguments**

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

**Details**

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowMedians` / `matrixStats::colMedians`.

**Value**

Returns a [numeric vector](#) of length N (K).

**See Also**

- `matrixStats::rowMedians()` and `matrixStats::colMedians()` which are used when the input is a [matrix](#) or [numeric](#) vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.

**Examples**

```

mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowMedians(mat)
colMedians(mat)

```

rowMins

*Calculates the minimum for each row (column) of a matrix-like object***Description**

Calculates the minimum for each row (column) of a matrix-like object.

**Usage**

```

rowMins(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowMins(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
rowMins(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

colMins(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colMins(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
colMins(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

```

**Arguments**

<code>x</code>	An NxK matrix-like object.
<code>rows, cols</code>	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
<code>na.rm</code>	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
<code>...</code>	Additional arguments passed to specific methods.

- useNames      If `NA`, the default behavior of the function about naming support is remained. If `FALSE`, no naming support is done. Else if `TRUE`, names attributes of result are set.
- dim.            An `integer vector` of length two specifying the dimension of `x`, essential when `x` is a `numeric` vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowMins/matrixStats::colMins`.

### Value

Returns a `numeric vector` of length `N (K)`.

### See Also

- `matrixStats::rowMins()` and `matrixStats::colMins()` which are used when the input is a `matrix` or `numeric` vector.
- For max estimates, see `rowMaxs()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowMins(mat)
colMins(mat)
```

---

rowOrderStats	<i>Calculates an order statistic for each row (column) of a matrix-like object</i>
---------------	--

---

### Description

Calculates an order statistic for each row (column) of a matrix-like object.

**Usage**

```

rowOrderStats(x, rows = NULL, cols = NULL, which, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowOrderStats(x, rows = NULL,
  cols = NULL, which, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
rowOrderStats(x, rows = NULL, cols = NULL, which, ..., useNames = NA)

colOrderStats(x, rows = NULL, cols = NULL, which, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colOrderStats(x, rows = NULL,
  cols = NULL, which, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
colOrderStats(x, rows = NULL, cols = NULL, which, ..., useNames = NA)

```

**Arguments**

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
which	An integer index in [1,K] ([1,N]) indicating which order statistic to be returned
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

**Details**

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowOrderStats` / `matrixStats::colOrderStats`.

**Value**

Returns a [numeric vector](#) of length N (K).

**See Also**

- `matrixStats::rowOrderStats()` and `matrixStats::colOrderStats()` which are used when the input is a [matrix](#) or [numeric](#) vector.

**Examples**

```

mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- 2
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowOrderStats(mat, which = 1)
colOrderStats(mat, which = 3)

```

---

rowProds	<i>Calculates the product for each row (column) of a matrix-like object</i>
----------	---

---

**Description**

Calculates the product for each row (column) of a matrix-like object.

**Usage**

```

rowProds(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowProds(x, rows = NULL,
  cols = NULL, na.rm = FALSE, method = c("direct", "expSumLog"), ...,
  useNames = NA)

## S4 method for signature 'ANY'
rowProds(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

colProds(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colProds(x, rows = NULL,
  cols = NULL, na.rm = FALSE, method = c("direct", "expSumLog"), ...,
  useNames = NA)

## S4 method for signature 'ANY'
colProds(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

```

**Arguments**

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.

...	Additional arguments passed to specific methods.
useNames	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.
method	A character vector of length one that specifies the how the product is calculated. Note, that this is not a generic argument and not all implementation have to provide it.

### Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowProds` / `matrixStats::colProds`.

### Value

Returns a `numeric vector` of length `N (K)`.

### See Also

- `matrixStats::rowProds()` and `matrixStats::colProds()` which are used when the input is a `matrix` or `numeric vector`.
- For sums across rows (columns), see `rowSums2()` (`colSums2()`)
- `base::prod()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowProds(mat)
colProds(mat)
```

---

rowQuantiles

*Calculates quantiles for each row (column) of a matrix-like object*

---

### Description

Calculates quantiles for each row (column) of a matrix-like object.

**Usage**

```

rowQuantiles(x, rows = NULL, cols = NULL, probs = seq(from = 0, to = 1,
  by = 0.25), na.rm = FALSE, type = 7L, ..., useNames = NA,
  drop = TRUE)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowQuantiles(x, rows = NULL,
  cols = NULL, probs = seq(from = 0, to = 1, by = 0.25), na.rm = FALSE,
  type = 7L, ..., useNames = NA, drop = TRUE)

## S4 method for signature 'ANY'
rowQuantiles(x, rows = NULL, cols = NULL,
  probs = seq(from = 0, to = 1, by = 0.25), na.rm = FALSE, type = 7L,
  ..., useNames = NA, drop = TRUE)

colQuantiles(x, rows = NULL, cols = NULL, probs = seq(from = 0, to = 1,
  by = 0.25), na.rm = FALSE, type = 7L, ..., useNames = NA,
  drop = TRUE)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colQuantiles(x, rows = NULL,
  cols = NULL, probs = seq(from = 0, to = 1, by = 0.25), na.rm = FALSE,
  type = 7L, ..., useNames = NA, drop = TRUE)

## S4 method for signature 'ANY'
colQuantiles(x, rows = NULL, cols = NULL,
  probs = seq(from = 0, to = 1, by = 0.25), na.rm = FALSE, type = 7L,
  ..., useNames = NA, drop = TRUE)

```

**Arguments**

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
probs	A numeric vector of J probabilities in [0, 1].
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
type	An integer specifying the type of estimator. See <code>stats::quantile()</code> for more details.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
drop	If <a href="#">TRUE</a> a vector is returned if $J == 1$ .

**Details**

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowQuantiles` / `matrixStats::colQuantiles`.

**Value**

a `numeric`  $N \times J$  ( $K \times J$ ) `matrix`, where  $N$  ( $K$ ) is the number of rows (columns) for which the  $J$  values are calculated.

**See Also**

- `matrixStats::rowQuantiles()` and `matrixStats::colQuantiles()` which are used when the input is a `matrix` or `numeric` vector.
- `stats::quantile`

**Examples**

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowQuantiles(mat)
colQuantiles(mat)
```

---

rowRanges	<i>Calculates the minimum and maximum for each row (column) of a matrix-like object</i>
-----------	---

---

**Description**

Calculates the minimum and maximum for each row (column) of a matrix-like object.

**Usage**

```
rowRanges(x, ...)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowRanges(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
rowRanges(x, ...)

colRanges(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colRanges(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
colRanges(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
...	Additional arguments passed to specific methods.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.

### Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowRanges` / `matrixStats::colRanges`.

### Value

a [numeric](#) Nx2 (Kx2) [matrix](#), where N (K) is the number of rows (columns) for which the ranges are calculated.

### Note

Unfortunately for the argument list of the `rowRanges()` generic function we cannot follow the scheme used for the other row/column matrix summarization generic functions. This is because we need to be compatible with the historic `rowRanges()` getter for [RangedSummarizedExperiment](#) objects. See `?SummarizedExperiment::rowRanges`.

### See Also

- `matrixStats::rowRanges()` and `matrixStats::colRanges()` which are used when the input is a matrix or numeric vector.
- For max estimates, see `rowMaxs()`.
- For min estimates, see `rowMins()`.
- `base::range()`.

**Examples**

```

mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowRanges(mat)
colRanges(mat)

```

---

rowRanks	<i>Calculates the rank of the elements for each row (column) of a matrix-like object</i>
----------	--

---

**Description**

Calculates the rank of the elements for each row (column) of a matrix-like object.

**Usage**

```

rowRanks(x, rows = NULL, cols = NULL, ties.method = c("max", "average"),
  ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowRanks(x, rows = NULL,
  cols = NULL, ties.method = c("max", "average", "first", "last", "random",
  "max", "min", "dense"), dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
rowRanks(x, rows = NULL, cols = NULL,
  ties.method = c("max", "average"), ..., useNames = NA)

colRanks(x, rows = NULL, cols = NULL, ties.method = c("max", "average"),
  ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colRanks(x, rows = NULL,
  cols = NULL, ties.method = c("max", "average", "first", "last", "random",
  "max", "min", "dense"), dim. = dim(x), preserveShape = FALSE, ...,
  useNames = NA)

## S4 method for signature 'ANY'
colRanks(x, rows = NULL, cols = NULL,
  ties.method = c("max", "average"), ..., useNames = NA)

```

**Arguments**

<code>x</code>	An <code>NxK</code> matrix-like object.
<code>rows, cols</code>	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>ties.method</code>	A character string specifying how ties are treated. Note that the default specifies fewer options than the original <code>matrixStats</code> package.
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.
<code>dim.</code>	An <a href="#">integer vector</a> of length two specifying the dimension of <code>x</code> , essential when <code>x</code> is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.
<code>preserveShape</code>	If <code>TRUE</code> the output matrix has the same shape as the input <code>x</code> . Note, that this is not a generic argument and not all implementation of this function have to provide it.

**Details**

The S4 methods for `x` of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowRanks / matrixStats::colRanks`.

The `matrixStats::rowRanks()` function can handle a lot of different values for the `ties.method` argument. Users of the generic function should however only rely on `max` and `average` because the other ones are not guaranteed to be implemented:

`max` for values with identical values the maximum rank is returned

`average` for values with identical values the average of the ranks they cover is returned. Note, that in this case the return value is of type `numeric`.

**Value**

a matrix of type [integer](#) is returned unless `ties.method = "average"`. It has dimensions `N x J` (`K x J`) [matrix](#), where `N` (`K`) is the number of rows (columns) of the input `x`.

**See Also**

- `matrixStats::rowRanks()` and `matrixStats::colRanks()` which are used when the input is a `matrix` or `numeric` vector.
- [base::rank](#)

**Examples**

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)
```

```
rowRanks(mat)
colRanks(mat)
```

---

rowSdDiffs	<i>Calculates the standard deviation of the difference between each element of a row (column) of a matrix-like object</i>
------------	---

---

### Description

Calculates the standard deviation of the difference between each element of a row (column) of a matrix-like object.

### Usage

```
rowSdDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE, diff = 1L,
           trim = 0, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowSdDiffs(x, rows = NULL,
           cols = NULL, na.rm = FALSE, diff = 1L, trim = 0, ...,
           useNames = NA)
```

```
## S4 method for signature 'ANY'
rowSdDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE,
           diff = 1L, trim = 0, ..., useNames = NA)
```

```
colSdDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE, diff = 1L,
           trim = 0, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colSdDiffs(x, rows = NULL,
           cols = NULL, na.rm = FALSE, diff = 1L, trim = 0, ...,
           useNames = NA)
```

```
## S4 method for signature 'ANY'
colSdDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE,
           diff = 1L, trim = 0, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
diff	An integer specifying the order of difference.

trim	A double in [0,1/2] specifying the fraction of observations to be trimmed from each end of (sorted) x before estimation.
...	Additional arguments passed to specific methods.
useNames	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.

### Details

The S4 methods for x of type `matrix`, `array`, or `numeric` call `matrixStats::rowSdDiffs / matrixStats::colSdDiffs`.

### Value

Returns a `numeric vector` of length N (K).

### See Also

- `matrixStats::rowSdDiffs()` and `matrixStats::colSdDiffs()` which are used when the input is a matrix or numeric vector.
- for the direct standard deviation see `rowSds()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowSdDiffs(mat)
colSdDiffs(mat)
```

---

rowSds	<i>Calculates the standard deviation for each row (column) of a matrix-like object</i>
--------	--

---

### Description

Calculates the standard deviation for each row (column) of a matrix-like object.

**Usage**

```

rowSds(x, rows = NULL, cols = NULL, na.rm = FALSE, center = NULL, ...,
       useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowSds(x, rows = NULL,
       cols = NULL, na.rm = FALSE, center = NULL, dim. = dim(x), ...,
       useNames = NA)

## S4 method for signature 'ANY'
rowSds(x, rows = NULL, cols = NULL, na.rm = FALSE,
       center = NULL, ..., useNames = NA)

colSds(x, rows = NULL, cols = NULL, na.rm = FALSE, center = NULL, ...,
       useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colSds(x, rows = NULL,
       cols = NULL, na.rm = FALSE, center = NULL, dim. = dim(x), ...,
       useNames = NA)

## S4 method for signature 'ANY'
colSds(x, rows = NULL, cols = NULL, na.rm = FALSE,
       center = NULL, ..., useNames = NA)

```

**Arguments**

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
center	(optional) the center, defaults to the row means
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric vector</a> . Note, that this is not a generic argument and not all methods need provide it.

**Details**

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowSds/matrixStats::colSds`.

**Value**

Returns a [numeric vector](#) of length N (K).

**See Also**

- `matrixStats::rowSds()` and `matrixStats::colSds()` which are used when the input is a matrix or numeric vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- For variance estimates, see `rowVars()`.

**Examples**

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowSds(mat)
colSds(mat)
```

---

rowSums2

*Calculates the sum for each row (column) of a matrix-like object*


---

**Description**

Calculates the sum for each row (column) of a matrix-like object.

**Usage**

```
rowSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowSums2(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
rowSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

colSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colSums2(x, rows = NULL,
  cols = NULL, na.rm = FALSE, dim. = dim(x), ..., useNames = NA)

## S4 method for signature 'ANY'
colSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.
dim.	An <a href="#">integer vector</a> of length two specifying the dimension of x, essential when x is a <a href="#">numeric</a> vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowSums2/matrixStats::colSums2`.

### Value

Returns a [numeric vector](#) of length N (K).

### See Also

- `matrixStats::rowSums2()` and `matrixStats::colSums2()` which are used when the input is a matrix or numeric vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- `base::sum()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowSums2(mat)
colSums2(mat)
```

---

rowTabulates	<i>Tabulates the values in a matrix-like object by row (column)</i>
--------------	---

---

## Description

Tabulates the values in a matrix-like object by row (column).

## Usage

```
rowTabulates(x, rows = NULL, cols = NULL, values = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowTabulates(x, rows = NULL, cols = NULL, values = NULL, ..., useNames = NA)

## S4 method for signature 'ANY'
rowTabulates(x, rows = NULL, cols = NULL, values = NULL, ..., useNames = NA)

colTabulates(x, rows = NULL, cols = NULL, values = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colTabulates(x, rows = NULL, cols = NULL, values = NULL, ..., useNames = NA)

## S4 method for signature 'ANY'
colTabulates(x, rows = NULL, cols = NULL, values = NULL, ..., useNames = NA)
```

## Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
values	the values to search for.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.

## Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowTabulates` / `matrixStats::colTabulates`.

## Value

a [numeric](#) NxJ (KxJ) [matrix](#), where N (K) is the number of rows (columns) for which the J values are calculated.

**See Also**

- `matrixStats::rowTabulates()` and `matrixStats::colTabulates()` which are used when the input is a matrix or numeric vector.
- `base::table()`

**Examples**

```
mat <- matrix(rpois(15, lambda = 3), nrow = 5, ncol = 3)
mat[2, 1] <- NA_integer_
mat[3, 3] <- 0L
mat[4, 1] <- 0L

print(mat)

rowTabulates(mat)
colTabulates(mat)

rowTabulates(mat, values = 0)
colTabulates(mat, values = 0)
```

---

rowVarDiffs

*Calculates the variance of the difference between each element of a row (column) of a matrix-like object*

---

**Description**

Calculates the variance of the difference between each element of a row (column) of a matrix-like object.

**Usage**

```
rowVarDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE, diff = 1L,
  trim = 0, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowVarDiffs(x, rows = NULL,
  cols = NULL, na.rm = FALSE, diff = 1L, trim = 0, ...,
  useNames = NA)

## S4 method for signature 'ANY'
rowVarDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE,
  diff = 1L, trim = 0, ..., useNames = NA)

colVarDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE, diff = 1L,
  trim = 0, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colVarDiffs(x, rows = NULL,
  cols = NULL, na.rm = FALSE, diff = 1L, trim = 0, ...,
  useNames = NA)

## S4 method for signature 'ANY'
colVarDiffs(x, rows = NULL, cols = NULL, na.rm = FALSE,
  diff = 1L, trim = 0, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
diff	An integer specifying the order of difference.
trim	A double in [0,1/2] specifying the fraction of observations to be trimmed from each end of (sorted) x before estimation.
...	Additional arguments passed to specific methods.
useNames	If <a href="#">NA</a> , the default behavior of the function about naming support is remained. If <a href="#">FALSE</a> , no naming support is done. Else if <a href="#">TRUE</a> , names attributes of result are set.

### Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowVarDiffs` / `matrixStats::colVarDiffs`.

### Value

Returns a [numeric vector](#) of length N (K).

### See Also

- `matrixStats::rowVarDiffs()` and `matrixStats::colVarDiffs()` which are used when the input is a [matrix](#) or [numeric vector](#).
- for the direct variance see [rowVars\(\)](#).

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowVarDiffs(mat)
```

```
colVarDiffs(mat)
```

---

rowVars	<i>Calculates the variance for each row (column) of a matrix-like object</i>
---------	--

---

### Description

Calculates the variance for each row (column) of a matrix-like object.

### Usage

```
rowVars(x, rows = NULL, cols = NULL, na.rm = FALSE, center = NULL, ...,
        useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowVars(x, rows = NULL,
        cols = NULL, na.rm = FALSE, center = NULL, dim. = dim(x), ...,
        useNames = NA)
```

```
## S4 method for signature 'ANY'
rowVars(x, rows = NULL, cols = NULL, na.rm = FALSE,
        center = NULL, ..., useNames = NA)
```

```
colVars(x, rows = NULL, cols = NULL, na.rm = FALSE, center = NULL, ...,
        useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colVars(x, rows = NULL,
        cols = NULL, na.rm = FALSE, center = NULL, dim. = dim(x), ...,
        useNames = NA)
```

```
## S4 method for signature 'ANY'
colVars(x, rows = NULL, cols = NULL, na.rm = FALSE,
        center = NULL, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
rows, cols	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <a href="#">NULL</a> , no subsetting is done.
na.rm	If <a href="#">TRUE</a> , <a href="#">NAs</a> are excluded first, otherwise not.
center	(optional) the center, defaults to the row means.
...	Additional arguments passed to specific methods.

useNames	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.
dim.	An <code>integer vector</code> of length two specifying the dimension of <code>x</code> , essential when <code>x</code> is a <code>numeric</code> vector. Note, that this is not a generic argument and not all methods need provide it.

### Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowVars/matrixStats::colVars`.

### Value

Returns a `numeric vector` of length `N (K)`.

### See Also

- `matrixStats::rowVars()` and `matrixStats::colVars()` which are used when the input is a `matrix` or `numeric` vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- For standard deviation estimates, see `rowSds()`.
- `stats::var()`.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowVars(mat)
colVars(mat)
```

---

rowWeightedMads	<i>Calculates the weighted median absolute deviation for each row (column) of a matrix-like object</i>
-----------------	--

---

### Description

Calculates the weighted median absolute deviation for each row (column) of a matrix-like object.

**Usage**

```

rowWeightedMads(x, w = NULL, rows = NULL, cols = NULL, na.rm = FALSE,
  constant = 1.4826, center = NULL, ...)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowWeightedMads(x, w = NULL,
  rows = NULL, cols = NULL, na.rm = FALSE, constant = 1.4826,
  center = NULL, ..., useNames = NA)

## S4 method for signature 'ANY'
rowWeightedMads(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, constant = 1.4826, center = NULL, ...)

colWeightedMads(x, w = NULL, rows = NULL, cols = NULL, na.rm = FALSE,
  constant = 1.4826, center = NULL, ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colWeightedMads(x, w = NULL,
  rows = NULL, cols = NULL, na.rm = FALSE, constant = 1.4826,
  center = NULL, ..., useNames = NA)

## S4 method for signature 'ANY'
colWeightedMads(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, constant = 1.4826, center = NULL, ..., useNames = NA)

```

**Arguments**

x	An NxK matrix-like object.
w	A <b>numeric</b> vector of length K (N) that specifies by how much each element is weighted.
rows, cols	A <b>vector</b> indicating the subset of rows (and/or columns) to operate over. If <b>NULL</b> , no subsetting is done.
na.rm	If <b>TRUE</b> , <b>NA</b> s are excluded first, otherwise not.
constant	A scale factor. See <code>stats::mad()</code> for details.
center	(optional) the center, defaults to the row means
...	Additional arguments passed to specific methods.
useNames	If <b>NA</b> , the default behavior of the function about naming support is remained. If <b>FALSE</b> , no naming support is done. Else if <b>TRUE</b> , names attributes of result are set.

**Details**

The S4 methods for x of type **matrix**, **array**, or **numeric** call `matrixStats::rowWeightedMads` / `matrixStats::colWeightedMads`.

**Value**

Returns a [numeric vector](#) of length N (K).

**See Also**

- `matrixStats::rowWeightedMads()` and `matrixStats::colWeightedMads()` which are used when the input is a matrix or numeric vector.
- See also [rowMads](#) for the corresponding unweighted function.

**Examples**

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)
w <- rnorm(n = 5, mean = 3)
rowWeightedMads(mat, w = w[1:3])
colWeightedMads(mat, w = w)
```

---

rowWeightedMeans	<i>Calculates the weighted mean for each row (column) of a matrix-like object</i>
------------------	---

---

**Description**

Calculates the weighted mean for each row (column) of a matrix-like object.

**Usage**

```
rowWeightedMeans(x, w = NULL, rows = NULL, cols = NULL, na.rm = FALSE,
  ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowWeightedMeans(x, w = NULL,
  rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'ANY'
rowWeightedMeans(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, ..., useNames = NA)

colWeightedMeans(x, w = NULL, rows = NULL, cols = NULL, na.rm = FALSE,
  ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
```

```
colWeightedMeans(x, w = NULL,
  rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'ANY'
colWeightedMeans(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, ..., useNames = NA)
```

### Arguments

<code>x</code>	An <code>NxK</code> matrix-like object.
<code>w</code>	A <a href="#">numeric</a> vector of length <code>K</code> ( <code>N</code> ) that specifies by how much each element is weighted.
<code>rows, cols</code>	A <a href="#">vector</a> indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>na.rm</code>	If <code>TRUE</code> , <code>NA</code> s are excluded first, otherwise not.
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.

### Details

The S4 methods for `x` of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowWeightedMeans` / `matrixStats::colWeightedMeans`.

### Value

Returns a [numeric vector](#) of length `N` (`K`).

### See Also

- `matrixStats::rowWeightedMeans()` and `matrixStats::colWeightedMeans()` which are used when the input is a `matrix` or `numeric` vector.
- See also [rowMeans2](#) for the corresponding unweighted function.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)
w <- rnorm(n = 5, mean = 3)
rowWeightedMeans(mat, w = w[1:3])
colWeightedMeans(mat, w = w)
```

---

rowWeightedMedians	<i>Calculates the weighted median for each row (column) of a matrix-like object</i>
--------------------	---

---

### Description

Calculates the weighted median for each row (column) of a matrix-like object.

### Usage

```
rowWeightedMedians(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowWeightedMedians(x,
  w = NULL, rows = NULL, cols = NULL, na.rm = FALSE, ...,
  useNames = NA)
```

```
## S4 method for signature 'ANY'
rowWeightedMedians(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, ..., useNames = NA)
```

```
colWeightedMedians(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colWeightedMedians(x,
  w = NULL, rows = NULL, cols = NULL, na.rm = FALSE, ...,
  useNames = NA)
```

```
## S4 method for signature 'ANY'
colWeightedMedians(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
w	A <b>numeric</b> vector of length K (N) that specifies by how much each element is weighted.
rows, cols	A <b>vector</b> indicating the subset of rows (and/or columns) to operate over. If <b>NULL</b> , no subsetting is done.
na.rm	If <b>TRUE</b> , <b>NA</b> s are excluded first, otherwise not.
...	Additional arguments passed to specific methods.
useNames	If <b>NA</b> , the default behavior of the function about naming support is remained. If <b>FALSE</b> , no naming support is done. Else if <b>TRUE</b> , names attributes of result are set.

**Details**

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowWeightedMedians` / `matrixStats::colWeightedMedians`.

**Value**

Returns a `numeric vector` of length `N (K)`.

**See Also**

- `matrixStats::rowWeightedMedians()` and `matrixStats::colWeightedMedians()` which are used when the input is a `matrix` or `numeric vector`.
- See also `rowMedians` for the corresponding unweighted function.

**Examples**

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)
w <- rnorm(n = 5, mean = 3)
rowWeightedMedians(mat, w = w[1:3])
colWeightedMedians(mat, w = w)
```

---

rowWeightedSds	<i>Calculates the weighted standard deviation for each row (column) of a matrix-like object</i>
----------------	---

---

**Description**

Calculates the weighted standard deviation for each row (column) of a matrix-like object.

**Usage**

```
rowWeightedSds(x, w = NULL, rows = NULL, cols = NULL, na.rm = FALSE,
  ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowWeightedSds(x, w = NULL,
  rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'ANY'
rowWeightedSds(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, ..., useNames = NA)
```

```
colWeightedSds(x, w = NULL, rows = NULL, cols = NULL, na.rm = FALSE,
  ..., useNames = NA)

## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colWeightedSds(x, w = NULL,
  rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'ANY'
colWeightedSds(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, ..., useNames = NA)
```

### Arguments

<code>x</code>	An $N \times K$ matrix-like object.
<code>w</code>	A <b>numeric</b> vector of length $K$ ( $N$ ) that specifies by how much each element is weighted.
<code>rows, cols</code>	A <b>vector</b> indicating the subset of rows (and/or columns) to operate over. If <b>NULL</b> , no subsetting is done.
<code>na.rm</code>	If <b>TRUE</b> , <b>NA</b> s are excluded first, otherwise not.
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <b>NA</b> , the default behavior of the function about naming support is remained. If <b>FALSE</b> , no naming support is done. Else if <b>TRUE</b> , names attributes of result are set.

### Details

The S4 methods for `x` of type **matrix**, **array**, or **numeric** call `matrixStats::rowWeightedSds / matrixStats::colWeightedSds`.

### Value

Returns a **numeric vector** of length  $N$  ( $K$ ).

### See Also

- `matrixStats::rowWeightedSds()` and `matrixStats::colWeightedSds()` which are used when the input is a **matrix** or **numeric** vector.
- See also **rowSds** for the corresponding unweighted function.

### Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)
w <- rnorm(n = 5, mean = 3)
```

```
rowWeightedSds(mat, w = w[1:3])
colWeightedSds(mat, w = w)
```

---

rowWeightedVars	<i>Calculates the weighted variance for each row (column) of a matrix-like object</i>
-----------------	---

---

### Description

Calculates the weighted variance for each row (column) of a matrix-like object.

### Usage

```
rowWeightedVars(x, w = NULL, rows = NULL, cols = NULL, na.rm = FALSE,
  ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
rowWeightedVars(x, w = NULL,
  rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)
```

```
## S4 method for signature 'ANY'
rowWeightedVars(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, ..., useNames = NA)
```

```
colWeightedVars(x, w = NULL, rows = NULL, cols = NULL, na.rm = FALSE,
  ..., useNames = NA)
```

```
## S4 method for signature 'matrix_OR_array_OR_table_OR_numeric'
colWeightedVars(x, w = NULL,
  rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)
```

```
## S4 method for signature 'ANY'
colWeightedVars(x, w = NULL, rows = NULL, cols = NULL,
  na.rm = FALSE, ..., useNames = NA)
```

### Arguments

x	An NxK matrix-like object.
w	A <b>numeric</b> vector of length K (N) that specifies by how much each element is weighted.
rows, cols	A <b>vector</b> indicating the subset of rows (and/or columns) to operate over. If <b>NULL</b> , no subsetting is done.
na.rm	If <b>TRUE</b> , <b>NA</b> s are excluded first, otherwise not.
...	Additional arguments passed to specific methods.
useNames	If <b>NA</b> , the default behavior of the function about naming support is remained. If <b>FALSE</b> , no naming support is done. Else if <b>TRUE</b> , names attributes of result are set.

**Details**

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowWeightedVars` / `matrixStats::colWeightedVars`.

**Value**

Returns a `numeric vector` of length `N (K)`.

**See Also**

- `matrixStats::rowWeightedVars()` and `matrixStats::colWeightedVars()` which are used when the input is a `matrix` or `numeric vector`.
- See also `rowVars` for the corresponding unweighted function.

**Examples**

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)
w <- rnorm(n = 5, mean = 3)
rowWeightedVars(mat, w = w[1:3])
colWeightedVars(mat, w = w)
```

# Index

## \* array

- rowAvgPerColSet, 8
- rowCollapse, 9
- rowCummaxs, 12
- rowCummins, 14
- rowCumprods, 15
- rowCumsums, 17
- rowDiffs, 18
- rowIQRDiffs, 20
- rowIQRs, 21
- rowLogSumExps, 23
- rowMadDiffs, 24
- rowMads, 26
- rowMaxs, 27
- rowMeans2, 29
- rowMedians, 30
- rowMins, 32
- rowOrderStats, 33
- rowProds, 35
- rowQuantiles, 36
- rowRanges, 38
- rowRanks, 40
- rowSdDiffs, 42
- rowSds, 43
- rowSums2, 45
- rowTabulates, 47
- rowVarDiffs, 48
- rowVars, 50
- rowWeightedMads, 51
- rowWeightedMeans, 53
- rowWeightedMedians, 55
- rowWeightedSds, 56
- rowWeightedVars, 58

## \* iteration

- rowAvgPerColSet, 8
- rowCollapse, 9
- rowCummaxs, 12
- rowCummins, 14
- rowCumprods, 15

- rowCumsums, 17
- rowDiffs, 18
- rowIQRDiffs, 20
- rowIQRs, 21
- rowLogSumExps, 23
- rowMadDiffs, 24
- rowMads, 26
- rowMaxs, 27
- rowMeans2, 29
- rowMedians, 30
- rowMins, 32
- rowOrderStats, 33
- rowProds, 35
- rowQuantiles, 36
- rowRanges, 38
- rowRanks, 40
- rowSdDiffs, 42
- rowSds, 43
- rowSums2, 45
- rowTabulates, 47
- rowVarDiffs, 48
- rowVars, 50
- rowWeightedMads, 51
- rowWeightedMeans, 53
- rowWeightedMedians, 55
- rowWeightedSds, 56
- rowWeightedVars, 58

## \* robust

- rowAvgPerColSet, 8
- rowCollapse, 9
- rowCummaxs, 12
- rowCummins, 14
- rowCumprods, 15
- rowCumsums, 17
- rowDiffs, 18
- rowIQRDiffs, 20
- rowIQRs, 21
- rowLogSumExps, 23
- rowMadDiffs, 24

- rowMads, [26](#)
- rowMaxs, [27](#)
- rowMeans2, [29](#)
- rowMedians, [30](#)
- rowMins, [32](#)
- rowOrderStats, [33](#)
- rowProds, [35](#)
- rowQuantiles, [36](#)
- rowRanges, [38](#)
- rowRanks, [40](#)
- rowSdDiffs, [42](#)
- rowSds, [43](#)
- rowSums2, [45](#)
- rowTabulates, [47](#)
- rowVarDiffs, [48](#)
- rowVars, [50](#)
- rowWeightedMads, [51](#)
- rowWeightedMeans, [53](#)
- rowWeightedMedians, [55](#)
- rowWeightedSds, [56](#)
- rowWeightedVars, [58](#)
- \* **univar2**
  - rowAvgPerColSet, [8](#)
- \* **univar**
  - rowCollapse, [9](#)
  - rowCummaxs, [12](#)
  - rowCummins, [14](#)
  - rowCumprods, [15](#)
  - rowCumsums, [17](#)
  - rowDiffs, [18](#)
  - rowIQRDiffs, [20](#)
  - rowIQRs, [21](#)
  - rowLogSumExps, [23](#)
  - rowMadDiffs, [24](#)
  - rowMads, [26](#)
  - rowMaxs, [27](#)
  - rowMeans2, [29](#)
  - rowMedians, [30](#)
  - rowMins, [32](#)
  - rowOrderStats, [33](#)
  - rowProds, [35](#)
  - rowSdDiffs, [42](#)
  - rowSds, [43](#)
  - rowSums2, [45](#)
  - rowTabulates, [47](#)
  - rowVarDiffs, [48](#)
  - rowVars, [50](#)
  - rowWeightedMads, [51](#)
  - rowWeightedMeans, [53](#)
  - rowWeightedMedians, [55](#)
  - rowWeightedSds, [56](#)
  - rowWeightedVars, [58](#)
- all, [4](#)
- any, [6, 7](#)
- array, [4, 5, 7, 9, 10, 12, 13, 15–17, 19, 21, 22, 24, 25, 27, 28, 30, 31, 33, 34, 36, 38, 39, 41, 43, 44, 46, 47, 49, 51, 52, 54, 56, 57, 59](#)
- base::rank, [41](#)
- class:matrix\_OR\_array\_OR\_table\_OR\_numeric  
(MatrixGenerics-package), [3](#)
- colAalls, [4](#)
- colAalls (rowAalls), [3](#)
- colAalls, ANY-method (rowAalls), [3](#)
- colAalls, matrix\_OR\_array\_OR\_table\_OR\_numeric-method  
(rowAalls), [3](#)
- colAnyNAs, [6](#)
- colAnyNAs (rowAnyNAs), [5](#)
- colAnyNAs, ANY-method (rowAnyNAs), [5](#)
- colAnyNAs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method  
(rowAnyNAs), [5](#)
- colAnys, [7](#)
- colAnys (rowAnys), [6](#)
- colAnys, ANY-method (rowAnys), [6](#)
- colAnys, matrix\_OR\_array\_OR\_table\_OR\_numeric-method  
(rowAnys), [6](#)
- colAvgPerRowSet, [9](#)
- colAvgPerRowSet (rowAvgPerColSet), [8](#)
- colAvgPerRowSet, ANY-method  
(rowAvgPerColSet), [8](#)
- colAvgPerRowSet, matrix\_OR\_array\_OR\_table\_OR\_numeric-method  
(rowAvgPerColSet), [8](#)
- colCollapse, [10](#)
- colCollapse (rowCollapse), [9](#)
- colCollapse, ANY-method (rowCollapse), [9](#)
- colCollapse, matrix\_OR\_array\_OR\_table\_OR\_numeric-method  
(rowCollapse), [9](#)
- colCounts, [12](#)
- colCounts (rowCounts), [11](#)
- colCounts, ANY-method (rowCounts), [11](#)
- colCounts, matrix\_OR\_array\_OR\_table\_OR\_numeric-method  
(rowCounts), [11](#)
- colCummaxs, [13](#)
- colCummaxs (rowCummaxs), [12](#)

- colCummaxs, ANY-method (rowCummaxs), 12
- colCummaxs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowCummaxs), 12
- colCummins, 15
- colCummins (rowCummins), 14
- colCummins, ANY-method (rowCummins), 14
- colCummins, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowCummins), 14
- colCumprods, 16
- colCumprods (rowCumprods), 15
- colCumprods, ANY-method (rowCumprods), 15
- colCumprods, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowCumprods), 15
- colCumsums, 18
- colCumsums (rowCumsums), 17
- colCumsums, ANY-method (rowCumsums), 17
- colCumsums, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowCumsums), 17
- colDiffs, 19
- colDiffs (rowDiffs), 18
- colDiffs, ANY-method (rowDiffs), 18
- colDiffs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowDiffs), 18
- colIQRDiffs, 21
- colIQRDiffs (rowIQRDiffs), 20
- colIQRDiffs, ANY-method (rowIQRDiffs), 20
- colIQRDiffs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowIQRDiffs), 20
- colIQRs, 22
- colIQRs (rowIQRs), 21
- colIQRs, ANY-method (rowIQRs), 21
- colIQRs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowIQRs), 21
- colLogSumExps, 24
- colLogSumExps (rowLogSumExps), 23
- colLogSumExps, ANY-method (rowLogSumExps), 23
- colLogSumExps, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowLogSumExps), 23
- colMadDiffs, 25
- colMadDiffs (rowMadDiffs), 24
- colMadDiffs, ANY-method (rowMadDiffs), 24
- colMadDiffs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMadDiffs), 24
- colMads, 27
- colMads (rowMads), 26
- colMads, ANY-method (rowMads), 26
- colMads, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMads), 26
- colMeans, 28
- colMeans (rowMeans), 27
- colMeans, ANY-method (rowMeans), 27
- colMeans, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMeans), 27
- colMeans2, 30
- colMeans2 (rowMeans2), 29
- colMeans2, ANY-method (rowMeans2), 29
- colMeans2, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMeans2), 29
- colMedians, 31
- colMedians (rowMedians), 30
- colMedians, ANY-method (rowMedians), 30
- colMedians, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMedians), 30
- colMins, 33
- colMins (rowMins), 32
- colMins, ANY-method (rowMins), 32
- colMins, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMins), 32
- colOrderStats, 34
- colOrderStats (rowOrderStats), 33
- colOrderStats, ANY-method (rowOrderStats), 33
- colOrderStats, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowOrderStats), 33
- colProds, 36
- colProds (rowProds), 35
- colProds, ANY-method (rowProds), 35
- colProds, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowProds), 35
- colQuantiles, 38
- colQuantiles (rowQuantiles), 36
- colQuantiles, ANY-method (rowQuantiles), 36
- colQuantiles, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowQuantiles), 36
- colRanges, 39
- colRanges (rowRanges), 38
- colRanges, ANY-method (rowRanges), 38
- colRanges, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowRanges), 38
- colRanks, 41
- colRanks (rowRanks), 40
- colRanks, ANY-method (rowRanks), 40
- colRanks, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowRanks), 40

- colSdDiffs, [43](#)
- colSdDiffs (rowSdDiffs), [42](#)
- colSdDiffs, ANY-method (rowSdDiffs), [42](#)
- colSdDiffs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowSdDiffs), [42](#)
- colSds, [45](#)
- colSds (rowSds), [43](#)
- colSds, ANY-method (rowSds), [43](#)
- colSds, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowSds), [43](#)
- colSums2, [46](#)
- colSums2 (rowSums2), [45](#)
- colSums2(), [36](#)
- colSums2, ANY-method (rowSums2), [45](#)
- colSums2, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowSums2), [45](#)
- colTabulates, [48](#)
- colTabulates (rowTabulates), [47](#)
- colTabulates, ANY-method (rowTabulates), [47](#)
- colTabulates, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowTabulates), [47](#)
- colVarDiffs, [49](#)
- colVarDiffs (rowVarDiffs), [48](#)
- colVarDiffs, ANY-method (rowVarDiffs), [48](#)
- colVarDiffs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowVarDiffs), [48](#)
- colVars, [51](#)
- colVars (rowVars), [50](#)
- colVars, ANY-method (rowVars), [50](#)
- colVars, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowVars), [50](#)
- colWeightedMads, [53](#)
- colWeightedMads (rowWeightedMads), [51](#)
- colWeightedMads, ANY-method (rowWeightedMads), [51](#)
- colWeightedMads, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowWeightedMads), [51](#)
- colWeightedMeans, [54](#)
- colWeightedMeans (rowWeightedMeans), [53](#)
- colWeightedMeans, ANY-method (rowWeightedMeans), [53](#)
- colWeightedMeans, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowWeightedMeans), [53](#)
- colWeightedMedians, [56](#)
- colWeightedMedians (rowWeightedMedians), [55](#)
- colWeightedMedians, ANY-method (rowWeightedMedians), [55](#)
- colWeightedMedians, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowWeightedMedians), [55](#)
- colWeightedSds, [57](#)
- colWeightedSds (rowWeightedSds), [56](#)
- colWeightedSds, ANY-method (rowWeightedSds), [56](#)
- colWeightedSds, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowWeightedSds), [56](#)
- colWeightedVars, [59](#)
- colWeightedVars (rowWeightedVars), [58](#)
- colWeightedVars, ANY-method (rowWeightedVars), [58](#)
- colWeightedVars, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowWeightedVars), [58](#)
- cummax, [13](#)
- cummin, [15](#)
- cumprod, [16](#)
- cumsum, [18](#)
- diff, [19](#)
- FALSE, [4](#), [5](#), [7](#), [10](#), [11](#), [13](#), [14](#), [16](#), [17](#), [19](#), [21–23](#), [25](#), [27](#), [28](#), [30](#), [31](#), [33](#), [34](#), [36](#), [37](#), [39](#), [41](#), [43](#), [44](#), [46](#), [47](#), [49](#), [51](#), [52](#), [54](#), [55](#), [57](#), [58](#)
- integer, [4](#), [7](#), [8](#), [10](#), [12–14](#), [16](#), [17](#), [19](#), [23](#), [27](#), [28](#), [30](#), [31](#), [33](#), [34](#), [39](#), [41](#), [44](#), [46](#), [51](#)
- IQR, [22](#)
- is.na, [6](#)
- logical, [4](#), [5](#), [7](#)
- mad, [27](#), [52](#)
- matrix, [4](#), [5](#), [7](#), [9](#), [10](#), [12](#), [13](#), [15–17](#), [19](#), [21](#), [22](#), [24](#), [25](#), [27](#), [28](#), [30](#), [31](#), [33](#), [34](#), [36](#), [38](#), [39](#), [41](#), [43](#), [44](#), [46](#), [47](#), [49](#), [51](#), [52](#), [54](#), [56](#), [57](#), [59](#)
- matrix\_OR\_array\_OR\_table\_OR\_numeric (MatrixGenerics-package), [3](#)
- matrix\_OR\_array\_OR\_table\_OR\_numeric-class (MatrixGenerics-package), [3](#)
- MatrixGenerics-package, [3](#)
- NA, [4](#), [5](#), [7](#), [10](#), [11](#), [13](#), [14](#), [16](#), [17](#), [19–23](#), [25](#), [27–37](#), [39](#), [41–44](#), [46](#), [47](#), [49–52](#), [54](#), [55](#), [57](#), [58](#)
- NULL, [4](#), [5](#), [7](#), [8](#), [10](#), [11](#), [13](#), [14](#), [16](#), [17](#), [19](#), [20](#), [22](#), [23](#), [25](#), [26](#), [28](#), [29](#), [31](#), [32](#), [34](#), [35](#)

- [37, 39, 41, 42, 44, 46, 47, 49, 50, 52, 54, 55, 57, 58](#)  
 numeric, [4, 5, 7, 9, 10, 12–17, 19, 21–25, 27, 28, 30, 31, 33, 34, 36, 38, 39, 41, 43, 44, 46, 47, 49, 51–59](#)  
 prod, [36](#)  
 quantile, [37](#)  
 range, [39](#)  
 RangedSummarizedExperiment, [39](#)  
 rowAlls, [3, 4, 7, 12](#)  
 rowAlls, ANY-method (rowAlls), [3](#)  
 rowAlls, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowAlls), [3](#)  
 rowAnyNAs, [5, 6](#)  
 rowAnyNAs, ANY-method (rowAnyNAs), [5](#)  
 rowAnyNAs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowAnyNAs), [5](#)  
 rowAnys, [4, 6, 6, 7, 12](#)  
 rowAnys, ANY-method (rowAnys), [6](#)  
 rowAnys, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowAnys), [6](#)  
 rowAvgPerColSet, [8, 9](#)  
 rowAvgPerColSet, ANY-method (rowAvgPerColSet), [8](#)  
 rowAvgPerColSet, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowAvgPerColSet), [8](#)  
 rowCollapse, [9, 10](#)  
 rowCollapse, ANY-method (rowCollapse), [9](#)  
 rowCollapse, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowCollapse), [9](#)  
 rowCounts, [11, 12](#)  
 rowCounts, ANY-method (rowCounts), [11](#)  
 rowCounts, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowCounts), [11](#)  
 rowCummaxs, [12, 13](#)  
 rowCummaxs, ANY-method (rowCummaxs), [12](#)  
 rowCummaxs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowCummaxs), [12](#)  
 rowCummins, [14, 15](#)  
 rowCummins, ANY-method (rowCummins), [14](#)  
 rowCummins, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowCummins), [14](#)  
 rowCumprods, [15, 16](#)  
 rowCumprods, ANY-method (rowCumprods), [15](#)  
 rowCumprods, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowCumprods), [15](#)  
 rowCumsums, [17, 18](#)  
 rowCumsums, ANY-method (rowCumsums), [17](#)  
 rowCumsums, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowCumsums), [17](#)  
 rowDiffs, [18, 19](#)  
 rowDiffs, ANY-method (rowDiffs), [18](#)  
 rowDiffs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowDiffs), [18](#)  
 rowIQRDiffs, [20, 21](#)  
 rowIQRDiffs, ANY-method (rowIQRDiffs), [20](#)  
 rowIQRDiffs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowIQRDiffs), [20](#)  
 rowIQRs, [21, 21, 22](#)  
 rowIQRs, ANY-method (rowIQRs), [21](#)  
 rowIQRs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowIQRs), [21](#)  
 rowLogSumExps, [23, 24](#)  
 rowLogSumExps, ANY-method (rowLogSumExps), [23](#)  
 rowLogSumExps, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowLogSumExps), [23](#)  
 rowMadDiffs, [24, 25](#)  
 rowMadDiffs, ANY-method (rowMadDiffs), [24](#)  
 rowMadDiffs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMadDiffs), [24](#)  
 rowMads, [26, 27, 53](#)  
 rowMads(), [22](#)  
 rowMads, ANY-method (rowMads), [26](#)  
 rowMads, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMads), [26](#)  
 rowMaxs, [13, 27, 28, 33, 39](#)  
 rowMaxs, ANY-method (rowMaxs), [27](#)  
 rowMaxs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMaxs), [27](#)  
 rowMeans, [27, 30, 31, 45, 46, 51](#)  
 rowMeans2, [27, 29, 30, 31, 45, 46, 51, 54](#)  
 rowMeans2, ANY-method (rowMeans2), [29](#)  
 rowMeans2, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMeans2), [29](#)  
 rowMedians, [30, 31, 56](#)  
 rowMedians, ANY-method (rowMedians), [30](#)  
 rowMedians, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMedians), [30](#)  
 rowMins, [15, 28, 32, 33, 39](#)  
 rowMins, ANY-method (rowMins), [32](#)  
 rowMins, matrix\_OR\_array\_OR\_table\_OR\_numeric-method (rowMins), [32](#)  
 rowOrderStats, [33, 34](#)

- rowOrderStats, ANY-method
  - (rowOrderStats), 33
- rowOrderStats, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowOrderStats), 33
- rowProds, 35, 36
- rowProds, ANY-method (rowProds), 35
- rowProds, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowProds), 35
- rowQuantiles, 36, 38
- rowQuantiles, ANY-method (rowQuantiles), 36
- rowQuantiles, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowQuantiles), 36
- rowRanges, 38, 39
- rowRanges, ANY-method (rowRanges), 38
- rowRanges, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowRanges), 38
- rowRanks, 40, 41
- rowRanks, ANY-method (rowRanks), 40
- rowRanks, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowRanks), 40
- rowSdDiffs, 42, 43
- rowSdDiffs, ANY-method (rowSdDiffs), 42
- rowSdDiffs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowSdDiffs), 42
- rowSds, 22, 27, 43, 45, 51, 57
- rowSds(), 43
- rowSds, ANY-method (rowSds), 43
- rowSds, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowSds), 43
- rowSums2, 36, 45, 46
- rowSums2(), 24
- rowSums2, ANY-method (rowSums2), 45
- rowSums2, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowSums2), 45
- rowTabulates, 47, 48
- rowTabulates, ANY-method (rowTabulates), 47
- rowTabulates, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowTabulates), 47
- rowVarDiffs, 48, 49
- rowVarDiffs, ANY-method (rowVarDiffs), 48
- rowVarDiffs, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowVarDiffs), 48
- rowVars, 30, 45, 50, 51, 59
- rowVars(), 49
- rowVars, ANY-method (rowVars), 50
- rowVars, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowVars), 50
- rowWeightedMads, 51, 53
- rowWeightedMads, ANY-method
  - (rowWeightedMads), 51
- rowWeightedMads, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowWeightedMads), 51
- rowWeightedMeans, 53, 54
- rowWeightedMeans, ANY-method
  - (rowWeightedMeans), 53
- rowWeightedMeans, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowWeightedMeans), 53
- rowWeightedMedians, 55, 56
- rowWeightedMedians, ANY-method
  - (rowWeightedMedians), 55
- rowWeightedMedians, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowWeightedMedians), 55
- rowWeightedSds, 56, 57
- rowWeightedSds, ANY-method
  - (rowWeightedSds), 56
- rowWeightedSds, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowWeightedSds), 56
- rowWeightedVars, 58, 59
- rowWeightedVars, ANY-method
  - (rowWeightedVars), 58
- rowWeightedVars, matrix\_OR\_array\_OR\_table\_OR\_numeric-method
  - (rowWeightedVars), 58
- stats::quantile, 38
- sum, 46
- table, 48
- TRUE, 4, 5, 7, 10, 11, 13, 14, 16, 17, 19–23, 25, 27–37, 39, 41–44, 46, 47, 49–52, 54, 55, 57, 58
- var, 51
- vector, 4, 5, 7, 8, 10–14, 16, 17, 19–37, 39, 41–44, 46, 47, 49–59