

# BSgenome.Hsapiens.UCSC.hg17

September 27, 2024

---

BSgenome.Hsapiens.UCSC.hg17

*Full genome sequences for Homo sapiens (UCSC version hg17)*

---

## Description

Full genome sequences for Homo sapiens (Human) as provided by UCSC (hg17, May 2004) and stored in Biostrings objects.

## Note

This BSgenome data package was made from the following source data files:

chromFa.zip from <http://hgdownload.cse.ucsc.edu/goldenPath/hg17/bigZips/>

See [?BSgenomeForge](#) and the BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

## Author(s)

The Bioconductor Dev Team

## See Also

- [BSgenome](#) objects and the `available.genomes` function in the **BSgenome** software package.
- [DNAString](#) objects in the **Biostrings** package.
- The BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

## Examples

```
BSgenome.Hsapiens.UCSC.hg17
genome <- BSgenome.Hsapiens.UCSC.hg17
seqlengths(genome)
genome$chr1 # same as genome[["chr1"]]
```

```
## ----- ## Upstream sequences
## -----
```

```
## Starting with BioC 3.0, the upstream1000, upstream2000, and
## upstream5000 sequences for hg17 are not included in the BSgenome data
## package anymore. However they can easily be extracted from the full
## genome sequences with something like:

library(GenomicFeatures)
txdb <- makeTranscriptDbFromUCSC("hg17", "knownGene")
gn <- sort(genes(txdb))
up1000 <- flank(gn, width=1000)
up1000seqs <- getSeq(genome, up1000)

## IMPORTANT: Make sure you use a TxDb package (or TranscriptDb object),
## that contains a gene model based on the exact same reference genome
## as the BSgenome object you pass to getSeq(). Note that you can make
## your own custom TranscriptDb object from various annotation resources.
## See the makeTranscriptDbFromUCSC(), makeTranscriptDbFromBiomart(),
## and makeTranscriptDbFromGFF() functions in the GenomicFeatures
## package.

## -----
## Genome-wide motif searching
## -----
## See the GenomeSearching vignette in the BSgenome software
## package for some examples of genome-wide motif searching using
## Biostrings and the BSgenome data packages:
if (interactive())
  vignette("GenomeSearching", package="BSgenome")
```

# Index

**\* data**

BSgenome.Hsapiens.UCSC.hg17, [1](#)

**\* package**

BSgenome.Hsapiens.UCSC.hg17, [1](#)

available.genomes, [1](#)

BSgenome, [1](#)

BSgenome.Hsapiens.UCSC.hg17, [1](#)

BSgenome.Hsapiens.UCSC.hg17-package  
(BSgenome.Hsapiens.UCSC.hg17),  
[1](#)

BSgenomeForge, [1](#)

DNAStrng, [1](#)

Hsapiens (BSgenome.Hsapiens.UCSC.hg17),  
[1](#)