

Package ‘Nebulosa’

November 21, 2024

Type Package

Title Single-Cell Data Visualisation Using Kernel Gene-Weighted
Density Estimation

Version 1.17.0

Description This package provides an enhanced visualization of single-cell data based on gene-weighted density estimation. Nebulosa recovers the signal from dropped-out features and allows the inspection of the joint expression from multiple features (e.g. genes). Seurat and SingleCellExperiment objects can be used within Nebulosa.

URL <https://github.com/powellgenomicslab/Nebulosa>

BugReports <https://github.com/powellgenomicslab/Nebulosa/issues>

License GPL-3

Encoding UTF-8

Depends R (>= 4.0), ggplot2, patchwork

Imports SingleCellExperiment, SummarizedExperiment, SeuratObject, ks,
Matrix, stats, methods, ggrastr

RoxygenNote 7.2.3

VignetteBuilder knitr

Suggests testthat, BiocStyle, knitr, rmarkdown, covr, scater, scan,
DropletUtils, igraph, BiocFileCache, Seurat

biocViews Software, GeneExpression, SingleCell, Visualization,
DimensionReduction

git_url <https://git.bioconductor.org/packages/Nebulosa>

git_branch devel

git_last_commit 29d6923

git_last_commit_date 2024-10-29

Repository Bioconductor 3.21

Date/Publication 2024-11-20

Author Jose Alquicira-Hernandez [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-9049-7780>>)

Maintainer Jose Alquicira-Hernandez <alquicirajose@gmail.com>

Contents

| | |
|-----------------------------|---|
| calculate_density | 2 |
| plot_density | 3 |
| plot_density_ | 5 |
| wkde2d | 6 |

| | |
|--------------|----------|
| Index | 8 |
|--------------|----------|

| | |
|-------------------|---|
| calculate_density | <i>Estimate weighted kernel density</i> |
|-------------------|---|

Description

Estimate weighted kernel density

Usage

```
calculate_density(w, x, method, adjust = 1, map = TRUE)
```

Arguments

| | |
|--------|--|
| w | Vector with weights for each observation |
| x | Matrix with dimensions where to calculate the density from. Only the first two dimensions will be used |
| method | Kernel density estimation method: <ul style="list-style-type: none"> • ks: Computes density using the kde function from the ks package. • wkde: Computes density using a modified version of the kde2d function from the MASS package to allow weights. Bandwidth selection from the ks package is used instead. |
| adjust | Numeric value to adjust to bandwidth. Default: 1. Not available for ks method |
| map | Whether to map densities to individual observations |

Value

If map is TRUE, a vector with corresponding densities for each observation is returned. Otherwise, a list with the density estimates from the selected method is returned.

Author(s)

Jose Alquicira-Hernandez

Examples

```
dens <- Nebulosa:::calculate_density(iris[, 3], iris[, 1:2], method = "wkde")
```

| | |
|--------------|---|
| plot_density | <i>Plot gene-weighted 2D kernel density</i> |
|--------------|---|

Description

Plot gene-weighted 2D kernel density

Usage

```
plot_density(  
  object,  
  features,  
  slot = NULL,  
  joint = FALSE,  
  reduction = NULL,  
  dims = c(1, 2),  
  method = c("ks", "wkde"),  
  adjust = 1,  
  size = 1,  
  shape = 16,  
  combine = TRUE,  
  pal = "viridis",  
  raster = TRUE,  
  ...  
)
```

```
## S4 method for signature 'Seurat'
```

```
plot_density(  
  object,  
  features,  
  slot = NULL,  
  joint = FALSE,  
  reduction = NULL,  
  dims = c(1, 2),  
  method = c("ks", "wkde"),  
  adjust = 1,  
  size = 1,  
  shape = 16,  
  combine = TRUE,  
  pal = "viridis",  
  raster = TRUE,  
  ...  
)
```

```
## S4 method for signature 'SingleCellExperiment'
```

```
plot_density(  
  object,
```

```

features,
slot = NULL,
joint = FALSE,
reduction = NULL,
dims = c(1, 2),
method = c("ks", "wkde"),
adjust = 1,
size = 1,
shape = 16,
combine = TRUE,
pal = "viridis",
raster = TRUE,
...
)

```

Arguments

| | |
|-----------|--|
| object | Seurat or SingleCellExperiment object |
| features | Features (e.g. genes) to visualize |
| slot | Type of data: counts or data for Seurat objects and counts, logcounts, or normcounts for SingleCellExperiment objects |
| joint | Return joint density plot? By default FALSE |
| reduction | Name of the reduction to visualize. If not provided, last computed reduction is visualized |
| dims | Vector of length 2 specifying the dimensions to be plotted. By default, the first two dimensions are considered. |
| method | Kernel density estimation method: <ul style="list-style-type: none"> ks: Computes density using the kde function from the ks package. wkde: Computes density using a modified version of the kde2d function from the MASS package to allow weights. Bandwidth selection from the ks package is used instead. |
| adjust | Numeric value to adjust to bandwidth. Default: 1. Not available for ks method |
| size | Size of the geom to be plotted (e.g. point size) |
| shape | Shape of the geom to be plotted |
| combine | Create a single plot? If FALSE, a list with ggplot objects is returned |
| pal | String specifying the viridis color palette to use. |
| raster | Rasterise plot |
| ... | Further scale arguments passed to scale_color_viridis_c Options: <ul style="list-style-type: none"> viridis magma cividis inferno plasma |

Value

A scatterplot from a given reduction showing the gene-weighted density

Methods (by class)

- `plot_density(Seurat)`: Plot gene-weighted 2D kernel density
- `plot_density(SingleCellExperiment)`: Plot gene-weighted 2D kernel density

Author(s)

Jose Alquicira-Hernandez

Examples

```
data <- SeuratObject::pbmc_small
plot_density(data, "CD3E")
```

| | |
|---------------|-------------------------------|
| plot_density_ | <i>Plot density estimates</i> |
|---------------|-------------------------------|

Description

Plot density estimates

Usage

```
plot_density_(
  z,
  feature,
  cell_embeddings,
  dim_names,
  shape,
  size,
  legend_title,
  pal = c("viridis", "magma", "cividis", "inferno", "plasma"),
  raster,
  ...
)
```

Arguments

| | |
|------------------------------|--|
| <code>z</code> | Vector with density values for each cells |
| <code>feature</code> | Name of the feature being plotted |
| <code>cell_embeddings</code> | Matrix with cell embeddings |
| <code>dim_names</code> | Names of the dimensions from the cell embeddings |

| | |
|--------------|--|
| shape | Geom shape |
| size | Geom size |
| legend_title | String used as legend title |
| pal | String specifying the viridis color palette to use |
| raster | Rasterise plot |
| ... | Further scale arguments passed to <code>scale_color_viridis_c</code> |

Value

A ggplot object

Author(s)

Jose Alquicira-Hernandez

wkde2d

Weighted 2D kernel density estimation

Description

Weighted 2D kernel density estimation

Usage

```
wkde2d(x, y, w, h, adjust = 1, n = 100, lims = c(range(x), range(y)))
```

Arguments

| | |
|--------|---|
| x | Dimension 1 |
| y | Dimension 2 |
| w | Weight variable |
| h | vector of bandwidths for x and y directions. Defaults to normal reference bandwidth (<code>ks::hpi</code>). A scalar value will be taken to apply to both directions. |
| adjust | Bandwidth adjustment |
| n | Number of grid points in each direction. Can be scalar or a length-2 integer vector. |
| lims | The limits of the rectangle covered by the grid as <code>c(xl, xu, yl, yu)</code> . |

Value

A list of three components.

- x, y The x and y coordinates of the grid points, vectors of length n.
- z An $n[1]$ by $n[2]$ matrix of the weighted estimated density: rows correspond to the value of x, columns to the value of y.

Author(s)

Jose Alquicira-Hernandez

Examples

```
set.seed(1)
x <- rnorm(100)
```

```
set.seed(2)
y <- rnorm(100)
```

```
set.seed(3)
w <- sample(c(0, 1), 100, replace = TRUE)
```

```
dens <- Nebulosa::wkde2d(x, y, w)
```

Index

`calculate_density`, [2](#)

`plot_density`, [3](#)

`plot_density`, Seurat-method

(`plot_density`), [3](#)

`plot_density`, SingleCellExperiment-method

(`plot_density`), [3](#)

`plot_density_`, [5](#)

`wkde2d`, [6](#)