

# Package ‘a4Preproc’

November 22, 2024

**Type** Package

**Title** Automated Affymetrix Array Analysis Preprocessing Package

**Version** 1.55.0

**Date** 2020-10-14

**Description** Utility functions to pre-process data for the Automated Affymetrix Array Analysis set of packages.

**Imports** BiocGenerics, Biobase

**Suggests** ALL, hgu95av2.db, knitr, rmarkdown

**License** GPL-3

**biocViews** Microarray, Preprocessing

**RoxygenNote** 7.1.1

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/a4Preproc>

**git\_branch** devel

**git\_last\_commit** 2b1a86f

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.21

**Date/Publication** 2024-11-22

**Author** Willem Talloen [aut],  
Tobias Verbeke [aut],  
Laure Cougnaud [cre]

**Maintainer** Laure Cougnaud <[laure.cougnaud@openanalytics.eu](mailto:laure.cougnaud@openanalytics.eu)>

## Contents

addGeneInfo . . . . .	2
<b>Index</b>	<b>4</b>

---

`addGeneInfo`*Utility Function to Add Annotation to existing ExpressionSet Objects*

---

**Description**

Adds appropriate featureData, similar to the metadata added in the pipeline script, to the ExpressionSet object.

**Usage**

```
addGeneInfo(eset, annotationLibrary = NULL)
```

**Arguments**

<code>eset</code>	ExpressionSet object for to which one wants to add additional annotation information
<code>annotationLibrary</code>	Annotation Library to use. Must be specified when working with Entrez gene IDs. In this case, one can make use of the JnJ annotation packages such as <code>hgu133plus2hsentrezgJnJ</code> . If not specified, the annotation of the package will be automatically requested with <code>annotation()</code> of the expressionSet object <code>eset</code> and then Affymetrix probe set IDs are expected in <code>featureNames</code>

**Details**

Slots of `featureData(a4ALL)` are

- `Entrez ID~`: Entrez ID as retrieved from annotation package
- `Ensembl ID~`: Ensembl ID as retrieved from annotation package
- `Gene Symbol~`: Gene symbol as retrieved from annotation package
- `Description~`: Description as retrieved from annotation package

**Value**

a new ExpressionSet object with the additional information stored as feature data

**Note**

One should always use subscripting of `featureData` by column name (e.g. `featureData(a4ALL)$`Entrez ID``); as the pipeline ExpressionSets have one additional column compared to the ExpressionSet objects produced by `addGeneInfo`, i.e. column 2 of the pipeline ExpressionSets corresponds to column one of an `addGeneInfo` ExpressionSet.

**Author(s)**

Tobias Verbeke, Steven Osselaer

**Examples**

```
library(ALL)
data(ALL)
a4ALL <- addGeneInfo(ALL)
head(featureData(a4ALL)$`Entrez ID`)
```

# Index

\* **manip**

addGeneInfo, [2](#)

addGeneInfo, [2](#)